Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1

			ckies i doke	er-Leanaye		Revised June 10, 2		
		Leas	e Name KING	, 		Well No1		
: Unit Letter	r <u>A</u> S	Sec22	Twp030N	Rge	010W API	# 30-045-09385		
Name of Reservoir or Pool			Type of Prod		Method of Prod	Prod Medium		
PC		Gas	Gas		,	Casing		
MV		Gas	Gas		ial Lift	Tubing		
		Pre-Flow S	Shut-In Pressu	ıre Data				
Upper Hour, Date, Shut-In Completion 4/13/2009			Length of Time Shut-In 203 hours		SI Press. PSIG Stabilized?(Yes or 116 Yes			
Lower Hour, Date, Shut-In 4/13/2009		,	Length of Time Shut-In 0 hours		ss. PSIG 234	Stabilized?(Yes or No) Yes		
	,	Flo	ow Test No. 1					
•	4/13/2009 Zone Producing (Upper or Lower): Lower							
Time Lapsed Time (date/time) Since*			SSURE Lower zone	Prod Zone Temperature	Remarks			
) AM	9	102	220	76	shut in psi			
) AM	33	107	225	76	shut in psi RCVD MAY 6 '09			
) AM	57	113	231	76	shut in psi OIL CONS. DIV.			
) AM	81	115	233	76	shut in psi DIST. 3			
) AM	105	116	234	76	plunger clock in drop time			
) AM	127	155	118	76	plunger clock in drop time			
0 AM	155	119	94	76	Well in afterflow FR/60 SP/114			
0 AM	179	199	120	76	well shutin in drop time			
0 AM	203	121	96	76	Well in afterflow FR50 SP 101			
during test								
BPOD Base	ed on:	Bbls. In	Hrs.		Grav.	GOR		
	MCFPD; Test t	hru (Orifice or N	Meter)					
Hour, Date, Sh	ut-in	Length	Length of Time Shut-In		ss. PSIG	Stabilized?(Yes or No)		
Hour, Date, Shut-In			Length of Time Shut-In			t .		
	PC MV Hour, Date, Sh 4/13/200 Hour, Date, Sh 4/13/200 : L AM	PC MV Hour, Date, Shut-In 4/13/2009 Hour, Date, Shut-In 4/13/2009 Lapsed Time Since* AM 9 AM 33 AM 57 AM 105 AM 105 AM 127 AM 155 AM 179 AM 203 during test BPOD Based on:	Name of Reservoir or Pool	Name of Reservoir or Pool	Name of Reservoir or Pool	Unit Letter		

(Continue on reverse side)

Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

Commenced at: Zone Producing (Upper or Lower)									
Time	Lapsed Time	PRESSURE		Prod Zone					
(date/time)	Since*	Upper zone	Lower zone	Temperature	!	Remarks			
,									
Production rate during Oil: BPOI		Bbls. In	Hrs.		Grav.	GOR			
Gas									
Remarks:		`	,						
I hereby certify that the information herein contained is true and complete to the best of my knowledge.									
Approved:	MAY 0 8 2009	20	Opera	tor: BR					
New Mexico Oil Conservation Division			Ву:	By: Richard Ivy					
By: Fally G. Rout			Title:	Multi-Skilled	•				
Title: Deputy Oil & Gas Inspector, District #3				Date: Tuesday, May 05, 2009					

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- 2 At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No 1, one zone of the dual completion shall be produced at the normal rate of production
- while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1 Procedure for Flow Test No 2 is to be the same as for Flow Test No 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests, immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data

24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)

5 Following completion of Flow Test No 1, the well shall again be shut-in, in accordance with Paragraph 3 above