

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

MAY 18 2009

Sundry Notices and Reports on Wells

Bureau of Land Management
Farmington Field Office

1. Type of Well
GAS

5. Lease Number
SF-077764

6. If Indian, All. or
Tribe Name

2. Name of Operator

BURLINGTON

RESOURCES OIL & GAS COMPANY LP

7. Unit Agreement Name

3. Address & Phone No. of Operator

P.O. Box 4289, Farmington, NM 87499

8. Well Name & Number
Schumacher 1A

9. API Well No.

30-045-26639

4. Location of Well, Footage, Sec., T, R, M

Unit C (NENW), 870' FNL & 1430' FWL, Section 17, T30N, R10W, NMPM

10. Field and Pool
Blanco Mesa Verde

11. County and State
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment

Type of Action

☒ Abandonment☐ Recompletion☐ Plugging☐ Casing Repair☐ Altering Casing☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut off☐ Conversion to Injection☐ Other -RCVD MAY 21 '09
OIL CONS. DIV.

DIST. 3

13. Describe Proposed or Completed Operations

5/6/09 MIRU A-Plus 10. Pump H2S Scavenger down csg.

5/7/09 Pump 25 bbls H2O dwn tbg & attempt to PT - test failed. PU rods & unseat pump. ND WH NU BOP & test- good test.

5/11/09 TOH w/2 3/8" tbg. PU csg scraper & TIH to 4510'. TOH w/scraper. PU cement retainer, TIH & set @ 4499'.

5/12/09 RIH w/fishing tool PU on standing valve & release H2O. Unseat & POOH w/SV. RD fishing equip. Load csg w/37 bbls H2O & circ clean w/another 113 bbls. PT csg to 500# 30/min - good test. Plug #1 (4499' - 4301') pumped 15 sx(18cf-3bbls) Class B Cement. Plug increased per BLM rep Mike Gilbreth. Load csg w/2 1/2 bbls H2O. Plug #2 (3744' - 3546') pumped 15 sx(18cf-3 bbl) Class B Cement. Load csg w/1 1/2 bbls H2O. Plug 3 (3383' - 2509') pumped 139 sx(164cf-29 bbls) Class B Cement w/2% CaCl. WOC. TIH tag TOC @ 2529'. (BLM rep requested to top off plug)

5/13/09 Load csg w/2 1/2 bbls H2O. Plug 3A 2529' - 2425') pumped 20 sx(24cf-4 bbls) Class B Cement. Load csg w/2 1/2 bbls H2O. Plug 4 (1773' - 1451') pumped 62 sx(73cf-13 bbls) Class B Cement. RU W/L. RIH & perf 3 holes @ 362'. RD W/L. Break circ Out BH w/10 bbls H2O. Circ clean. Plug 5 (362' - surface) pumped 153 sx (181cf-32 bbls) Class B Cement. Circ good cmnt out BH valve. WOC. ND BOP. Dig out WH. Cut off WH. Cmt in 7" down 15' & 2' in annulus. Top off & set P & A marker w/20 sx Cement. RD RR on 5/13/09.

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Staff Regulatory Technician Date 5/14/09

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

Date
MAY 20 2009

FARMINGTON FIELD OFFICE

NMCCD