This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator BR			Lease Name ZACHRY							Well No. 19E		
Location of We	ll: Unit L	etter O	Sec	12	Twp _	028N	Rg	je ()10W AF	PI# <u>30-045</u>	5-24357	
	Name of Reservoir or Pool		r Pool	Type of Prod				Method of Prod		Prod Medium		
Upper Completion	СН			Gas				Flow		Casing	Casing	
Lower Completion	DK .			Gas				Flow		Tubing	23/80 6240	
			Pr	e-Flow S	Shut-In	Pressu	re Data	-				
Upper Hour, Date, S		Shut-In		Length of Time Shut-In				SI Press. PSIG 188.3		Stabilized?	Stabilized?(Yes or No)	
Completion	5/11/2009			144 hours						Yes		
Lower Completion	Hour, Date, Shut-In			Length of Time Shut-In				SI Press. PSIG		Stabilized?(Yes or No)		
	5/11/2009			84 hours					252.1	Yes	ļ	
Commenced :	et: /14/2	009 12:00:00 F		Flo	w Test		oducina	(i Inner	or Lower): L	ower		
	711/2			DDEC			,					
Time (date/time	ارد	Lapsed Time Since*		PRESSURI Upper zone Low		r 7000	Prod Zone Temperature			Remarks		
(dato/time	5) 011100		Opp			ZONE			Tomano			
5/15/2009 12:48:00 PM 24		24		190.1 46.		6.8	64 R		RC	CVD MAY 20 '09		
5/16/2009 36			193.2 49.1		74 O		IL CONS. DIV.					
5/17/2009			197		16	73			DIST. 3			
Production rate		est										
Oil:BPOD Based on:			Bb	Bbls. InHrs.				Grav.		GOR	GOR	
Gas		MCFPD; Te	est thru (Or	ifice or M	leter)							
			R/I	id-Taet S	hut-In	Process	ro Data					
Upper Completion	Hour, Date, Shut-In			d-Test Shut-In Pressure Da Length of Time Shut-In			Jaca	SI Press. PSIG		Stabilized?	Stabilized?(Yes or No)	
Lower Completion	Hour, Date, Shut-In			Length of Time Shut-In			,	SI Press. PSIG		Stabilized?	(Yes or No)	

(Continue on reverse side)

Flow Test No. 2

Commenced at:	,	Zone Producing (Upper or Lower)							
Time	Lapsed Time	PRES	SURE	Prod Zone					
(date/time)	Since*	Upper zone	Lower zone	Temperature	·	Remarks			
	1								
						· .			
,						•			
	,								
Production rate during	g test D Based on:	Bbls. In	Hrs.		Grav.	GOR			
Gas	MCFPD; Test th	nru (Orifice or M	leter)						
Remarks:									
	- 								
I hereby certify that th	ne information herein c	ontained is true	and complete	to the best of	my knowledo	ge.			
	JUN 1 9 2009	20	Opera	tor: BR					
New Mexico Oil Conservation Division				Mitchell Sewell					
By:			Title:	Multi-Skilled	Operator				
Title: Depu	DODGLY On Grad mopoution				Tuesday, May 19, 2009				
,	District #3		an arma rates		,	•			

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days
- For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note, if, on an initial packer leakage test, a gas well is being flowed to the
- atmosphere due to lack of a pipeline connection the flow period shall be three hours

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight piessure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

Following completion of Flow Test No 1, the well shall again be shut-in, in accordance with Paragraph 3