

Burlington

## Current Schematic

ConocoPhillips

Well Name SAN JUAN 28-6 UNIT #205N

API # 30-039-30565

|                                   |                                           |                                  |                                |                                |                                     |
|-----------------------------------|-------------------------------------------|----------------------------------|--------------------------------|--------------------------------|-------------------------------------|
| API / UWI<br>3003930565           | Surface Legal Location<br>009-027N-006W-D | Field Name<br>MV/DK COM          | License No                     | State/Province<br>NEW MEXICO   | Well Configuration Type<br>VERTICAL |
| Ground Elevation (ft)<br>6,230.00 | Original KB Elevation (ft)<br>6,245.00    | KB-Ground Distance (ft)<br>15.00 | KB-Casing Flange Distance (ft) | KB-Tubing Hanger Distance (ft) |                                     |

Well Config: VERTICAL - Original Hole: 6/10/2009 6:08:54 PM

| ftKB (MD) | Schematic - Actual                                     | Frm Final |
|-----------|--------------------------------------------------------|-----------|
| 15        | Tubing Hanger, 4in, 4 70lbs/ft, J-55, 16 ftKB          |           |
| 16        |                                                        |           |
| 16        | Casing Hanger, 7in, 20 00lbs/ft, J-55, 16 ftKB         |           |
| 18        |                                                        |           |
| 18        | Casing Hanger, 4 1/2in, 11 60lbs/ft, J-55, 16 ftKB     |           |
| 19        |                                                        |           |
| 19        | Casing Head (Cameron), 9 5/8in, 18 ftKB                |           |
| 56        |                                                        |           |
| 56        | Casing Nipple, 9 5/8in, 32 30lbs/ft, H-40, 20 ftKB     |           |
| 232       |                                                        |           |
| 232       | Casing Pup Joint, 4 1/2in, 11 60lbs/ft, J-55, 56 ftKB  |           |
| 233       |                                                        |           |
| 233       | Casing Joints, 9 5/8in, 32 30lbs/ft, H-40, 232 ftKB    |           |
| 242       |                                                        |           |
| 242       | Surface Casing Cement, 15-233, 3/22/2009               |           |
| 473       |                                                        |           |
| 473       | SAW TOOTH COLLAR, 9 5/8in, 32 30lbs/ft, H-40, 233 ftKB |           |
| 2,289     |                                                        |           |
| 2,289     | Casing Joints, 4 1/2in, 11 60lbs/ft, J-55, 473 ftKB    |           |
| 2,292     |                                                        |           |
| 2,292     | Intermediate Casing Cement, 15-2,289, 3/26/2009        |           |
| 3,169     |                                                        |           |
| 3,169     | Casing Joints, 7in, 20 00lbs/ft, J-55, 2,289 ftKB      |           |
| 3,170     |                                                        |           |
| 3,170     | Stage-Tool, 7in, 20 00lbs/ft, J-55, 2,292 ftKB         |           |
| 3,211     |                                                        |           |
| 3,211     | Casing Joints, 7in, 20 00lbs/ft, J-55, 3,169 ftKB      |           |
| 3,212     |                                                        |           |
| 3,212     | Float Collar, 7in, 20 00lbs/ft, J-55, 3,170 ftKB       |           |
| 3,222     |                                                        |           |
| 3,222     | Casing Joints, 7in, 20 00lbs/ft, J-55, 3,211 ftKB      |           |
| 3,378     |                                                        |           |
| 3,378     | Intermediate Casing Cement, 2,289-3,212, 3/26/2009     |           |
| 3,388     |                                                        |           |
| 3,388     | Float Shoe, 7in, 20 00lbs/ft, J-55, 3,212 ftKB         |           |
| 4,460     |                                                        |           |
| 4,460     | Casing Joints, 4 1/2in, 10 50lbs/ft, J-55, 3,378 ftKB  |           |
| 4,792     |                                                        |           |
| 4,792     | Marker Joint, 4 1/2in, 10 50lbs/ft, J-55, 3,388 ftKB   |           |
| 4,872     |                                                        |           |
| 4,872     | Perforated, 4,460-4,792, 4/29/2009                     |           |
| 5,298     |                                                        |           |
| 5,298     | PERFORATED, 4,872-5,298, 4/29/2009                     |           |
| 6,950     |                                                        |           |
| 6,950     | Casing Joints, 4 1/2in, 10 50lbs/ft, J-55, 6,950 ftKB  |           |
| 6,960     |                                                        |           |
| 6,960     | Marker Joint, 4 1/2in, 10 50lbs/ft, J-55, 6,960 ftKB   |           |
| 7,130     |                                                        |           |
| 7,130     | Perforated, 7,130-7,316, 4/29/2009                     |           |
| 7,212     |                                                        |           |
| 7,212     |                                                        |           |
| 7,214     |                                                        |           |
| 7,214     |                                                        |           |
| 7,246     |                                                        |           |
| 7,246     |                                                        |           |
| 7,247     |                                                        |           |
| 7,247     |                                                        |           |
| 7,248     |                                                        |           |
| 7,248     |                                                        |           |
| 7,316     |                                                        |           |
| 7,316     |                                                        |           |
| 7,366     |                                                        |           |
| 7,366     |                                                        |           |
| 7,367     |                                                        |           |
| 7,367     |                                                        |           |
| 7,368     |                                                        |           |
| 7,368     |                                                        |           |
| 7,370     |                                                        |           |
| 7,370     |                                                        |           |

RCVD JUN 26 '09  
OIL CONS. DIV.

DIST. 3