	DIDEAU OF LAND MANA		Expire	s: July 31, 2010	
BUREAU OF LAND MANAGEMENT  SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.		5. Lease Serial No. NMNM28277			
abandoned w	ell. Use form 3160-3 (APD	) for such proposals.	V. II Malan, Million		
SUBMIT IN TRIPLICATE - Other instructions on reverse side.  I Type of Well Other Other			7. If Unit or CA/Agr	7. If Unit or CA/Agreement, Name and/or N	
			8. Well Name and No CARRACAS 17B 3		
2 Name of Operator Contact: VICKI DONAGHE ENERGEN RESOURCES CORPORA <b>HOM</b> ail: vdonaghe@energen.com		VICKI DONAGHEY genergen.com	9. API Well No. 30-039-30467-00-X1		
3a. Address 2010 AFTON PLACE FARMINGTON, NM 87401		3h. Phone No. (include area code Ph: 505-325-6800 Fx: 505-326-6112	) 10. Field and Pool, o BASIN FRUIT		
4 Location of Well (Footage, Sec., T, R., M., or Survey Description)		· · · · · · · · · · · · · · · · · · ·	11. County or Parish	11. County or Parish, and State	
Sec 17 T32N R4W SESW 802FSL 1853FWL 36.98160 N Lat, 107.28073 W Long			RIO ARRIBA COUNTY, NM		
12. CHECK API	PROPRIATE BOX(ES) TO	INDICATE NATURE OF 1	NOTICE, REPORT, OR OTHE	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
□ Notice of Intent	□ Acidize	Deepen	Production (Start/Resume)	□ Water Shut-C	
Subsequent Report	☐ Alter Casing	Fracture Treat	Reclamation	Well Integrity	
Final Abandonment Notice	Casing Repair Change Plans	☐ New Construction☐ Plug and Abandon	☐ Recomplete ☐ Temporarily Abandon	<b>⊠</b> Other	
I man Abandonment Notice	1 —				
13. Describe Proposed or Completed C	Convert to Injection	Plug Back	☐ Water Disposal	roximate duration there	
If the proposal is to deepen directic Attach the Bond under which the w following completion of the involvesting has been completed. Final determined that the site is ready for 07/07/09. Drill 6-25" hole to 4 Halliburton. Cement with 64 150 sks Class G, 1/4#/sk flocement. Will run temperature	operation (clearly state all pertinen in ally or recomplete horizontally, york will be performed or provide ed operations. If the operation res Abandonment Notices shall be file final inspection.)  4763'. Run 108 jts. 7.0" 23# 5 sks Class G, 2% CaCl2, 1 cele (1436 cu.ft.). Plug down es survey. NU BOP. Test ca	t details, including estimated starting two subsurface locations and meast the Bond No on file with BLM/BL ults in a multiple completion or recidency after all requirements, included the subsurface of the subsu	g date of any proposed work and appirured and true vertical depths of all per A. Required subsequent reports shall to ompletion in a new interval, a Form 3 ding reclamation, have been complete [763]. RU le tailed by id not circulate	tinent markers and zone ne filed within 30 days 160-4 shall be filed onc	
If the proposal is to deepen directic Attach the Bond under which the w following completion of the involvesting has been completed. Final determined that the site is ready for 07/07/09. Drill 6.25" hole to 4 Halliburton. Cement with 64 150 sks Class G, 1/4#/sk flocement. Will run temperature to 250 psi, low and 1500 psi.	Operation (clearly state all pertinen in ally or recomplete horizontally, york will be performed or provide ed operations. If the operation res Abandonment Notices shall be file final inspection.)  1763'. Run 108 jts. 7.0" 23# 5 sks Class G, 2% CaCl2, 1 cele (1436 cu.ft.). Plug down es survey. NU BOP. Test cale, high, 15 minutes - ok.	t details, including estimated starting two subsurface locations and meast the Bond No on file with BLM/BL ults in a multiple completion or recidency after all requirements, included the subsurface of the subsu	g date of any proposed work and apply ured and true vertical depths of all per A. Required subsequent reports shall to ompletion in a new interval, a Form 3 ding reclamation, have been complete [763]. RU le tailed by id not circulate 5 - ok. Test BOP	tinent markers and zone filed within 30 days 160-4 shall be filed one d, and the operator has	
If the proposal is to deepen directic Attach the Bond under which the w following completion of the involvesting has been completed. Final determined that the site is ready for 07/07/09. Drill 6-25" hole to 4 Halliburton. Cement with 64 150 sks Class G, 1/4#/sk flocement. Will run temperature to 250 psi, low and 1500 psi. Temperature survey - TOC (	pperation (clearly state all pertinent on ally or recomplete horizontally, york will be performed or provide ed operations. If the operation reshandonment Notices shall be filed final inspection.)  4763'. Run 108 jts. 7.0" 23# 5 sks Class G, 2% CaCl2, 1 cele (1436 cu.ft.). Plug down es survey. NU BOP. Test called, high, 15 minutes - ok.	t details, including estimated starting two subsurface locations and meast the Bond No on file with BLM/BL ults in a multiple completion or recidency after all requirements, included the subsurface of the subsu	g date of any proposed work and approved and true vertical depths of all per A. Required subsequent reports shall to ompletion in a new interval, a Form 3 ding reclamation, have been complete (63'. RU) le tailed by id not circulate 5 - ok. Test BOP	tinent markers and zone filed within 30 days 160-4 shall be filed one d, and the operator has	
If the proposal is to deepen directic Attach the Bond under which the w following completion of the involvesting has been completed. Final determined that the site is ready for 07/07/09. Drill 6.25" hole to 4 Halliburton. Cement with 64 150 sks Class G, 1/4#/sk flocement. Will run temperature to 250 psi, low and 1500 psi.	pperation (clearly state all pertinent on ally or recomplete horizontally, york will be performed or provide ed operations. If the operation reshandonment Notices shall be filed final inspection.)  4763'. Run 108 jts. 7.0" 23# 5 sks Class G, 2% CaCl2, 1 cele (1436 cu.ft.). Plug down es survey. NU BOP. Test called, high, 15 minutes - ok.	t details, including estimated starting two subsurface locations and meast the Bond No on file with BLM/BL ults in a multiple completion or recidency after all requirements, included the subsurface of the subsu	g date of any proposed work and apply ured and true vertical depths of all per A. Required subsequent reports shall to ompletion in a new interval, a Form 3 ding reclamation, have been complete [763]. RU le tailed by id not circulate 5 - ok. Test BOP	tinent markers and zone filed within 30 days 160-4 shall be filed one d, and the operator has	
If the proposal is to deepen directic Attach the Bond under which the w following completion of the involvesting has been completed. Final determined that the site is ready for 07/07/09. Drill 6-25" hole to 4 Halliburton. Cement with 64 150 sks Class G, 1/4#/sk flocement. Will run temperature to 250 psi, low and 1500 psi. Temperature survey - TOC (	operation (clearly state all pertinen nally or recomplete horizontally, york will be performed or provide ed operations. If the operation res Abandonment Notices shall be file final inspection.)  4763'. Run 108 jts. 7.0" 23#5 sks Class G, 2% CaCl2, 1 cele (1436 cu.ft.). Plug down survey. NU BOP. Test ca, high, 15 minutes - ok.	t details, including estimated starting the Bond No on file with BLM/BL ults in a multiple completion or recidently after all requirements, included the starting of the start	g date of any proposed work and approved and true vertical depths of all per A. Required subsequent reports shall to ompletion in a new interval, a Form 3 ding reclamation, have been complete (63'. RU) le tailed by id not circulate 5 - ok. Test BOP	tinent markers and zone filed within 30 days 160-4 shall be filed one d, and the operator has 13 '09 S. DIV.	
If the proposal is to deepen directic Attach the Bond under which the w following completion of the involvesting has been completed. Final determined that the site is ready for 07/07/09. Drill 6.25" hole to 4 Halliburton. Cement with 64 150 sks Class G, 1/4#/sk flocement. Will run temperature to 250 psi, low and 1500 psi.  Temperature survey - TOC 6 Will drop off survey @ BLM.  **Manual OCS w/6**  **Juvale OCS w/6**  **Juv	operation (clearly state all pertinentially or recomplete horizontally, prork will be performed or provide ed operations. If the operation rest Abandonment Notices shall be filed final inspection.)  4763'. Run 108 jts. 7.0" 23# 5 sks Class G, 2% CaCl2, 1 cele (1436 cu.ft.). Plug down as survey. NU BOP. Test cate, high, 15 minutes - ok.  1700'  18 frue and entrect Electronic Submission #1 For ENERGEN RESOL	t details, including estimated starting the Bond No on file with BLM/BL ults in a multiple completion or recidently after all requirements, included the starting of the start	g date of any proposed work and apply ured and true vertical depths of all per A. Required subsequent reports shall completion in a new interval, a Form 3 ding reclamation, have been complete 763°. RU le tailed by id not circulate 6 - ok. Test BOP  RCUD JUL OIL CON	tinent markers and zone filed within 30 days 160-4 shall be filed one d, and the operator has 13 '09 S. DIV.	
If the proposal is to deepen directic Attach the Bond under which the w following completion of the involvesting has been completed. Final determined that the site is ready for 07/07/09. Drill 6.25" hole to 4 Halliburton. Cement with 64 150 sks Class G, 1/4#/sk flocement. Will run temperature to 250 psi, low and 1500 psi.  Temperature survey - TOC 6 Will drop off survey @ BLM.  **Manual OCS w/6**  **Juvale OCS w/6**  **Juv	Operation (clearly state all pertinentially) or recomplete horizontally, is rock will be performed or provide ed operations. If the operation rest Abandonment Notices shall be filed final inspection.)  4763'. Run 108 jts. 7.0" 23# 5 sks Class G, 2% CaCl2, 1 cele (1436 cu.ft.). Plug down as survey. NU BOP. Test cath high, 15 minutes - ok.  4700'  48 Junior American Carrect Catherican Catherine Submission #1 For ENERGEN RESOLommitted to AFMSS for process.	t details, including estimated starting the Bond No on file with BLM/BL ults in a multiple completion or recidently after all requirements, included a starting to the Bond No on file with BLM/BL ults in a multiple completion or recidently after all requirements, included a starting to 12-55 LT&C casing, set @ 47 0#/sk gilsonite, 1/4#/sk floce in @ 1:45 am on 07/08/09. Dising to 1200 psi - 30 minutes a sing to 1200 psi - 30 minutes a starting to 1200 psi - 30	g date of any proposed work and apply ured and true vertical depths of all per A. Required subsequent reports shall completion in a new interval, a Form 3 ding reclamation, have been complete 763°. RU le tailed by id not circulate 6 - ok. Test BOP  RCUD JUL OIL CON	tinent markers and zone filed within 30 days 160-4 shall be filed one d, and the operator has 13 '09 S. DIV.	
If the proposal is to deepen directic Attach the Bond under which the w following completion of the involvesting has been completed. Final determined that the site is ready for 07/07/09. Drill 6.25" hole to 4 Halliburton. Cement with 64 150 sks Class G, 1/4#/sk flocement. Will run temperature to 250 psi, low and 1500 psi.  Temperature survey - TOC 6 Will drop off survey @ BLM.  Will drop off survey @ BLM.  14. Thereby certify that the foregoing Communication of the property	Operation (clearly state all pertinentially) or recomplete horizontally, is rock will be performed or provide ed operations. If the operation rest Abandonment Notices shall be filed final inspection.)  4763'. Run 108 jts. 7.0" 23# 5 sks Class G, 2% CaCl2, 1 cele (1436 cu.ft.). Plug down as survey. NU BOP. Test cath high, 15 minutes - ok.  4700'  48 Junior American Carrect Catherican Catherine Submission #1 For ENERGEN RESOLommitted to AFMSS for process.	t details, including estimated starting the Bond No on file with BLM/BL ults in a multiple completion or recidently after all requirements, included a starting to the Bond No on file with BLM/BL ults in a multiple completion or recidently after all requirements, included a starting to 12-55 LT&C casing, set @ 47 0#/sk gilsonite, 1/4#/sk floce in @ 1:45 am on 07/08/09. Dising to 1200 psi - 30 minutes a sing to 1200 psi - 30 minutes a starting to 1200 psi - 30	g date of any proposed work and apply ured and true vertical depths of all per A. Required subsequent reports shall completion in a new interval, a Form 3 ding reclamation, have been complete (F63'. RU)  le tailed by id not circulate (F64). Test BOP  RCVD JUL OIL CON  DIST  Information System to the Farmington (07/09/2009 (09TLS0004SE))  ATORY ANALYST	tinent markers and zone filed within 30 days 160-4 shall be filed one d, and the operator has 13 '09 S. DIV.	
If the proposal is to deepen directic Attach the Bond under which the w following completion of the involvesting has been completed. Final determined that the site is ready for 07/07/09. Drill 6-25" hole to 4 Halliburton. Gement with 64 150 sks Class G, 1/4#/sk flocement. Will run temperature to 250 psi, low and 1500 psi.  Temperature survey - TOC (Will drop off survey @ BLM.)  Will drop off survey @ BLM.	pperation (clearly state all pertinent on ally or recomplete horizontally, york will be performed or provide ed operations. If the operation rest Abandonment Notices shall be filed final inspection.)  4763'. Run 108 jts. 7.0" 23# 5 sks Class G, 2% CaCl2, 1 cele (1436 cu.ft.). Plug down es survey. NU BOP. Test cath high, 15 minutes - ok.  1700'  1700'  Light Full Advanced to Electronic Submission #7 For ENERGEN RESOLOMMITTED TO CONAGHEY  C Submission)	t details, including estimated starting the Bond No on file with BLM/BL ults in a multiple completion or recidently after all requirements, included a starting the Bond No on file with BLM/BL ults in a multiple completion or recidently after all requirements, included a starting to 12-55 LT&C casing, set @ 47 0#/sk gilsonite, 1/4#/sk floce in @ 1:45 am on 07/08/09. Dising to 1200 psi - 30 minutes a starting to 1200 psi - 30 minutes a starting by TROY SALYERS on Title REGUL	g date of any proposed work and appropriete and true vertical depths of all per A. Required subsequent reports shall completion in a new interval, a Form 3 ding reclamation, have been complete (FG3'). RU le tailed by id not circulate (FG4). Test BOP  RCVD JUL OIL COMPLETE	tinent markers and zone filed within 30 days 160-4 shall be filed one d, and the operator has 13 '09 S. DIV.	
If the proposal is to deepen directic Attach the Bond under which the w following completion of the involvesting has been completed. Final determined that the site is ready for 07/07/09. Drill 6-25" hole to 4 Halliburton. Gement with 64 150 sks Class G, 1/4#/sk flocement. Will run temperature to 250 psi, low and 1500 psi.  Temperature survey - TOC (Will drop off survey @ BLM.)  Will drop off survey @ BLM.	pperation (clearly state all pertinent on ally or recomplete horizontally, york will be performed or provide ed operations. If the operation rest Abandonment Notices shall be filed final inspection.)  4763'. Run 108 jts. 7.0" 23# 5 sks Class G, 2% CaCl2, 1 cele (1436 cu.ft.). Plug down es survey. NU BOP. Test cath high, 15 minutes - ok.  1700'  1700'  Light Full Advanced to Electronic Submission #7 For ENERGEN RESOLOMMITTED TO CONAGHEY  C Submission)	t details, including estimated starting the Bond No on file with BLM/BL ults in a multiple completion or recidently after all requirements, included the starting of the BLM Casing, set @ 47 0#/sk gilsonite, 1/4#/sk floce in @ 1:45 am on 07/08/09. Dising to 1200 psi - 30 minutes are singly the BLM Wells of the starting by TROY SALYERS on Title REGUIDATE OF STATE	g date of any proposed work and appured and true vertical depths of all per A. Required subsequent reports shall to ompletion in a new interval, a Form 3 ding reclamation, have been completed (63'). RU le tailed by id not circulate (6 - ok. Test BOP)  I Information System to the Farmington (07/09/2009 (09TLS0004SE))  ATORY ANALYST	tinent markers and zone filed within 30 days 160-4 shall be filed one d, and the operator has 13 '09 S. DIV.	

\*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\*