UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0135
Expires July 31, 2010

SUNDRY NOTICES AND REPORTS ON WERES CENTER

Lease Serial No. NMNM30015

Do not use till abandoned we		will as to so antas an	AED		
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on reverse side. Bureau of Land Management				6. If Indian, Allottee of	or Tribe Name
				7. If Unit or CA/Agreement, Name and/or No. 8. Well Name and No	
Type of Well					
Oil Well Gas Well Other				CARRACAS 18B	1
2. Name of Operator ENERGEN RESOURCES CO			9. API Well No 30-039-30483-00-X1		
2010 AFTON PLACE Ph: 505.		3b Phone No. (include area co Ph: 505.324.4136 Fx: 505.326.6112	de)	10. Field and Pool, or Exploratory BASIN FRUITLAND COAL	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, and State	
Sec 18 T32N R4W SWSE 570 36.89098 N Lat, 107.29289 W			RIO ARRIBA C	OUNTY, NM	
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE NATURE OF	F NOTICE, RE	PORT, OR OTHER	R DATA
TYPE OF SUBMISSION		ТҮРЕ			
Notice of Intent	□ Acidize	Deepen	□ Product	ion (Start/Resume)	□ Water Shut-Off
_	☐ Alter Casing	☐ Fracture Treat	□ Reclam	ation	☐ Well Integrity
Subsequent Report	Casing Repair	New Construction	□ Recomp	olete	Other
☐ Final Abandonment Notice	Change Plans	☐ Plug and Abandon	☐ Tempor	arily Abandon	
	Convert to Injection	□ Plug Back	□ Water I	Disposal	
07/21/09 Drill 8.75" hole to 46 Halliburton. Cement with 620 tailed by 150 sky. Class C. 174	sks Howco Light, 6% gel,	2% CaCl2, 10#/sk gilsonite	990. KU 1/2#/sk floce	le	
Circulate 25 bbls cement to suminutes & to 2000 psi, high -	urface. WOC. RD Hallibur	Plug down @ 7:45 pm on 0 ton. NU BOP. Test BOP to)7/21/09. o 250 psi, low -	-5	
Circulate 25 bbls cement to su	urface. WOC. RD Hallibur	Plug down @ 7:45 pm on 0 ton. NU BOP. Test BOP to)7/21/09. o 250 psi, low -	-5	
Circulate 25 bbls cement to su	urface. WOC. RD Hallibur	Plug down @ 7:45 pm on 0 ton. NU BOP. Test BOP to)7/21/09. o 250 psi, low -	RCVD JUL	
Circulate 25 bbls cement to suminutes & to 2000 psi, high - 2	s true and correct. Electronic Submission #7	Plug down @ 7:45 pm on 0 ton. NU BOP. Test BOP to test casing to 1200 psi - 30 test casing to 1200 psi - 30 years	7/21/09. 250 psi, low - minutes - ok. /ell Information to the Farmin	RCVD JUL OIL CON: DIST	
Circulate 25 bbls cement to suminutes & to 2000 psi, high - 2	s true and correct. Electronic Submission #7 For ENERGEN RESOU	Plug down @ 7:45 pm on 0 ton. NU BOP. Test BOP to test casing to 1200 psi - 30 test casing to 1200 psi - 30 years	07/21/09. 0 250 psi, low - 0 minutes - ok. 0 minutes - ok.	RCVD JUL OIL CON: DIST	
Circulate 25 bbls cement to suminutes & to 2000 psi, high - 2	s true and correct. Electronic Submission #7 For ENERGEN RESOUMMITTED TO SUBMISSION #7 FOR ENERGEN RESOUMMITTED TO SUBMISSION #7 ENERGEN RESOUMMITTED TO SUBMISSION #7 ENERGEN RESOUMMITTED TO SUBMISSION)	Plug down @ 7:45 pm on 0 ton. NU BOP. Test BOP to test casing to 1200 psi - 30 rest casing to 1200 psi - 30 rest casing by the BLM WIRCES CORPORATION, sen passing by TROY SALYERS on Title REGIONATION.	7/21/09. 2 250 psi, low - 0 minutes - ok. /ell Information 1 to the Farmin 1 to 1 the Farmin 1 o 7/23/2009 (0 ULATORY AN	RCVD JUL OIL CON: DIST System gton 9TLS0010SE) ALYST	
Circulate 25 bbls cement to suminutes & to 2000 psi, high - 2	s true and correct. Electronic Submission #7 For ENERGEN RESOUMMITTED TO SUBMISSION #7 FOR ENERGEN RESOUMMITTED TO SUBMISSION #7 ENERGEN RESOUMMITTED TO SUBMISSION #7 ENERGEN RESOUMMITTED TO SUBMISSION)	Plug down @ 7:45 pm on 0 ton. NU BOP. Test BOP to test casing to 1200 psi - 30 test casing to 1200 psi - 30 psi	7/21/09. 250 psi, low - 250 psi, low	RCVD JUL OIL CON: DIST System gton 9TLS0010SE) ALYST	
Circulate 25 bbls cement to suminutes & to 2000 psi, high - 2000 psi, high	s true and correct. Electronic Submission #7 For ENERGEN RESOUMMITTED TO SUBMISSION #7 FOR ENERGEN RESOUMMITTED TO SUBMISSION #7 ENERGEN RESOUMMITTED TO SUBMISSION #7 ENERGEN RESOUMMITTED TO SUBMISSION)	Plug down @ 7:45 pm on 0 ton. NU BOP. Test BOP to test casing to 1200 psi - 30 test casing to 1200 psi - 30 Test Corporation, sensing by TROY SALYERS of Title REGION Date 07/23 TROY S	7/21/09. 2 250 psi, low - 0 minutes - ok. /ell Information 1 to the Farmin 1 to 1 the Farmin 1 o 7/23/2009 (0 ULATORY AN	RCVD JUL OIL CON: DIST System gton 9TLS0010SE) ALYST	

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.