This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator COF)			Leas	e Name SAN	JUAN 32	-7 UN	IIT	Well No. 39	
Location of We	ell: Unit	Letter K	Sec	23	Twp 032N	N Rg	е	007W AF	PI # 30-045-11298	
	Name of Reservoir or Pool				Type of Prod			Method of Prod	Prod Medium	
Upper Completion	MV			Gas	Gas				Tubing	
Lower Completion	DK			Gas	Gas				Tubing	
			Р	re-Flow S	Shut-In Pressi	ure Data				
Upper	Hour, Date, Shut-In				Length of Time Shut-In			s. PSIG	Stabilized?(Yes or No)	
Completion	6/8/2009			131	131 hours			210	Yes	
Lower	Hour, Date, Shut-In				Length of Time Shut-In			ss. PSIG	Stabilized?(Yes or No)	
Completion	6/8/2009			83 h	ours		329		Yes	
Commenced	at: /11	/2009 11:00:0	0 AM	Flo	w Test No. 1 Zone Pro	oducing (I	Jppei	r or Lower): Lo	ower	
Time (date/time)		Lapsed Time Since* Uppe		PRES	PRESSURE Pro					
				per zone	Lower zone	e Temperature		Remarks		
6/11/2009 11:00:00 AM		0		210	310	67		started flowing lower zone		
6/12/2009 10:30:00 AM		23		211	143	64		lower zone flowed below upper zone psi by greater than 20% test complete.		
6/13/2009 11:00:00 AM 48			213	147		3 re check pressure		es		
Production rate	during	test						`		
Dil:BPOD Based on:Bbls			ols. In	s. InHrs		Grav.		GOR		
Gas		MCFPD;	Test thru (O	rifice or M	eter)					
			M	id-Test S	hut-In Pressu	ıre Data				
Upper Completion	Hour, Date, Shut-In			Length o	Length of Time Shut-In			s. PSIG	Stabilized?(Yes or No)	
•								RCUD JUN 23 '09		
Lower Completion	Hour, Date, Shut-In			Length o	Length of Time Shut-In		SI Press. PSIG		Stabilized?(Yes or No)	
									IL CONS. DIV.	

Flow Test No. 2

Commenced at:			Zone Producing (Upper or Lower)								
Time	Lapsed Time	PRESSURE		Prod Zone							
(date/time)	Since*	Upper zone	Lower zone	Temperature		Remarks					
	,										
Production rate du	-	Phlo In	Lleo	,		GOR					
	POD Based on:										
Gas	MCFPD; Test th	ru (Orifice or M	leter)								
Remarks:											
I hereby certify that the information herein contained is true and complete to the best of my knowledge.											
Approved: J	UL 2 2 2009	20	Operat	or: COP							
New Mexico Oil	Conservation Division		Ву:	Chad Comer							
Dy: `	G. Roll		Title: _	Multi-Skilled	Operator						
Title: Dep	Deputy Oil & Gas Inspector, District #3				Date: Monday, June 22, 2009						

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days tollowing recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the
 Dryssion in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5 Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1 Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests, immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests, immediately prior to the beginning of each flow period data opproximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests; all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Dission on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).