This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator BR				Lease Name SAN JUAN 30-6 UNIT							Well No. 76A		
Location of We	ell: Unit	Letter _	0	Sec	24	Twp _	030N	R	ge	007W	API	# 30-039-25675	
	Name of Reservoir or Pool				Type of Prod				Method of Prod			Prod Medium	
Upper Completion	MV				Gas				Flow			Tubing	
Lower Completion					Gas				Flow			Tubing	
Pre-Flow Shut-In Pressure Data													
Upper	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG			Stabilized?(Yes or No)	
Completion	6/19/2009				151 hours				214.2			Yes	
Lower	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG			Stabilized?(Yes or No)	
Completion					104 hours				408.5			Yes	
Flow Test No. 1													
Commenced	at: 6/2	3/2009 8:	00:00 AM			Z	one Pro	ducing	(Upper	r or Lower	r): Low	er	
Time Lapsed Time				PRESSURE			Prod	Prod Zone					
(date/time)		'a		Upp	er zone	Lower	zone	Tempe	erature		l	Remarks	
6/24/2009 8:00:00 AM			24		214.4	154	4.6	65		LP = 166.4; 20% Crossover Achieved		Crossover Achieved	
6/25/2009 7:32:	3/25/2009 7:32:00 AM 47		2	214.6		2.2	65		LP = 158.1; Test Completed				
Production rate	e during	test											
Oil: BPOD Based on:			Bbl	Bbls. In			(Grav.		GOR		
Gas	·	MCF	PD; Test	thru (Orit	fice or M	leter) _		***************************************					
				Mic	d-Test S	ihut-In F	Pressu	re Data	l				
Upper Completion	Hour, Date, Shut-In				Length of Time Shut-In			. J Dutt	SI Press. PSIG			Stabilized?(Yes or No)	
Lower Completion	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG			Stabilized?(Yes or No)	

(Continue on reverse side)





Flow Test No. 2

		FIC	W Test No. 2							
Commenced at:			Zone Pro	oducing (Uppe	er or Lower)					
Time	Lapsed Time	PRES	SURE	Prod Zone		ينين كالمناطقة فالم الجداوات والمقادات المائمة المناطقة ا				
(date/time)	Since*	Upper zone	Lower zone	Temperature		Remarks				
roduction rate durin	g test D Based on:	Bbls. In	Hrs.		Grav.	GOR				
as	MCFPD; Test thru (Orifice or Meter)									
emarks:										
				4 - 4b - 1 4 - 6						
-	ne information herein o	contained is true	and complete	to the best of	my knowledge	•				
pproved: JUL ?	proved: JUL 2 3 2009 20			Operator: BR						
	onservation Division		Ву:	Dustin McEl	reath					
y: Jahq. Col	Title:	Title: Multi-Skilled Operator								
itle: Dep	e: Deputy Oil & Gas Inspector,				Wednesday, July 01, 2009					
		PHUTOT MEWALVICO	DIOVED LEAVACE	TEST METALICATE	N. I.O.					

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- 6 Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7 Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have pregnally shown questionable test data.
- which have previously shown questionable test data.

 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)