submitted in lieu of Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	Sundry Notices and Report	s on Wells			
				5.	Lease Number
1.	Type of Well GAS			6.	I-22-IND-2772 If Indian, All. or Tribe Name
2. Name of Operator				7.	Ute Mountain Ute Unit Agreement Name Ute Mtn Ute
	BURLINGTON BESON &	CAS COMDANV I D			
3.	RESCURCES OIL & GAS COMPANY LP 3. Address & Phone No. of Operator				Well Name & Number Ute Mtn Ute #50
	PO Box 4289, Farmington, NM	87499 (505) 326-9700	•	9.	API Well No.
				-	30-045-29548
4.	Location of Well, Footage, Sec.,	T, R, M		10.	Field and Pool
JH.	Surf: Unit F (SENW), 1800' FNL & 1850' FWL, Sec. 22, T32N, R14W, NMPM 11.				Hovo Vistorial r mosa, Rico Sand, Cutler Sand County and State San Juan, NM
12.	CHECK APPROPRIATE BOX	TO INDICATE NATURE	OF NOTICE, REPORT, O	THER	DATA
		of Action Abandonment	Change of Plans	х	
		Recompletion	New Construction		
	Subsequent Report	Plugging	Non-Routine Fracturing		
		Casing Repair	Water Shut off		
	Final Abandonment	Altering Casing	Conversion to Injection		
13 .	Describe Proposed or Complete	d Operations			
cor	rlington Resources is requesting a valitioner type system. Please exten Estandard.				
301	standard.		SEE ATTACHED BOTTONS OF APPROVAL		RCVD AUG 12'09 OIL CONS. DIV.
14. I hereby certify that the foregoing is true and correct.					DIST. 3
Sig	ned Patsy Clus	Patsy	Clugston Title Sr. Regulate	ory Spe	<u>cialist</u> Date <u>5/19/09</u>
AP CC Title	nis space for Federal or State Office PROVED BY (S) DAN F ONDITION OF APPROVAL, if any Is U.S.C Section 1001, makes it a crime for any person k inted States any false, fictitious or fiaudulent statements o	RABINOVITE 46 /: nowingly and willfully to make any department		FC	AUG 1 0 2009

receved

MAY 2 1 2009

Bureau of Land Management Durango, Colorado



Conditions of Approval:

- 1. Isolating flow conditioners must be installed per manufacturer specifications.
- 2. The isolating flow conditioner make, model, and location must be available on site at all times.
- 3. Thermometer wells must be placed downstream of the orifice in compliance with AGA 3, (1985).
- 4. If the final review of the isolating flow conditioners by the BLM results in installation requirements different from the manufacturer specifications, you will be required to retrofit your installations to BLM standards. If needed, you will have to replace the meter run with one that complies with AGA 3, (1985).
- 5. A Subsequent Report Sundry Notice must be submitted for each well that has had an isolating flow conditioner installed in the meter run. This must be done within 10 days after the installation indicating date of installation. Attached to the Subsequent Report will be an "As Built" schematic diagram for the meter run, including exact measurements of the configuration and all components of the primary element. The Subsequent Report will also identify the type of meter and the isolating flow conditioner installed.