This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## **Oil Conservation Division**

## Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

perator COP				Lease	Name STOF	REY C LS		Well No7	
ocation of We	ll: Unit	Letter B	Sec	27	Twp028N	Rge	009W API	# 30-045-07198	
	Name of Reservoir or Pool			Type of Prod			Method of Prod	Prod Medium	
Upper Completion	PC			Gas	Gas		cial Lift	Tubing	
Lower Completion	MV			Gas		Artifi	cial Lift	Tubing	
				Pre-Flow S	hut-In Pressu	ıre Data			
Upper Completion	Hour, Date, Shut-In 8/24/2009			81 h	Length of Time Shut-In 81 hours		ess. PSIG 117	Stabilized?(Yes or No) Yes	
Lower Completion	Hour, Date, Shut-In 8/24/2009			Length of Time Shut-In O hours		SI Pre	ess. PSIG 152	Stabilized?(Yes or No) Yes	
				Flo	w Test No. 1				
Commenced a	at:	8/24	/2009		Zone Producing (Upper or Lower): Lower				
Time (date/time)		Lapsed Time Since* Up		PRES Jpper zone	SURE Lower zone	Prod Zone Temperature	e	Remarks	
8/24/2009 12:27:00 PM 12			117	151	78	Stabilized lower # 151 upper zone 117 #			
8/25/2009 2:41:00 PM 38			117	78	89	Upper zone held at 117 psi			
8/26/2009 8:20:00 AM 56			117	77	86	Upper zone holdi	ng at 117 psi		
8/27/2009 9:02:00 AM 81			117	60	88 Upper zone held		at 117 psi		
roduction rate	during	test					,		
il:	:BPOD Based on:			Bbls. InHrs.			Grav.	GOR	
as		MCFPD	; Test thru	(Orifice or M	leter)			<u> </u>	
				Mid-Test S	hut-In Pressu	ıre Data	•		
Upper Completion	Hour, Date, Shut-In 8/24/2009			Length of Time Shut-In		SI Press. PSIG		Stabilized?(Yes or No) Yes	
Lower Completion	Hour, Date, Shut-In 8/24/2009			Length of Time Shut-In O hours		SI Press. PSIG		Stabilized?(Yes or No) Yes	

(Continue on reverse side)

RCVD AUG 31 '05 OIL COMS. DIV.

DIST. 3

1 Toddollon I	rate daring test							
Oil:	BPOD Based on:	Bbls. In	Hrs	Grav.	GOR			
Gas	MCFPD; Test	thru (Orifice or Me	ter)					
Remarks:	'							
I hereby cer	tify that the information herein	contained is true a	and complete to the	best of my knowled	ge.			
Approved:	SEP 1 8 2009	20	·	COP				
	xico Oil Conservation Division		By: Bren	t Hottell	,			
By:	h C. ROS		Title: Multi	Title: Multi-Skilled Operator				
Title:	Deputy Oil & Gas Insp District #3	ector,	Date: Frida	y, August 28, 2009				

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure

for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall

7 Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests; immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each

flow period, at least one time during each flow period (at approximately the midway point) and immediately prior

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and

to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells

completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required

The results of the above-described tests shall be filed in triplicate within 15 days after completion of the
test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on

Northwest New Mexico Packet Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)

once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual

remain shut-in while the zone which was previously shut-in is produced

which have previously shown questionable test data.

above being taken on the gas zone

Production rate during test

requested by the Division.

A packer leakage test shall be commenced on each multiply completed well within seven days after actual

Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or

chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when

completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion

2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the

Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified

stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided

4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the

Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3

however, that they need not remain shut-in more than seven days

atmosphere due to lack of a pipeline connection the flow period shall be three hours

The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure