Office	ico Form C-103
<u>District I</u> Energy, Minerals and Natura	1 Resources June 19, 2008
1625 N. French Dr., Hobbs, NM 88240	WELL API NO. 30-039-30479
District II 1301 W. Grand Ave, Artesia, NM 88210 OIL CONSERVATION I	DIVISION 5. Indicate Type of Lease
District III 1220 South St. France 1000 River Property 1220 River Prop	is Dr. STATE FEE X
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 875	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr , Santa Fe, NM 87505	FEE
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUC DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR	
PROPOSALS.) 1. Type of Well: Oil Well Gas Well X Other	8. Well Number 25C
2. Name of Operator	9. OGRID Number 120782
Williams Production Company, LLC.	
3. Address of Operator	10. Pool name or Wildcat
P.O. Box 640 – Aztec, NM 87410 634-4208	Blanco MV/Basin MC/Basin DK
4. Well Location	
Unit LetterN_:1130feet from theSouth line an	
	Range 6W NMPM Rio Arriba County
11. Elevation (Show whether DR, K	PKB, RT, GR, etc.)
6154' GR	
12 Choole Ammonmisto Poy to Indicate Not	area of Nation Donart or Other Date
12. Check Appropriate Box to Indicate Nat	ure of Notice, Report of Other Data
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK ☐ ALTERING CASING ☐
_	COMMENCE DRILLING OPNS. P AND A
_	CASING/CEMENT JOB
DOWNHOLE COMMINGLE	
	OTHER: FINAL CASING
OTHER:	OTHER: FINAL CASING rtinent details, and give pertinent dates, including estimated date
	rtinent details, and give pertinent dates, including estimated date
OTHER: 13. Describe proposed or completed operations. (Clearly state all per of starting any proposed work). SEE RULE 1103. For Multiple	rtinent details, and give pertinent dates, including estimated date
OTHER: 13. Describe proposed or completed operations. (Clearly state all perof starting any proposed work). SEE RULE 1103. For Multiple or recompletion.	rtinent details, and give pertinent dates, including estimated date
OTHER: 13. Describe proposed or completed operations. (Clearly state all perof starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ', 0800 HRS.	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion
OTHER: 13. Describe proposed or completed operations. (Clearly state all perof starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ', 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50", 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152', FC	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616'
OTHER: 13. Describe proposed or completed operations. (Clearly state all perof starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ', 0800 HRS.	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER
OTHER: 13. Describe proposed or completed operations. (Clearly state all perof starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ′, 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50", 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152′, FC PRESSURE TEST LINES TO 3000 PSI. CEMENT 4.1/2" CSG.PUMP 20BBLS (590sx (826 cu.ft.) of Fraccem +0.8% Halad-9+0.1% CRF-3 + 5#sk Gilsonite+0.1 (Yeild=1.4 ft/sk, Weight=13.1#/gal) 5.91 gal/sk 147 bbls cmt @ 13.1#, H20. Discribed in the starting any proposed work).	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER [25#/sk Poly-e-Flake+0.15% HR-800
OTHER: 13. Describe proposed or completed operations. (Clearly state all perof starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ', 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50", 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152', FC PRESSURE TEST LINES TO 3000 PSI. CEMENT 4.1/2" CSG.PUMP 20BBLS 6590sx (826 cu.ft.) of Fraccem +0.8% Halad-9+0.1% CRF-3 + 5#sk Gilsonite+0.1	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER [25#/sk Poly-e-Flake+0.15% HR-800
OTHER: 13. Describe proposed or completed operations. (Clearly state all perof starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ′, 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50", 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152′, FC PRESSURE TEST LINES TO 3000 PSI. CEMENT 4.1/2" CSG.PUMP 20BBLS (590sx (826 cu.ft.) of Fraccem +0.8% Halad-9+0.1% CRF-3 + 5#sk Gilsonite+0.1 (Yeild=1.4 ft/sk, Weight=13.1#/gal) 5.91 gal/sk 147 bbls cmt @ 13.1#, H20. Disbump plug w/3000 psi. On 2230 hrs @9/29/2009. floats held.	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER [25#/sk Poly-e-Flake+0.15% HR-800 splace w/ 125. bbls .600 differential psi
OTHER: 13. Describe proposed or completed operations. (Clearly state all perof starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ′, 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50", 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152′, FC PRESSURE TEST LINES TO 3000 PSI. CEMENT 4.1/2" CSG.PUMP 20BBLS (590sx (826 cu.ft.) of Fraccem +0.8% Halad-9+0.1% CRF-3 + 5#sk Gilsonite+0.1 (Yeild=1.4 ft/sk, Weight=13.1#/gal) 5.91 gal/sk 147 bbls cmt @ 13.1#, H20. Discribed in the starting any proposed work).	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER [25#/sk Poly-e-Flake+0.15% HR-800 splace w/ 125. bbls .600 differential psi PRY RCUD OCT 1'03
OTHER: 13. Describe proposed or completed operations. (Clearly state all per of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ', 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50", 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152', FC PRESSURE TEST LINES TO 3000 PSI. CEMENT 4.1/2" CSG.PUMP 20BBLS of 590sx (826 cu.ft.) of Fraccem +0.8% Halad-9+0.1% CRF-3 + 5#sk Gilsonite+0.1 (Yeild=1.4 ft/sk, Weight=13.1#/gal) 5.91 gal/sk 147 bbls cmt @ 13.1#, H20. Disbump plug w/3000 psi. On 2230 hrs @9/29/2009. floats held. NOTE: CASING TEST AND TOC WILL BE REPORTED ON COMPLETION SUNIT	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER [25#/sk Poly-e-Flake+0.15% HR-800 splace w/ 125. bbls .600 differential psi PRY RCUD OCT 1'03 OIL CONS. DIV.
OTHER: 13. Describe proposed or completed operations. (Clearly state all per of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ′, 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50", 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152′, FC PRESSURE TEST LINES TO 3000 PSI. CEMENT 4.1/2" CSG.PUMP 20BBLS of 590sx (826 cu.ft.) of Fraccem +0.8% Halad-9+0.1% CRF-3 + 5#sk Gilsonite+0.1 (Yeild=1.4 ft/sk, Weight=13.1#/gal) 5.91 gal/sk 147 bbls cmt @ 13.1#, H20. Disbump plug w/3000 psi. On 2230 hrs @9/29/2009. floats held. NOTE: CASING TEST AND TOC WILL BE REPORTED ON COMPLETION SUNIDRILLING RIG RELEASED ON 9/30/09 @ 1800 HRS	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER [25#/sk Poly-e-Flake+0.15% HR-800 splace w/ 125. bbls .600 differential psi PRY RCUD OCT 1'03
OTHER: 13. Describe proposed or completed operations. (Clearly state all per of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ′, 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50″, 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152′, FC PRESSURE TEST LINES TO 3000 PSI. CEMENT 4.1/2″ CSG.PUMP 20BBLS 590sx (826 cu.ft.) of Fraccem +0.8% Halad-9+0.1% CRF-3 + 5#sk Gilsonite+0.1 (Yeild=1.4 ft/sk, Weight=13.1#/gal) 5.91 gal/sk 147 bbls cmt @ 13.1#, H20. Disbump plug w/3000 psi. On 2230 hrs @9/29/2009. floats held. NOTE: CASING TEST AND TOC WILL BE REPORTED ON COMPLETION SUNIDRILLING RIG RELEASED ON 9/30/09 @ 1800 HRS	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER [25#/sk Poly-e-Flake+0.15% HR-800 splace w/ 125. bbls .600 differential psi PRY RCUD OCT 1'03 OIL CONS. DIV. DIST. 3
OTHER: 13. Describe proposed or completed operations. (Clearly state all per of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ′, 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50", 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152′, FC PRESSURE TEST LINES TO 3000 PSI. CEMENT 4.1/2" CSG.PUMP 20BBLS of 590sx (826 cu.ft.) of Fraccem +0.8% Halad-9+0.1% CRF-3 + 5#sk Gilsonite+0.1 (Yeild=1.4 ft/sk, Weight=13.1#/gal) 5.91 gal/sk 147 bbls cmt @ 13.1#, H20. Disbump plug w/3000 psi. On 2230 hrs @9/29/2009. floats held. NOTE: CASING TEST AND TOC WILL BE REPORTED ON COMPLETION SUNIDRILLING RIG RELEASED ON 9/30/09 @ 1800 HRS	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER [25#/sk Poly-e-Flake+0.15% HR-800 splace w/ 125. bbls .600 differential psi PRY RCUD OCT 1'03 OIL CONS. DIV. DIST. 3
OTHER: 13. Describe proposed or completed operations. (Clearly state all per of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ′, 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50″, 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152′, FC PRESSURE TEST LINES TO 3000 PSI. CEMENT 4.1/2″ CSG.PUMP 20BBLS 590sx (826 cu.ft.) of Fraccem +0.8% Halad-9+0.1% CRF-3 + 5#sk Gilsonite+0.1 (Yeild=1.4 ft/sk, Weight=13.1#/gal) 5.91 gal/sk 147 bbls cmt @ 13.1#, H20. Disbump plug w/3000 psi. On 2230 hrs @9/29/2009. floats held. NOTE: CASING TEST AND TOC WILL BE REPORTED ON COMPLETION SUNIDRILLING RIG RELEASED ON 9/30/09 @ 1800 HRS	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER [25#/sk Poly-e-Flake+0.15% HR-800 splace w/ 125. bbls .600 differential psi PRY RCUD OCT 1'03 OIL CONS. DIV. DIST. 3
OTHER: 13. Describe proposed or completed operations. (Clearly state all per of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ', 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50", 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152', FC PRESSURE TEST LINES TO 3000 PSI. CEMENT 4.1/2" CSG.PUMP 20BBLS 590sx (826 cu.ft.) of Fraccem +0.8% Halad-9+0.1% CRF-3 + 5#sk Gilsonite+0.1 (Yeild=1.4 ft/sk, Weight=13.1#/gal) 5.91 gal/sk 147 bbls cmt @ 13.1#, H20. Disbump plug w/3000 psi. On 2230 hrs @9/29/2009. floats held. NOTE: CASING TEST AND TOC WILL BE REPORTED ON COMPLETION SUNID RILLING RIG RELEASED ON 9/30/09 @ 1800 HRS	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER 25#/sk Poly-e-Flake+0.15% HR-800 splace w/ 125. bbls .600 differential psi PRY RCVD OCT 1'03 OIL CONS. DIV. DIST. 3 c of my knowledge and belief.
OTHER: 13. Describe proposed or completed operations. (Clearly state all per of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ′, 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50″, 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152′, FC PRESSURE TEST LINES TO 3000 PSI. CEMENT 4.1/2″ CSG.PUMP 20BBLS 590sx (826 cu.ft.) of Fraccem +0.8% Halad-9+0.1% CRF-3 + 5#sk Gilsonite+0.1 (Yeild=1.4 ft/sk, Weight=13.1#/gal) 5.91 gal/sk 147 bbls cmt @ 13.1#, H20. Disbump plug w/3000 psi. On 2230 hrs @9/29/2009. floats held. NOTE: CASING TEST AND TOC WILL BE REPORTED ON COMPLETION SUNIDRILLING RIG RELEASED ON 9/30/09 @ 1800 HRS	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER 25#/sk Poly-e-Flake+0.15% HR-800 splace w/ 125. bbls .600 differential psi PRY RCVD OCT 1'03 OIL CONS. DIV. DIST. 3 c of my knowledge and belief.
OTHER: 13. Describe proposed or completed operations. (Clearly state all per of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ', 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50", 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152', FC PRESSURE TEST LINES TO 3000 PSI. CEMENT 4.1/2" CSG.PUMP 20BBLS 590sx (826 cu.ft.) of Fraccem +0.8% Halad-9+0.1% CRF-3 + 5#sk Gilsonite+0.1 (Yeild=1.4 ft/sk, Weight=13.1#/gal) 5.91 gal/sk 147 bbls cmt @ 13.1#, H20. Disbump plug w/3000 psi. On 2230 hrs @9/29/2009. floats held. NOTE: CASING TEST AND TOC WILL BE REPORTED ON COMPLETION SUNID RILLING RIG RELEASED ON 9/30/09 @ 1800 HRS	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER 125#/sk Poly-e-Flake+0.15% HR-800 splace w/ 125. bbls .600 differential psi PRY RCVD OCT 1'03 OIL CONS. DIV. DIST. 3 c of my knowledge and belief.
OTHER: 13. Describe proposed or completed operations. (Clearly state all per of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ¾" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ', 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50", 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152', FC PRESSURE TEST LINES TO 3000 PSI. CEMENT 4.1/2" CSG.PUMP 20BBLS 590sx (826 cu.ft.) of Fraccem +0.8% Halad-9+0.1% CRF-3 + 5#sk Gilsonite+0.1 (Yeild=1.4 ft/sk, Weight=13.1#/gal) 5.91 gal/sk 147 bbls cmt @ 13.1#, H20. Disbump plug w/3000 psi. On 2230 hrs @9/29/2009. floats held. NOTE: CASING TEST AND TOC WILL BE REPORTED ON COMPLETION SUNID RILLING RIG RELEASED ON 9/30/09 @ 1800 HRS I hereby certify that the information above is true and complete to the best SIGNATURE	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER [25#/sk Poly-e-Flake+0.15% HR-800 splace w/ 125. bbls .600 differential psi DRY RCUD OCT 1 'O'S OIL CONS. DIV. DIST. 3 c of my knowledge and belief. COM DATE: 10/1/09 COM DATE: 10/1/09
OTHER: 13. Describe proposed or completed operations. (Clearly state all per of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. 9/24/09-9/28/09 - Drill 6 ½" hole. 9/28/09- TD 6 ¾" PROD HOLE @ 8152 ', 0800 HRS. 9/29/09 - RAN 211 JTS, 4.50", 11.6#, N-80, LT&C, 8rd, CSG SET @ 8152', FC PRESSURE TEST LINES TO 3000 PSI. CEMENT 4.1/2" CSG.PUMP 20BBLS 590sx (826 cu.ft.) of Fraccem +0.8% Halad-9+0.1% CRF-3 + 5#sk Gilsonite+0.1 (Yeild=1.4 ft/sk, Weight=13.1#/gal) 5.91 gal/sk 147 bbls cmt @ 13.1#, H20. Disbump plug w/3000 psi. On 2230 hrs @9/29/2009. floats held. NOTE: CASING TEST AND TOC WILL BE REPORTED ON COMPLETION SUNID RILLING RIG RELEASED ON 9/30/09 @ 1800 HRS I hereby certify that the information above is true and complete to the best SIGNATURE TITLE: Drilling Type or print name: Larry Higgins E-mail address: larry.higgins@will For State Use Only	rtinent details, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of proposed completion @ 8111', MARKER JT @ 5616' GEL/WATER SPACER 125#/sk Poly-e-Flake+0.15% HR-800 splace w/ 125. bbls .600 differential psi PRY RCVD OCT 1'03 OIL CONS. DIV. DIST. 3 c of my knowledge and belief.