Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 200

	NO.			
Expires:	Nove	mber	30,	2
A 1111				۰

_	
- 1	
, i	
71	
/ 1	

SUNDRY NOTICES AND REPORTS ON WELLS

Lease Serial No. 14206032037

Do not upo this	o form for proposals to d	rill or to re enter			, ,20000200.		
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.			6.	6. If Indian, Allottee or Tribe Name EASTERN NAVAJO, SHIP ROCK			
SUBMIT IN TRIPLICATE - Other instructions on reve			ide.	7.	If Unit or CA/Agree NMNM78393X	ement, Name and/or No.	
1. Type of Well ☐ Gas Well ☐ Oth	ner	· · · · · · · · · · · · · · · · · · ·		8.	Well Name and No. HGU 100		
Name of Operator VULCAN MINERALS & ENER		AMMY WIMSATT -Mail: twimsatt@br-i	nc.com	9.	. API Well No. 30-045-10559-0)0-S1	
3a. Address 10777 WESTHEIMER, SUITE 1100 HOUSTON, TX 77042 B. Phone No. (Ph.: 505.599) Fx: 505.326.9			3	10	10. Field and Pool, or Exploratory HORSESHOE		
4. Location of Well (Footage, Sec., 7	., R., M., or Survey Description)			1	1. County or Parish,	and State	
Sec 24 T31N R17W NESE 19 36.88406 N Lat, 108.57565 W				SAN JUAN COL	UNTY, NM		
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE NAT	URE OF N	OTICE, REP	ORT, OR OTHE	R DATA	
TYPE OF SUBMISSION		TYPE OF ACTION					
□ Notice of Intent	☐ Acidize	□ Deepen		□ Production	(Start/Resume)	□ Water Shut-Off	
_	☐ Alter Casing	☐ Fracture Tr	eat	☐ Reclamation	on	☐ Well Integrity	
Subsequent Report	☐ Casing Repair	□ New Const	ruction	☐ Recomplet	e	□ Other	
Final Abandonment Notice	Change Plans	Plug and A	bandon	☐ Temporari	ly Abandon		
_	Convert to Injection	Plug Back		□ Water Disp	oosal		
determined that the site is ready for 1 (11/21/03) MIRU. Dig out brac sub and rods. SI well. SDON. (11/22/03) RU Mote hot oil trucirculate 20 bbls of oil to pit. (11/24/03) LD polish rod. TOO Remove wellhead cap. PU on test. TOOH and tally 44 joints Round-trip 5-1/2" casing scra Pressure test tubing to 1000#30 sxs cement inside casing a tubing. Shut in well. SDON. (11/25/03) RU pump on casing	denhead valve. Open up we lock. Hot oil tubing by pumpi Circ oil out of csg. Shut in w DH and LD sub, rods, sub a tubing and release tubing 2-3/8" tubing, SN and 15' i per to 1200'. TIH and set 5 . Pressure test casing to 50 above retainer up to 935' to g and load hole. RU A-Plus	ng 40 bbls hot wa vell. SDON. and pump with stra slips. Install comp mud anchor. Tubi -1/2" DHS cement 00#. Plug #1 with i isolate the Gallu	ter down tu ainer nipple panion flang ng landed at retainer at o perforatio	ubing to Then LD purge and NU BC at 1418'. 1200'. 1200', spot ns. TOOH with	mp. OS DE COLOR	12 13 14 75 AND 2004	
14. Thereby certify that the foregoing is							
	Electronic Submission #2 For VULCAN MINER	6630 verified by th ALS & ENERGY IN	e BLM Well C, sent to tl	Information Sy he Farmington	/stem		
	ommitted to AFMSS for proc	essing by STEVE N	IASON on 0	1/08/2004 (03S	(XM0899S		
Name (Printed/Typed) TAMMY V	VIMSATT	Title	REGULA	ATORY SPEC	IALIST		
Signature (Electronic	Submission)	Date	01/07/20	004			
	THIS SPACE FO	R FEDERAL OF	STATE	OFFICE USE			
Approved By ACCEPT	ED		STEPHEN PETROLEU	MASON JM ENGINEE	R	Date 01/08/2004	
Conditions of approval, if any, are attache certify that the applicant holds legal or eq which would entitle the applicant to cond	uitable title to those rights in the uct operations thereon.	subject lease Offic	e Farmingt				
Fitle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a c statements or representations as t	rime for any person k o any matter within it	nowingly and jurisdiction.	willfully to make	to any department o	or agency of the United	

Additional data for EC transaction #26630 that would not fit on the form

32. Additional remarks, continued

154'. Establish circulation out bradenhead. Plug #2 with 75 sxs cement pumped down the 5-1/2" casing from 154' to surface, circulate good cement returns out bradenhead. Shut in well and WOC 3 hours. Dig out wellhead. ND BOP. Cut off wellhead. Found cement down 2' in annulus and at surface in 5-1/2" casing. Mix 20 sxs cement to fill annulus and install P&A marker. RD. Rig released. R. Maurer, Burlington Resources representative was on location. W. Ashley, Navajo Nation representative was on location. Well was plugged and abandoned 11/25/03.