1625 N French Dr , Hobbs, NM 88240 District II 1301 W. Grand Ave , Artesia, NM 88210 District III

#### State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

July 21, 2008

Form C-144

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office

1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87505	For permanent pits and exceptions submit to the Santa Fe
District IV 1220 S St Francis Dr., Santa Fe, NM 87505		Environmental Bureau office and provide a copy to the appropriate NMOCD District Office
Pit, C	losed-Loop System, Below-G	rade Tank, or
4 136 Proposed A	Iternative Method Permit or C	Closure Plan Application
Type of action: Pern	nit of a pit, closed-loop system, below-gra	ade tank, or proposed alternative method
XClos	sure of a pit, closed-loop system, below-gr	rade tank, or proposed alternative method
<b>=</b>	lification to an existing permit	
Clos	sure plan only submitted for an existing pe	ermitted or non-permitted pit, closed-loop system,
belo	w-grade tank, or proposed alternative met	thod
Instructions: Please submit one applica	ntion (Form C-144) per individual pit, clo	osed-loop system, below-grade tank or alternative
		ons result in pollution of surface water, ground water or the cable governmental authority's rules, regulations or ordinances
1	noi of its responsionity to comply with any other applic	adde governmental authority's rules, regulations of ordinances
Operator: ConocoPhillips Company		OGRID#: <u>217817</u>
Address: P.O. Box 4289, Farmington, NM	87499	
Facility or well name: Hughes B 23		
API Number: 30-045-340	087 OCD Permit N	umber '
U/L or Qtr/Qtr: C(NE/NW) Section: 2	1 Township: 29N Range:	8W County: San Juan
·	66*42'48.35667 °N Longitude:	107*41'1.18395 °W NAD: X 1927 1983
Surface Owner: X Federal S	State Private Tribal Trust or In	ndian Allotment
X   Pit: Subsection F or G of 19 15.17.11 NMA     Temporary   X   Drilling   Workover     Permanent   Emergency   Cavitation     X   Lined   Unlined   Liner type     X   String-Reinforced     Liner Seams   X   Welded   X   Factory	P&A Thickness 12 mil X LLDPE	HDPE PVC Other  4400 bbl Dimensions L 65' x W 45' x D 10'
	9 15 17 11 NMAC ga new well Workover or Drilling (Applinatice of intent)	ies to activities which require prior approval of a permit or
Drying Pad Above Ground Steel T Lined Unlined Liner type. Liner Seams Welded Factory		HDPE PVD Other 1819202722
Below-grade tank: Subsection I of 19 15  Volume bbl T  Tank Construction material.	17 11 NMAC Type of fluid	/ ** N IL IL - I I I I I I I I I I I I I I I I
Secondary containment with leak detection  Visible sidewalls and liner  Vis  Liner Type  Thickness  mil	Visible sidewalls, liner, 6-inch lift and sible sidewalls only Other  HDPE PVC Other	153426
5 Alternative Method:		

Submittal of an exception request is required 
Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval

6					
Fencing: Subsection D of 19 15 17 11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks)					
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institu	tution or churc	-h)			
Four foot height, four strands of barbed wire evenly spaced between one and four feet	arrow or chart	,			
Alternate. Please specify					
7					
Netting: Subsection E of 19 15 17 11 NMAC (Applies to permanent pits and permanent open top tanks)					
Screen Netting Other					
Monthly inspections (If netting or screening is not physically feasible)					
8					
Signs: Subsection C of 19 15 17 11 NMAC					
12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers					
X Signed in compliance with 19 15 3.103 NMAC					
9					
Administrative Approvals and Exceptions:					
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15 17 NMAC for guidance.					
Please check a box if one or more of the following is requested, if not leave blank:					
Administrative approval(s) Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consi (Fencing/BGT Liner)	deration of app	proval.			
Exception(s) Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.		İ			
10 Siting Criteria (regarding permitting). 19 15 17 10 NMAC					
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable					
source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the					
appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria					
does not apply to drying pads or above grade-tanks associated with a closed-loop system.					
	<b></b>	m.,			
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	∐No			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa	Yes	□No			
lake (measured from the ordinary high-water mark).					
- Topographic map; Visual inspection (certification) of the proposed site					
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes	□No			
application. (Applies to temporary, emergency, or cavitation pits and below-grade tanks)	□NIA				
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image					
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	∐ <sup>No</sup>			
(Applied to permanent pits)	∐NA				
- Visual inspection (certification) of the proposed site; Aerial photo, Satellite image	_				
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	No			
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.					
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	Yes	□No			
- Written confirmation or verification from the municipality; Written approval obtained from the municipality					
Within 500 feet of a wetland.	Yes	□No			
- US Fish and Wildlife Wetland Identification map, Topographic map; Visual inspection (certification) of the proposed site					
Within the area overlying a subsurface mine.	Yes	□No			
- Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division					
Within an unstable area.	Yes	∐No			
<ul> <li>Engineering measures incorporated into the design, NM Bureau of Geology &amp; Mineral Resources, USGS, NM Geological Society; Topographic map</li> </ul>					
Within a 100-year floodplain	Yes	□No			

Form C-144 Oil Conservation Division Page 2 of 5

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19 15 17 9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19 15 17 9 NMAC
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15 17 9
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC
Design Plan - based upon the appropriate requirements of 19.15 17 11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17 12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 15.17 9 NMAC and 19 15 17 13 NMAC
Previously Approved Design (attach copy of design)  API  or Permit Number
Closed-loop Systems Permit Application Attachment Checklist:  Subsection B of 19.15 17 9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.  Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19 15 17 9
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19 15 17 10 NMAC
Design Plan - based upon the appropriate requirements of 19.15 17.11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19 15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 15 17 9 NMAC and 19 15 17 13 NMAC
Previously Approved Design (attach copy of design)  API
Previously Approved Operating and Maintenance Plan API
13
Permanent Pits Permit Application Checklist: Subsection B of 19 15 17 9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19 15 17 9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC
Climatological Factors Assessmen
Certified Engineering Design Plans - based upon the appropriate requirements of 19 15 17 11 NMAC
Dike Protection and Structural Integrity Design. based upon the appropriate requirements of 19 15 17.11 NMAC
Leak Detection Design - based upon the appropriate requirements of 19 15 17 11 NMAC
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19 15 17 11 NMAC
Quality Control/Quality Assurance Construction and Installation Plar
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19 15 17 11 NMAC
Nuisance or Hazardous Odors, including H2S, Prevention Plan
Emergency Response Plan
Oil Field Waste Stream Characterization
Monitoring and Inspection Plan
Erosion Control Plan  Closure Plan hand when the appropriate of Subsection C of 10 15 17 0 NIMAC and 10 15 17 13 NIMAC
Closure Plan - based upon the appropriate requirements of Subsection C of 19 15.17.9 NMAC and 19 15 17 13 NMAC
14  Proposed Closure: 19 15 17 13 NMAC  Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.
Type Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System
Alternative
Proposed Closure Method Waste Excavation and Removal
Waste Removal (Closed-loop systems only)
On-site Closure Method (only for temporary pits and closed-loop systems)
In-place Burial On-site Trench Burial
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
15
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.  Please indicate, by a check mark in the box, that the documents are attached.
Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19 15 17 13 NMAC
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15 17 13 NMAC
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15 17 13 NMAC

Form C-144 Oil Conservation Division Page 3 of 5

Intersections (Peterse destroit) the facility of pecialized for the disposal of lapseach, drilling fluids and daily causing. (Internal Section of the control of the contro	16 Waste Removal Closure For Closed-loop Systems That Utilize Above (	Ground Steel Tanks or Haul-off Bins Only: (19 15 17 13 D NMAC)				
Disposal Facility Name	are required	ias, ariting julias and ariti cultings. Use attachment if more than two jac	cumes			
Will any of the proposed closed-loop system operations and susceilated activities occur on or in areas that will not be used for future service and operations?   Yes (1 ftyrs, plene provide the information   No	Disposal Facility Name	Disposal Facility Permit #				
Yes (If yes, please provide the information   No   Regressified or maps claim of the second for plant is recorded by the properties of the second of the properties of the p	Disposal Facility Name	Disposal Facility Permit#				
Site Rectal and Cover Design Specification - based upon the appropriate requirements of Subsection I of 19.15 17 13 NMAC		ed activities occur on or in areas that will not be used for future serv	vice and operations?			
Sling Criteria (Regarding on-site closure methods only: _0   S   17 lo NMAC  Internacence Each interna	Soil Backfill and Cover Design Specification - based upon the Re-vegetation Plan - based upon the appropriate requirements	e appropriate requirements of Subsection H of 19 15 17 13 NMAC s of Subsection I of 19.15 17 13 NMAC				
Internations Each stong criteria requires a dimensional group of complete in the closure plan. Recommendations of acceptable source material arm promoted below. Request regarding charges to certain general progressian administrative globard from the demonstration of equivalence of the state fragment of the state fragment of the state fragment in the state state of the state state state state of the state state state of the state	17					
- NM Office of the State Engineer - IWATERS database search, USGS. Data obtained from nearby wells  - NM Office of the State Engineer - IWATERS database search, USGS, Data obtained from nearby wells  - NM Office of the State Engineer - IWATERS database search, USGS, Data obtained from nearby wells  - NM Office of the State Engineer - IWATERS database search, USGS, Data obtained from nearby wells  - NM Office of the State Engineer - IWATERS database search, USGS, Data obtained from nearby wells  - NM Office of the State Engineer - IWATERS database search, USGS, Data obtained from nearby wells  - Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark)  - Topographic map, Visual inspection (certification) of the proposed ste  - Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed stite, Aerial photo, satellite image purposes, or within 1000 horizontal feet of a private, domestic fresh water well or spring, in existence at the time of the inimal application  - NM Office of the State Engineer - IWATERS database, Visual inspection (certification) of the proposed site  Within 500 feet of a wetland  - Us fish and Wildlink Wetland Identification map, Topographic map, Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine  - Witten confirmation or verification from the municipality, Written approval obtained from the municipality  Within 500 feet of a wetland  - Us fish and Wildlink Wetland Identification map, Topographic map, Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine  - Written confirmation or verification from the MENINED-Mining and Mineral Division  Within an Instable area  - Written confirmation or verification from the MENINED-Mining and Mineral Division  W	Instructions Each siting criteria requires a demonstration of compliance in the clo- siting criteria may require administrative approval from the appropriate district off	sure plan Recommendations of acceptable source material are provided below . fice or may be considered an exception which must be submitted to the Santa Fe E				
- NM Office of the State Engineer - IWATERS database search, USGS, Data obtained from nearby wells  - NM Office of the State Engineer - IWATERS database search, USGS, Data obtained from nearby wells  - NM Office of the State Engineer - IWATERS database search, USGS, Data obtained from nearby wells  Within 300 feet of a conninuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark)  - Topographic map, Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site, Aerial photo, satellite image  - Within 500 horizontal feet of a private, domestic fresh water well or spring, in existence at the time of the initial application  - NM Office of the State Engineer - IWATERS database, Visual inspection (certification) for the proposed site within incorporated municipal boundaries or within a defined municipal afters water well or spring, in existence at the time of the initial application  - NM Office of the State Engineer - IWATERS database, Visual inspection (certification) for the proposed site within micropracted municipal boundaries or within a defined municipal fresh water well office overed under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as mended  - Written confirmation or verification from the municipality, Written approval obtained from the municipality  Within a 100-year overlying a subsurface mine  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an Instable area  - Engineering measures incorporated into the design, NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society, Topographic map  Within a 100-year floodplain  - FEMA map  - String Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC  -						
- NM Office of the State Engineer - IWATERS database search, USGS, Data obtained from nearby wells  - NM Office of the State Engineer - IWATERS database search, USGS, Data obtained from nearby wells  - NM Office of the State Engineer - IWATERS database search, USGS, Data obtained from nearby wells  Within 300 feet of a conninuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary) high-water mark)  - Topographic map, Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site, Aerial photo, satellite image  - Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existence at the time of the initial application  - NM Office of the State Engineer - IWATERS database, Visual inspection (certification) of the proposed site  Within morporated municipal boundaries or within a defined municipal fresh water well or spring, in existence at the time of minutal application  - Within 100 feet of a welland  - US Fish and Widfire Welland Identification from the municipality, Written approval obtained from the municipality  Within 500 feet of a welland  - US Fish and Widfire Welland Identification map, Topographic map, Visual inspection (certification) of the proposed site  Within a converting a subsurface mine  - Written confirmation or verification from the NM EMNRD-Mining and Mineral Division  Within an instable area  - Engineering measures incorporated into the design, NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society, Topographic map  - Word from the data from the Mining and Mineral Division  Within a 100-year floodplain  - French map  - French map  - Word from the	Ground water is between 50 and 100 feet below the bottom of the bu	uried waste	☐ Yes ☐No			
Ground water is more than 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database search, USGS, Data obtained from nearby wells  N/A  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark)  - Topographic map, Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site. Aerial photo, satellite image    Yes						
NM Office of the State Engineer - IWATERS database search, USGS, Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark)  - Topographic map, Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of mittal application.  - Visual inspection (certification) of the proposed site, Aerial photo, satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring, in existence at the time of the initial application.  - NM Office of the State Engineer - IWATERS database, Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as mended  - Writtee onfirmation or verification from the municipality, Written approval obtained from the municipality  Within 500 feet of a wetland  - US fish and Wildlife Wetland Identification map, Topographic map, Visual inspection (certification) of the proposed site  Within the area overlying as subsurface mine  - Writtee confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within a 100-year floodplain  - Engineering measures incorporated into the design, NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society, Topographic map  Within a 100-year floodplain  - FEMA map  IS  On-Stre Closure Plan Cheeklist: (19 15 17 13 NMAC) Instructions: Each of the following items must bee attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Sting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 11 NMAC    On-Struction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements	Ground water is more than 100 feet below the bottom of the buried v	waste	Yes No			
(measured from the ordnary high-water mark)  Topographic map, Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site, Aerial photo, satellite image    Yes   No			N/A			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site, Aerial photo, satellite image    Yes   No	· •	other significant watercourse or lakebed, sinkhole, or playa lake	Yes No			
- Visual inspection (certification) of the proposed site, Aerial photo, satellite image    Yes   No	- Topographic map, Visual inspection (certification) of the proposed s	inte				
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existence at the time of the initial application - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality, Written approval obtained from the municipality Within 500 feet of a wetland - US Fish and Wildlife Wetland Identification map, Topographic map, Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area - Engineering measures incorporated into the design, NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society, Topographic map Within a 100-year floodplain - FEMA map  IR  On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the following items must bee attached to the closure plan. Please indicate, by a check mark in the bax, that the documents are attached.  Sting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of 19 15.17 13 NMAC  Construction/Design Plan of Temporary Ptt (for in place burial of a drying pad) - based upon the appropriate requirements of 19 15 17 13 NMAC  Construction/Design Plan of Temporary Ptt (for in place burial of a flying pad) - based upon the appropriate requirements of 19 15 17 13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC	•	• • • • • • • • • • • • • • • • • • • •	Yes No			
purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existence at the time of the initial application - NM Office of the State Engineer - INATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality, Written approval obtained from the municipality Within 500 feet of a wetland - US Fish and Wildlife Wetland Identification map, Topographic map, Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area - Engineering measures incorporated into the design, NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society, Topographic map Within a 100-year floodplain - FEMA map  IN  IN  IN  IN  IN  IN  IN  IN  IN  I			Yes No			
pursuant to NMSA 1978, Section 3-27-3, as amended  Written confirmation or verification from the municipality, Written approval obtained from the municipality  Within 500 feet of a wetland  US Fish and Wildlife Wetland Identification map, Topographic map, Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area  Engineering measures incorporated into the design, NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society, Topographic map  Within a 100-year floodplain  FEMA map  Is  On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the following items must bee attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of 19 15 17 11 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19 15 17 11 NMAC  Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19 15 17 13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC	purposes, or within 1000 horizontal fee of any other fresh water well or spi	ring, in existence at the time of the initial application				
Within 500 feet of a wetland  - US Fish and Wildlife Wetland Identification map, Topographic map, Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine  - Written confiramtion or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area  - Engineering measures incorporated into the design, NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society, Topographic map  Within a 100-year floodplain  - FEMA map    Yes	pursuant to NMSA 1978, Section 3-27-3, as amended		Yes No			
Within the area overlying a subsurface mine - Written confiramtion or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area - Engineering measures incorporated into the design, NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society, Topographic map  Within a 100-year floodplain - FEMA map  IR  On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the following items must bee attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of 19 15 17 11 NMAC Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19 15 17 13 NMAC Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19 15 17 13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC	Within 500 feet of a wetland		Yes No			
Within an unstable area  - Engineering measures incorporated into the design, NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society, Topographic map  Within a 100-year floodplain  - FEMA map    Yes		,	Yes No			
- Engineering measures incorporated into the design, NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society, Topographic map  Within a 100-year floodplain - FEMA map    Yes	- Written confiramtion or verification or map from the NM EMNRD-N	Aining and Mineral Division				
Within a 100-year floodplain FEMA map    Yes	- Engineering measures incorporated into the design, NM Bureau of G	eology & Mineral Resources; USGS, NM Geological Society,	Yes No			
On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the following items must bee attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19 15.17 13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19 15 17 11 NMAC  Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19 15 17.11 NMAC  Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC	Within a 100-year floodplain		Yes No			
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19 15.17 13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19 15 17 11 NMAC  Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19 15 17.11 NMAC  Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC	On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instruction	ons: Each of the following items must bee attached to the closure	plan. Please indicate, by a			
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19 15.17 13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19 15 17 11 NMAC  Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19 15 17.11 NMAC  Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC		appropriate requirements of 19 15 17 10 NMAC				
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19 15 17.11 NMAC  Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC						
Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC						
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC						
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC	Protocols and Procedures - based upon the appropriate requir	rements of 19 15 17 13 NMAC				
	Confirmation Sampling Plan (if applicable) - based upon the	appropriate requirements of Subsection F of 19 15 17 13 NMAC				
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)	Waste Material Sampling Plan - based upon the appropriate a	requirements of Subsection F of 19 15 17 13 NMAC				
	Disposal Facility Name and Permit Number (for liquids, drill	ling fluids and drill cuttings or in case on-site closure standards can	not be achieved)			
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19 15 17 13 NMAC						
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15 17 13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15 17 13 NMAC						

Operator Application Cartification			
Operator Application Certification  I hereby certify that the information sub-	<u>n:</u> omitted with this application is true, accurate	and complete to the best of my known	owledge and belief
Name (Print)		Title	-
Signature		Date	
e-mail address		Telephone	
20 OCD Approval: Permit Appl OCD Representative Signature:	ication (including closure plan)	Closure Plan (only) OCI	O Conditions (see attachment)  Approval Date:
Title:		OCD Permit Numbe	r
riue.		OCD Termit Number	
Instructions. Operators are required to is required to be submitted to the divisi		nplementing any closure activities o	und submitting the closure report The closure report uplete this section of the form until an approved ion Date:August 19, 2008
22		* * * * * * * * * * * * * * * * * * * *	
Closure Method:  Waste Excavation and Remova  If different from approved plan		Alternative Closure Method	Waste Removal (Closed-loop systems only)
23			
	moval Closure For Closed-loop Systems T		
utilized.	y or faculties for where the liquias, arilling	g fluias ana arui cuttings were aisp	osed. Use attachment if more than two facilities were
Disposal Facility Name		Disposal Facility Permit Nur	mber
Disposal Facility Name		Disposal Facility Permit Nur	nber
l <u> </u>	ions and associated activities performed on o	or in areas that will not be used for	future service and opeartions?
Yes (If yes, please demonstrate	compliane to the items below)	No	
Required for impacted areas which	will not be used for future service and opera	ations.	
Site Reclamation (Photo Docui	·		
Soil Backfilling and Cover Inst			
Re-vegetation Application Rate	s and Seeding Technique		
24 Closure Report Attachment C the box, that the documents are att		ing items must be attached to the c	closure report. Please indicate, by a check mark in
X Proof of Closure Notice (sur	face owner and division)		
X Proof of Deed Notice (requi	red for on-site closure)		, , , , , , , , , , , , , , , , , , ,
X Plot Plan (for on-site closure	es and temporary pits)		
X Confirmation Sampling Ana	alytical Results (if applicable)	•	
Waste Material Sampling A	nalytical Results (if applicable)		
X Disposal Facility Name and	Permit Number		
Soil Backfilling and Cover I			
Re-vegetation Application F	Rates and Seeding Technique		
X Site Reclamation (Photo Do	cumentation)		
On-site Closure Location	Latitude. <b>36,71382</b> °	N Longitude 107.68528	<u>°W</u> NAD
	d attachments submitted with this closure re e closure requirements and conditions speci	=	to the best of my knowledge and belief. I also certify that
Name (Print):	Crystal Tafoya	Title	Regulatory Technician
Signature	stal Tologa	Date	1/19/2010
e-mail address <u>cry</u>	stal.tafoya@conocophillips com	Telephone	505-326-9837
	•		

Approved Franciscon Formell NMOCD 1/20/10
Form C-144

# ConocoPhillips Company San Juan Basin Closure Report

Lease Name: Hughes B 23 API No.: 30-045-34087

In accordance with Rule 19.15.17.13 NMAC the following information describes the closure of the temporary pit referenced above. All proper documentation regarding closure activities is being included with the C-144. The temporary pit for this location was constructed and location drilled before June 16, 2008 (effective date for Rule 19.15.17). While closure of the temporary pit did fall within the rule some dates for submittals are after the rig release date.

- Details on Capping and Covering, where applicable. (See report)
- Plot Plan (Pit Diagram) (Included as an attachment)
- Inspection Reports (Included as an attachment)
- Sampling Results (Included as an attachment)
- C-105 (Included as an attachment)
- Copy of Deed Notice will be filed with County Clerk (Not required on Federal, State, or Tribal land as stated by FAQ dated October 30, 2008)

#### **General Plan:**

1. All free standing liquids will be removed at the start of the pit closure process from the pit and disposed of in a division—approved facility or recycle, reuse or reclaim the liquids in a manner that the appropriate division district office approves.

All recovered liquids were disposed of at Basin Disposal (Permit #NM-01-005) and any sludge or soil required to be removed to facilitate closure was hauled to Envirotech Land Farm (Permit #NM-01-011) and JFJ Landfarm % IEI (Permit #NM-01-0010B).

2. The preferred method of closure for all temporary pits will be on-site burial, assuming that all the criteria listed in sub-section (B) of 19.15.17.13 are met.

The pit was closed using onsite burial.

3. The surface owner shall be notified of COPC's closing of the temporary pit as per the approved closure plan using certified mail, return receipt requested.

The closure process notification to the landowner was sent via email. (See Attached)(Well located on Federal Land, certified mail is not required for Federal Land per BLM/OCD MOU.)

4. Within 6 months of the Rig Off status occurring COPC will ensure that temporary pits are closed, re-contoured, and reseeded.

Provision 4 of the closure plan requirements were not met due to rig move off date as noted on C-105 which was prior to pit rule change. ConocoPhillips will ensure compliance with this rule in the future.

- 5. Notice of Closure will be given to the Aztec Division office between 72 hours and one week of closure via email, or verbally. The notification of closure will include the following:
  - i. Operator's name
  - ii. Location by Unit Letter, Section, Township, and Range. Well name and API number.

Notification is attached.

6. Liner of temporary pit shall be removed above "mud level" after stabilization. Removal of liner will consist of manually or mechanically cutting liner at mud level and removing all remaining liner. Care will be taken to remove "All" of the liner i.e., edges of liner entrenched or buried. All excessive liner will be disposed of at a licensed disposal facility.

Liner of temporary pit was removed above "mud level" after stabilization. Removal of the liner consisted of manually cutting liner at mud level and removing all remaining liner. Care was taken to remove "ALL" of the liner i.e., edges of liner entrenched or buried. All excessive liner was disposed of at a licensed disposal facility, (San Juan County Landfill).

7. Pit contents shall be mixed with non-waste containing, earthen material in order to achieve the solidification process. The solidification process will be accomplished using a combination of natural drying and mechanically mixing. Pit contents will be mixed with non-waste, earthen material to a consistency that is deemed a safe and stable. The mixing ratio shall not exceed 3 parts clean soil to 1 part pit contents.

ConocoPhillips mixed the Pit contents with non-waste containing, earthen material in order to achieve the solidification process. The solidification process was accomplished by using a combination of natural drying and mechanically mixing. Pit contents were mixed with non-waste, earthen material to a consistency that is deemed as safe and stable. The mixing ratio consisted of approximately 3 parts clean soil to 1 part pit contents.

8. A five point composite sample will be taken of the pit using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

A five point composite sample was taken of the pit using sampling tools and all samples tested per Subsection B of 19.15.17.1 3(B)(1)(b). (Sample results attached).

Components	Tests Method	Limit (mg/Kg)	Results
Benzene	EPA SW-846 8021B or 8260B	0.2	2.0 ug/kg
BTEX	EPA SW-846 8021B or 8260B	50	93.7 ug/kG
TPH	EPA SW-846 418.1	2500	82.2mg/kg
GRO/DRO	EPA SW-846 8015M	500	105 mg/Kg
Chlorides	EPA 300.1	1000/500	171 mg/L

9. Upon completion of solidification and testing standards being passed, the pit area will be backfilled with compacted, non-waste containing, earthen material. A minimum of four feet of cover shall be achieved and the cover shall include one foot of suitable material to establish vegetation at the site, or the background thickness of topsoil, whichever is greater. If standard testing fails BR will dig and haul all contents pursuant to 19.15.17.13.i.a. After doing such, confirmation sampling will be conducted to ensure a release has not occurred.

The pit material passed solidification and testing standards. The pit area was then backfilled with compacted, non-waste containing, earthen material. More than four feet of cover was achieved and the cover included one foot of suitable material to establish vegetation at the site.

10. During the stabilization process if the liner is ripped by equipment the Aztec OCD office will be notified within 48 hours and the liner will be repaired if possible. If the liner can not be repaired then all contents will be excavated and removed.

The integrity of the liner was not damaged in the pit closure process.

11. Dig and Haul Material will be transported to the Envirotech Land Farm located 16 miles south of Bloomfield on Angel Peak Road, CR 7175. Permit # NM010011

Dig and Haul was not required.

12. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final recontour shall have a uniform appearance with smooth surface, fitting the natural landscape.

The pit area was re-contoured to match fit, shape, line, form and texture of the surrounding area. Reshaping included drainage control, to prevent ponding and erosion. Natural drainages were unimpeded and water bars and/or silt traps were placed in areas where needed to prevent erosion on a large scale. Final recontour has a uniform appearance with smooth surface, fitting the natural landscape.

13. Notification will be sent to OCD when the reclaimed area is seeded.

Provision 13 was accomplished through complying with BLM seeding requirements as allowed by the BLM/OCD MOU.

14. COPC shall seed the disturbed areas the first growing season after the operator closes the pit. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Provision 14 was accomplished through complying with BLM seeding requirements as allowed by the BLM/OCD MOU.

15. The temporary pit will be located with a steel marker, no less than four inches in diameter, cemented in a hole three feet deep in the center of the onsite burial upon the abandonment of all the wells on the pad. The marker will be flush with the ground to allow access of the active well pad and for safety concerns. The marker will include a threaded collar to be used for future abandonment. The top of the marker will contain a welded steel 12" square plate that indicates the onsite burial of the temporary pit. The plate will be easily removable and a four foot tall riser will be threaded into the top of the collar marker and welded around the base with the operator's information at the time of all wells on the pad are abandoned. The operator's information will include the following: Operator Name, Lease Name, Well Name and number, Unit Number, Section, Township, Range and an indicator that the marker is an onsite burial location.

Provision 15 was accomplished by installing a steel marker in the temporary pit, no less than four inches in diameter, cemented in a hole three feet deep in the center of the onsite burial. The marker is flush with the ground to allow access of the active well pad and for safety concerns. The top of the marker contains a welded steel 12" square plate that indicates the onsite burial of the temporary pit. The plate contains the following: Operator Name, Lease Name, Well Name and number, Unit Number, Section, Township, Range and an indicator that the marker is an onsite burial location.

The plate will be easily removable and a four foot tall riser will be threaded into the top of the collar marker and welded around the base with the following operator's information at the time of all wells on the pad are abandoned. The riser will be labeled: COP, BLM, Hughes B 23, UL-F, Sec. 21, T 29N, R 8W, API # 30-045-34087

#### Tafoya, Crystal

From:

Sent:

Tafoya, Crystal Friday, September 26, 2008 1:30 PM 'mark\_kelly@nm.blm.gov'

To: Subject:

Surface Owner Notification

The Hughes B 23 temporary pit will be closed on-site. Please let me know if you have any questions.

Thank you,

Crystal L. Tafoya Regulatory Technician ConocoPhillips Company San Juan Business Unit Phone: (505) 326-9837

Email: Crystal.Tafoya@conocophillips.com

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Avenue, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505


Form C-102 Revised October 12, 2005 Submit to Appropriate District Office State Lease - 4 Copies Fee Lease - 3 Copies

☐ AMMENDED REPORT

#### WELL LOCATION AND ACREAGE DEDICATION PLAT

l A	PI Number		2	Pool Code		<sup>3</sup> Pool Name FRUITLAND COAL				
<sup>4</sup> Property Cod	le				<sup>5</sup> Propert HUGI	y Name HES B	<sup>6</sup> Well Number 23			
7 OGRID N	0.	•			•	Operator Name  9 Elevation  OPHILLIPS COMPANY  6464				
					<sup>10</sup> SURFACE	LOCATION			The second secon	
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County	
F	21	29-N	W-80		1584	NORTH	1407	WEST	SAN JUAN	
			<sup>11</sup> B	ottom Ho	ole Location	If Different Fro	m Surface			
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County	
Dedicated Acres 320.0	13 Joint	or Infill 14 C	Consolidation	Code 15	Order No.				L	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



PIT CROSS SECTION

NAD 83 LAT.: 36.713944° N / LONG.: 107.685139° W

CCI

P.O. BOX 328

CHENAULT CONSULTING INC. PHONE: (505)325-7707

BLOOMFIELD,NM, 87413

TO CONSTRUCTION. PRIOR UNMARKED BURIED (2) WORKING DAYS UNDERGROUND UTILITIES (
L. FOR LOCATION OF ANY
AND OR ACCESS ROAD A' FOR -CAL LIABLE ALL ONI rs is not SHOULD C. CABLES ON C.C.I. SUF CONTRACT PIPLINES

305' x 340' = 2.38 ACRES



#### EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Hughes B23	Date Reported:	08-07-08
Laboratory Number:	46588	Date Sampled:	08-01-08
Chain of Custody No:	4833	Date Received:	08-01-08
Sample Matrix:	Soil	Date Extracted:	08-05-08
Preservative:		Date Analyzed:	08-06-08
Condition:	Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	105	0.1
Total Petroleum Hydrocarbons	105	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

**Drill Mud Pit** 

Analyst

Review

5796 U.S. Highway 64 • Farmington, NM 87401 • Tel 505 • 632 • 0615 • Fax 505 • 632 • 1865



#### EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Hughes B23 Background	Date Reported:	08-07-08
Laboratory Number:	46589	Date Sampled:	08-01-08
Chain of Custody No:	4833	Date Received:	08-01-08
Sample Matrix:	Soil	Date Extracted:	08-05-08
Preservative:		Date Analyzed:	08-06-08
Condition:	Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments: Drill Mud Pit

Analyst

Aristus m Walter

5796 U.S. Highway 64 • Farmington, NM 87401 • Tel 505 • 632 • 0615 • Fax 505 • 632 • 1865



# EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

#### **Quality Assurance Report**

Mustur m Walters

Client:	QA/QC	Project #:		N/A
Sample ID:	08-06-08 QA/QC	Date Reported:		08-07-08
Laboratory Number:	46580	Date Sampled:		N/A
Sample Matrix:	Methylene Chloride	Date Received:	ĺ	V/A
Preservative:	N/A	Date Analyzed:		08-06-08
Condition:	N/A	Analysis Reque	sted:	TPH
	Î-Gal₁Date के 126	al RF: C-Cal RF:	% Difference	Accept Range
Gasoline Range C5 - C10	5.46600000000000000000000000000000000000	28E+002 9.9868E+002	0.04%	0 - 15%
Diesel Range C10 - C28		48E+002 9.9688E+002	0.04%	0 - 15%
2.000. (talligo 010 020	00 01 01	,02 · 002 · 0.00002 · 002	0.0 170	, ,
∗Blank Conc. (mg/L - mg/Kg)	Conc	entration	Detection Limit	
Gasoline Range C5 - C10		D	0.2	
Diesel Range C10 - C28	•	D	0.1	
Total Petroleum Hydrocarbons		D	0.2	
Total Felloleum Hydrocarbons			U.L	
Duplicate Conc. (mg/kg)	Sample Duj	olicate % Difference	Accept. Range	
Gasoline Range C5 - C10	2.2	2.2 0.0%	0 - 30%	
Diesel Range C10 - C28	147 1	46 0.6%	0 - 30%	
-				
Spike Conc. (mg/Kg)	Sample Spike	Added Spike Result	% Recovery	Accept. Range
Gasoline Range C5 - C10	20 3 4 3 5 4 5 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	250 251	99.6%	75 - 125%
Diesel Range C10 - C28	147 2	250 403	102%	75 - 125%
•				

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

QA/QC for Samples 46580 - 46589.

Analyst



## EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Hughes B23	Date Reported:	08-07-08
Laboratory Number:	46588	Date Sampled:	08-01-08
Chain of Custody:	4833	Date Received:	08-01-08
Sample Matrix:	Soil	Date Analyzed:	08-06-08
Preservative:		Date Extracted:	08-05-08
Condition:	Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	2.0	0.9
Toluene	11.4	1.0
Ethylbenzene	4.6	1.0
p,m-Xylene	55.3	1.2
o-Xylene	20.4	0.9
Total BTEX	93.7	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	98.0 %
	1,4-difluorobenzene	98.0 %
	Bromochlorobenzene	98.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

**Drill Mud Pit** 

Analyst

Review Duceten



## EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Hughes B23 Background	Date Reported:	08-07-08
Laboratory Number:	46589	Date Sampled:	08-01-08
Chain of Custody:	4833	Date Received:	08-01-08
Sample Matrix:	Soil	Date Analyzed:	08-06-08
Preservative:		Date Extracted:	08-05-08
Condition:	Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	ND	0.9
Toluene	ND	1.0
Ethylbenzene	ND	1.0
p,m-Xylene	ND	1.2
o-Xylene	ND	0.9
Total BTEX	ND	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	97.0 %
	1,4-difluorobenzene	97.0 %
	Bromochlorobenzene	97.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

**Drill Mud Pit** 

Analyst

Apristu n Walters
Review



## EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A	Decident #1	NI/A
Ciletit.	IN/A	Project #:	N/A
Sample ID:	08-06-BT QA/QC	Date Reported:	08-07-08
Laboratory Number:	46580	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	08-06-08
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)		C-Cal RF: Accept Rang	%Diff. ge 0 - 15%	Blank Conc	Detect. Limit
Benzene	8 5285E+007	8 5456E+007	0.2%	ND	0.1
Toluene	6.4832E+007	6.4962E+007	0.2%	ND	0.1
Ethylbenzene	5 1253E+007	5.1355E+007	0.2%	ND	0.1
p,m-Xylene	1 0553E+008	1.0575E+008	0.2%	ND	0.1
o-Xylene	4.9491E+007	4 9590E+007	0.2%	ND	0.1

Duplicate Conc. (ug/Kg)	Sample D	uplicate	%Diff.	Accept Range	Detect: Limit
Benzene	6.1	6.0	1.6%	0 - 30%	0.9
Toluene	18.3	18.0	1.6%	0 - 30%	1.0
Ethylbenzene	5.6	5.3	5.4%	0 - 30%	1.0
p,m-Xylene	223	222	0.3%	0 - 30%	1.2
o-Xylene	29.5	29.1	1.4%	0 - 30%	0.9

Spike Conc. (ug/Kg)	Sample Amo	unt Spiked Spik	ked Sample	% Recovery	Accept Range
Benzene	6.1	50.0	55.7	99.3%	39 - 150
Toluene	18.3	50.0	66.3	97.1%	46 - 148
Ethylbenzene	5,6	50.0	52.6	94.6%	32 - 160
p,m-Xylene	223	100	320	98.9%	46 - 148
o-Xylene	29.5	50.0	77.4	97.4%	46 - 148

ND - Parameter not detected at the stated detection limit.

References

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996

Comments:

QA/QC for Samples 46580 - 46589.

Analyst

Ahrestum Walles
Review



#### TRACE METAL ANALYSIS

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Hughes B 23	Date Reported:	08-06-08
Laboratory Number:	46588	Date Sampled:	08-01-08
Chain of Custody:	4833	Date Received:	08-01-08
Sample Matrix:	Soil	Date Analyzed:	08-05-08
Preservative:		Date Digested:	08-04-08
Condition:	Intact	Analysis Needed:	Total Metals

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)	TCLP Regulatory Level (mg/Kg)
<b>.</b>	0.000	0.004	5.0
Arsenic	0.032	0.001	5.0
Barium	17.6	0.001	100
Cadmium	ND	0.001	1.0
Chromium	0.082	0.001	5.0
Lead	0.187	0.001	5.0
Mercury	ND	0.001	0.2
Selenium	0.213	0.001	1.0
Silver	ND	0.001	5.0

ND - Parameter not detected at the stated detection limit.

References:

Method 3050B, Acid Digestion of Sediments, Sludges and Soils.

SW-846, USEPA, December 1996.

Method 6010B, Analysis of Metals by Inductively Coupled Plasma Atomic Emmision

Spectroscopy, SW-846, USEPA, December 1996.

Note:

Regulatory Limits based on 40 CFR part 261 subpart C

section 261.24, August 24, 1998.

Comments:

**Drill Mud Pit.** 

Analyst

Muster of Walter Review



#### TRACE METAL ANALYSIS

oject #: 96052-0026
te Reported: 08-06-08
te Sampled: 08-01-08
te Received: 08-01-08
te Analyzed: 08-05-08
te Digested: 08-04-08
alysis Needed: Total Metals

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)	TCLP Regulatory Level (mg/Kg)		
Arsenic	0.021	0.001	5.0		
Barium	4.1	0.001	100		
Cadmium	ND	0.001	1.0		
Chromium	0.047	0.001	5.0		
Lead	0.349	0.001	5.0		
Mercury	ND	0.001	0.2		
Selenium	0.010	0.001	1.0		
Silver	ND	0.001	5.0		

ND - Parameter not detected at the stated detection limit.

References:

Method 3050B, Acid Digestion of Sediments, Sludges and Soils.

SW-846, USEPA, December 1996.

Method 6010B, Analysis of Metals by Inductively Coupled Plasma Atomic Emmision

Spectroscopy, SW-846, USEPA, December 1996.

Note:

Regulatory Limits based on 40 CFR part 261 subpart C

section 261.24, August 24, 1998.

Comments:

Drill Mud Pit.

Analyst

5796 U.S. Highway 64 • Farmington, NM 87401 • Tel 505 • 632 • 0615 • Fax 505 • 632 • 1865



## TRACE METAL ANALYSIS Quality Control / Quality Assurance Report

Client:		QA/QC		Project #:			QA/QC		
Sample ID:		08-05 TM	QA/AC	Date Repo	orted:		08-06-08		
Laboratory Number:		46580		Date Sam			N/A		
Sample Matrix:		Soil		Date Rec	•		N/A		
Analysis Requested:		Total RCR	A Metals	Date Anal			08-05-08		
Condition:		N/A	, i molalo	Date Dige	•		08-04-08		
Condition.		1975		Date Dige	otou.		00 0 . 00		
		Method g) Blank	Detection Limit		Duplicate	% Diff.	Acceptance Range		
Arsenic	ND	ND	0.001	ND	ND	0.0%	0% - 30%		
Barium	ND	ND	0.001	33.1	33.1	0.0%	0% - 30%		
Cadmium	ND	ND	0.001	0.008	0.009	13.8%	0% - 30%		
Chromium	ND	ND	0.001	0.173	0.164	5.0%	0% - 30%		
Lead	ND	ND	0.001	0.346	0.343	0.8%	0% - 30%		
Mercury	ND	ND	0.001	ND	ND	0.0%	0% - 30%		
Selenium	ND	ND	0.001	ND	ND	0.0%	0% - 30%		
Silver	ND	ND	0.001	ND	ND	0.0%	0% - 30%		
Spike Conc (mg/Kg)		Spike Added	Sampl	e Spiked Sample	L		Acceptance Range		
Arsenic		0.250	ND	0.274	109%		80% - 120%		
Barium		0.500	33.1	29.6	88.1%		80% - 120%		
Cadmium		0.250	0.008	0.238	92.4%		80% - 120%		
Chromium		0.500	0.173	0.549	81.6%		80% - 120%		
Lead		0.500	0.346	0.696	82.3%		80% - 120%		
Mercury		0.100	ND	0.096	96.4%		80% - 120%		
Selenium		0.100	ND	0.097	97.2%		80% - 120%		
Silver		0.100	ND	0.085	84.6%		80% - 120%		

ND - Parameter not detected at the stated detection limit.

References:

Method 3050B, Acid Digestion of Sediments, Sludges and Soils.

SW-846, USEPA, December 1996.

Method 6010B, Analysis of Metals by Inductively Coupled Plasma Atomic Emmision

Spectorscopy, SW-846, USEPA, December 1996.

Comments:

QA/1QC for Samples 46580 - 46589.

Analyst

Review Walter



#### **CATION / ANION ANALYSIS**

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Hughes B23	Date Reported:	08-11-08
Laboratory Number:	46588	Date Sampled:	08-01-08
Chain of Custody:	4833	Date Received:	08-01-08
Sample Matrix	Soil Extract	Date Extracted:	08-04-08
Preservative:		Date Analyzed:	08-05-08
Condition:	Intact		

	Analytical			
Parameter	Result	Units		
рН	8.30	s.u.		
Conductivity @ 25° C	2,510	umhos/cm		
Total Dissolved Solids @ 180C	1,210	mg/L		
Total Dissolved Solids (Calc)	1,315	mg/L		
SAR	5.2	ratio		
Total Alkalinity as CaCO3	43.0	mg/L		
Total Hardness as CaCO3	387	mg/L		
Bicarbonate as HCO3	43.0	mg/L	0.70	meq/L
Carbonate as CO3	<0.1	mg/L	0.00	meq/L
Hydroxide as OH	<0.1	mg/L	0.00	meq/L
Nitrate Nitrogen	0.615	mg/L	0.01	meq/L
Nitrite Nitrogen	0.006	mg/L	0.00	meq/L
Chloride	171	mg/L	4.82	meq/L
Fluoride	0.811	mg/L	0.04	meq/L
Phosphate	1.90	mg/L	0.06	meq/L
Sulfate	697	mg/L	14.51	meq/L
Iron	0.041	· mg/L	0.00	meq/L
Calcium	133	mg/L	6.64	meq/L
Magnesium	13.2	mg/L	1.09	meq/L
Potassium	35.2	mg/L	0.90	meq/L
Sodium	236	mg/L	10.27	meq/L
Cations			18.89	meq/L
Anions			20.15	meq/L
Cation/Anion Difference			6.26%	

Reference: U.S.E.P.A., 600/4-79-020, "Methods for Chemical Analysis of Water and Wastes", 1983. Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments: Drill Mud Pit.

Analyst

Mister Wasters Review



#### **CATION / ANION ANALYSIS**

Client:	ConocoPhillips	Project #:	96052-0026	
Sample ID:	Hughes B23 Background	Date Reported:	08-11-08	
Laboratory Number:	46589	Date Sampled:	08-01-08	
Chain of Custody:	4833	Date Received:	08-01-08	
Sample Matrix:	Soil Extract	Date Extracted:	08-04-08	
Preservative:		Date Analyzed:	08-05-08	
Condition:	Intact			

	Analytical	The state of the s		
Parameter	Result	Units		
рН	7.85	s.u.		
Conductivity @ 25° C	2,210	umhos/cm		
Total Dissolved Solids @ 180C	1,340	mg/L		
Total Dissolved Solids (Calc)	1,343	mg/L		
SAR	1.9	ratio		
Total Alkalinity as CaCO3	29.0	mg/L		
Total Hardness as CaCO3	720	mg/L		
Bicarbonate as HCO3	29.0	mg/L	0.48	meq/L
Carbonate as CO3	<0.1	mg/L	0.00	meq/L
Hydroxide as OH	<0.1	mg/L	0.00	meq/L
Nitrate Nitrogen	0.832	mg/L	0.01	meq/L
Nitrite Nitrogen	0.077	mg/L	0.00	meq/L
Chloride	32.0	mg/L	0.90	meq/L
Fluoride	0.382	mg/L	0.02	meq/L
Phosphate	0.600	mg/L	0.02	meq/L
Sulfate	883	mg/L	18.38	meq/L
Iron	0.001	mg/L	0.00	meq/L
Calcium	270	mg/L	13.47	meq/L
Magnesium	11.0	mg/L	0.91	meq/L
Potassium	7.33	mg/L	0.19	meq/L
Sodium	120	mg/L	5.22	meq/L
Cations			19.79	meq/L
Anions			19.82	meq/L
Cation/Anion Difference			0.15%	

Reference: U.S.E.P.A., 600/4-79-020, "Methods for Chemical Analysis of Water and Wastes", 1983. Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments: Drill Mud Pit.

Analyst

Mustum Wooden
Review



#### EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Hughes B 23	Date Reported:	08-05-08
Laboratory Number:	46588	Date Sampled:	08-01-08
Chain of Custody No:	4833	Date Received:	08-01-08
Sample Matrix:	Soil	Date Extracted:	08-04-08
Preservative:		Date Analyzed:	08-04-08
Condition:	Intact	Analysis Needed:	TPH-418.1

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

**Total Petroleum Hydrocarbons** 

82.2

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

Drill Mud Pit.

Analyst

( Mustur Weeler Review



#### EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Hughes B 23 Background	Date Reported:	08-05-08
Laboratory Number:	46589	Date Sampled:	08-01-08
Chain of Custody No:	4833	Date Received:	08-01-08
Sample Matrix:	Soil	Date Extracted:	08-04-08
Preservative:		Date Analyzed:	08-04-08
Condition:	Intact	Analysis Needed:	TPH-418.1

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

**Total Petroleum Hydrocarbons** 

20.0

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

Drill Mud Pit.

Analyst

Review



#### **EPA METHOD 418.1 TOTAL PETROLEUM HYROCARBONS** QUALITY ASSURANCE REPORT

Client:

**QA/QC** 

Project #:

N/A

Sample ID:

QA/QC

Date Reported:

08-05-08

Laboratory Number:

08-04-TPH.QA/QC 46580

Date Sampled:

N/A

Sample Matrix:

Freon-113

Date Analyzed: Date Extracted: 80-0-80 08-04-08

Preservative: Condition:

N/A N/A

Analysis Needed:

TPH

Calibration

I-Cal Date

C-Cal Date

I-Cal RF:

C-Cal RF: % Difference

Accept. Range

08-01-08

08-0-08

1,790

1,750

2.2%

+/- 10%

Blank Conc. (mg/Kg)

**TPH** 

Concentration

Detection Limit

**Duplicate Conc. (mg/Kg)** 

**TPH** 

Sample

Duplicate

% Difference Accept. Range

+/- 30%

214

257

20.0%

Spike Conc. (mg/Kg)

**TPH** 

Sample Spike Added Spike Result % Recovery Accept Range

2,000

2,250

102%

80 - 120%

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

QA/QC for Samples 46558, 46559, 46561 - 46563, 46567, 46470, 46571 and 46576 - 46578.

5796 U.S. Highway 64 • Farmington, NM 87401 • Tel 505 • 632 • 0615 • Fax 505 • 632 • 1865

Two Copies	riate District O	ffice			State of No										rm C-105
District I 1625 N French Dr	, Hobbs, NM 8	88240		Energy,	Minerals an	ıd Na	tural Re	source	es	1. WELL API NO.				July 17, 2008	
District II 1301 W. Grand Av	enue, Artesia,	NM 88210		Oi	l Conserva	ition	Divisio	'n		30-045-34087					
<u>District III</u> 1000 Rio Brazos R	d , Aztec, NM	87410			20 South S					2 Type of Lease					
District IV 1220 S. St Francis	Dr. Santa Fe.	NM 87505		12	Santa Fe, 1			1.		☐ STATE ☐ FEE ☒ FED/INDIAN  3. State Oil & Gas Lease No.					
					····					SF-078046					
4. Reason for fil		ETION C	OR RE	COMPL	ETION RE	POF	RT AND	LOG	<del>)</del>	5. Lease Nam	o or I	Inst Agree	mont Non		
COMPLET	-	RT (Fill ın b	oxes #1	through #31	for State and Fe	ee wells	s only)			Hughes B 6 Well Num			———		
#33, attach this a	nd the plat to								and/or	23					
<ol> <li>Type of Comp</li> <li>NEW</li> </ol>	WELL   V	WORKOVE	R 🔲 D	EEPENING	□PLUGBAC	к 🗆	DIFFERE	NT RESI	ERVOII	R OTHER					
8 Name of Oper ConocoPhilli		. m. r.					-			9 OGRID 217817					
10 Address of O	perator									11 Pool name	or W	ildcat			-
PO Box 4298, Fa	armington, 'N	M 87499													
12.Location	Unit Ltr	Section	Ī	ownship	Range	Lot		Feet fr	om the	N/S Line	Fee	t from the	E/W Li	ne	County
Surface:						<u> </u>									
BH:					<u> </u>						<u>L</u>				
13 Date Spudde	d   14 Date	T.D. Reach	ed	15 Date Ri 03/22/2008	g Released		16.	Date Co	mpleted	d (Ready to Pro	duce)	- 1	7. Elevatio T, GR, etc		and RKB,
18 Total Measur	red Depth of	Well		19 Plug Ba	ck Measured De	pth	20	Was D	rection	al Survey Made	?	21. Typ	e Electric	and Ot	her Logs Run
22 Producing In	terval(s), of t	his complet	ion - Toj	p, Bottom, N	ame							<u> </u>			
23				CAS	SING REC	OR	D (Rep	ort all	strin	gs set in w	ell)				
CASING SI	ZE	WEIGHT	LB /FT		DEPTH SET			LE SIZI		CEMENTIN		CORD	AM	OUNT	PULLED
							477								
					· · · · · · · · · · · · · · · · · · ·			<del></del>							
		7													
					ED DECORD				105		PUIDI	NG DEC	ODD		
SIZE	TOP		BOTT		ER RECORD SACKS CEM		SCREE	1	25 SI	ZE		NG REC EPTH SET		PACK	ER SET
26. Perforation	record (inte	rval cize oi	ad numb	er)			27 40	ID SU	OT ED	ACTURE, CI	EME	T SOLI	EEZE E	TC	
20. Torioration	i iccora (inte	i vai, size, ai	ia namo	(CI)			DEPTH			AMOUNT A					
							-			<del>                                     </del>					
28		<del></del>				PRO	ODUC'	TION							
Date First Produ	ction	Pr	oduction	n Method (Fi	lowing, gas lift, j					Well Statu	s (Pro	d or Shut-	-ın)		
Date of Test	Hours To	ested	Choke	e Size	Prod'n For Test Period		Oıl - Bb	1	Ga	ıs - MCF	w	ater - Bbl		Gas - (	Oil Ratio
Flow Tubing Press	Casing F	Pressure	Calcu Hour	lated 24- Rate	Oil - Bbl		Gas	- MCF		Water - Bbl		Oıl Gra	wity - API	l - (Cor	r)
29 Disposition of	of Gas (Sold,	used for fue	l, ventea	l, etc.)	<u> </u>						30.	Test Witne	essed By		
31. List Attachm	ents										<u> </u>		***		
32. If a temporar	y pit was use	d at the wel	l, attach	a plat with t	ne location of th	e temp	orary pit								
33. If an on-site	burial was us	ed at the we	ll, repor	t the exact lo	cation of the on-	-site bu	ırial	<del></del>							
I hereby certi	for that the	Latitude	36.7138	82°N Lor	gitude 107.685	28°W	NAD 🔲	927 🛛	1983	to the best	of ver	knowla	dae en 1	halia	<del></del>
Signature	•	•	4	Pri	nted me Crystal	•			•			Date: /		-	
E-mail Addre	/	//			om							•	/' '1	-,0	

# ConocoPhillips

Pit Closure Form:		
Date: 8/19/08		
Well Name: Hughes B	<sup>±</sup> 23	_
Footages: <u> 5851 FN</u>	L 1408' FWL	Unit Letter:
Section: <u>2\</u> , T- <u>29</u>	-N, R- <u> </u>	Juan State: New Mexico
Contractor Closing Pit:	AtoZ	
Construction Inspector:	Johnny R. McDonald	Date: <u>8/19/08</u>
Inspector Signature:	Johnny R. M. Donald	

#### Powell, Brandon, EMNRD

From:

Busse, Dollie L [Dollie L Busse@conocophillips com]

Sent:

Wednesday, August 13, 2008 1:20 PM

To:

Powell, Brandon, EMNRD, Mark Kelly; Robert Switzer; Sherrie Landon

Cc:

jr\_mcdonald@msn.com; A&Z; Chavez, Virgil E; GRP:SJBU Production Foreman; GRP.SJBU Production Leads; Kramme, Jeff L; Larry Thacker; Blair, Maxwell O, Blakley, Maclovia, Clark, Joan E; Cornwall, Mary K (SOS Staffing Services, Inc.), Farrell, Juanita R, Maxwell, Mary

Alice, McWilliams, Peggy L, Seabolt, Elmo F

Subject:

Clean Up Notice - Hughes B 23

Importance: High

Attachments: Hughes b 23.rtf

**A&Z Contracting** will move a tractor to the **Hughes B 23** on **Saturday, August 16, 2008** to start the reclamation process. Please contact Johnny McDonald (215-2861) if you have any questions or need additional information

Thanks! Dollie

Network #:

10150379

Operator:

ConocoPhillips

Legals:

739' FNL, 2155' FWL

Section 21, T29N, R8W Unit Letter 'C' (NENW) San Juan County, NM

Lease:

SF-078046

API#:

30-045-34087

Surface/Minerals:

BLM/BLM

<<Hughes b 23 rtf>>


Dollie L. Busse


ConocoPhillips Company-SJBU Construction Technician Project Development 505-324-6104 505-599-4062 (fax) Dollie.L.Busse@conocophillips.com


This inbound email has been scanned by the MessageLabs Email Security System.


## ConocoPhillips Reclamation Form:

Date: 8/24/08	
Well Name: Hughes B #23	
Footages: 1585' FNL 1468' FWL Unit Letter:	
Section: 21 , T- 29 -N, R- 8 -W, County: <u>Section</u>	
Reclamation Contractor: A to Z	,
Reclamation Date: 8/20/08	
Road Completion Date: 8/20/08	
Seeding Date: 8/23/08	
Johnsy R. McDeneld 8/26/08 Construction Inspector Name Date	
Construction Inspector Name Date    Journal Of Construction Inspector Name   Date   Journal Of Construction Inspector Name   Date   Journal Of Construction Inspector Name   Date	ConocoPhillips
Signature	
Daylord 0.(6)(00	









## WELL PAD SAFETY AND ENVIRONMENTAL CHECK LIST

WELL NAME: Hughes B #23

API#: 30-045-34087

DATE	INSPECTOR	SAFETY	LOCATION CHECK	PICTURES TAKEN	COMMENTS
4/3/08	Art Sanchez	Х	Х	Χ	Called contractor to repair fence
4/11/08	Art Sanchez	Х	Х	Х	Rig on location
4/23/08	Art Sanchez	Х	Х	Х	Called contractor to repair fence and rekey liner
4/30/08	Art Sanchez	Х	Х	Х	Called contractor to repair fence
5/8/08	Art Sanchez	Х	Х	Х	
5/15/08	Art Sanchez	Х	Х	Х	
5/28/08	Rodney Woody	Х	Х	Х	Rig on location
6/5/08	Rodney Woody	Х	, X	X	Called contractor for liner repair and fence called Brandon with OCD
6/12/08	Rodney Woody				Flow back on location
6/19/08	Rodney Woody	Х			Rig on location
6/26/08	Rodney Woody	X	Х	Х	Fence Split, blow pit melted
7/3/08	Rodney Woody	Х	Х	Х	Pit and location look good, Herbert's on location
7/10/08	Rodney Woody	Х	Х	Х	Called contractor to patch holes, called OCD
7/24/08	Rodney Woody	Х	Х		Pit and location look good
7/31/08	Rodney Woody	Х	Х		Pit and location look good
8/7/08	Rodney Woody	Х	Х		Pit and location look good
8/14/08	Rodney Woody	Х	Х	/	Pit and location look good
8/17/08	Rodney Woody	Х	Х		Pit and location look good
8/19/08	J. McDonald				Pit Closed