

(SUBMIT IN TRIPLICATE)

Land Office Navajo TribalLease No. I-149-Ind.-7654

Unit _____

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

30045 29858

RECEIVED

SEP 4 1952

SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|--|--|---|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF | |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF REDRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT | X |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Sept. 2, 1952

Well No. 740-1 is located 660 ft. from [N] line and 660 ft. from [E] line of sec. 5

| | | |
|---|--|---|
| <u>SE/4</u> <u>5</u> (1/4 Sec. and Sec. No.) | <u>30 North</u> <u>17 West</u> (Twp.) (Range) | <u>N.M.P.M.</u> (Meridian) |
| <u>Wildcat</u> (Field) | <u>San Juan</u> (County or Subdivision) | <u>New Mexico</u> (State or Territory) |

The elevation of the ~~derrick~~ ^{Ground} floor above sea level is 5064 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

The following is our notice of cementing and abandonment of above described well.

- (1) A continuous cement plug run from T.D. 1367 feet back thru the top of the Dakota 1040 feet. (40 sacks cement.)
- (2) A 60 foot plug placed thru the Tocito 480 feet to 540 feet. (7 sacks cement.)
- (3) A 20 foot plug was placed at the bottom on casing 90 feet to 110 feet. (3 sacks cement.)
- (4) A 15 foot plug was placed from 15 feet back into cellar. (3 sacks cement.)
- (5) ~~A well marker of 4 inch pipe was set and cemented:~~
~~Below surface 40 inches.~~
~~Above natural surface 5 feet.~~

Pits were filled and location leveled.

No marker required.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Phillips Petroleum CompanyAddress 400 West Frank Phillips Blvd.Bartlesville, Oklahoma.By P. H. HulseyTitle Core Drill Mgr.