

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Navajo Tribal
Lease No. I-149-Ind.-7654
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

SEP 2 1952

U. S. GEOLOGICAL SURVEY

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Aug. 29, 1952

Well No. 740 is located 660 ft. from SW line and 660 ft. from EW line of sec. 5
SE/4 5 30 North 17 West N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wilcox San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the Ground floor above sea level is 5064 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

The following is to be out notice of our intentions to plug and abandon the above described hole.

- (1) A continuous cement plug from T.D. 1367 ft\$ back thru the top of the Dakota 1040 ft\$ 40 sacks cement.
- (2) 60 feet plug thru the Tecite. 480' to 540' 7 sacks Cement.
- (3) 20 feet plug at the bottom of casing 90' to 110' 3 sacks cement.
- (4) 15 foot plug 15' to in cellar 3 sacks Cement.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Phillips Petroleum Company
Address 400 W. Frank Phillips Blvd.
Bartlesville, Oklahoma.

By

Title Asst. Core Drill Supt.