Form 3160-5 --(August 2007)

### UNITED STATES . DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an

FORM APPROVED OMB NO. 1004-0137 Expires July 31, 2010

5. Lease Serial No.

NMSF-	'n	70	Λ	Q	o
	U.	<i>,</i> 0	u	o	-

6. If Indian, Allottee or Tribe Name

abandoned well. Use For	rm 3160-3 (APD) for si	ich proposals.			
SUBMIT IN TRIPLICA	TE - Other instructions	on pageRECE	IVED	7. If Unit or CA/Agreement, Name and/or No	
1. Type of Well					
Oil Well X Gas Well Other		MAR 2 6	2010	8. Well Name and No	
2. Name of Operator		<del></del>		SCOTT E FEDERAL 25 #32	
XTO ENERGY INC.		Bureau of Land Fermination F	Managemen	9 API Well No	
3a. Address	31	p. Phone No. (include area	code)	30-045-28486	
382 CR 3100 AZTEC, NM 87410		505-333-3100		10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey				W. KUTZ PICTURED CLIFF	
1190' FNL & 1510' FEL NWNE SEC 2	25 (B) -T27N-R11W			11 Canada a Parida Stata	
İ				11. County or Parish, State	
12. CHECK APPROPRIATI	E BOX(ES) TO INDIC	ATE NATURE OF NO	TICE, REPO	SAN JUAN NM RT. OR OTHER DATA	
TYPE OF SUBMISSION		ТҮРЕ			
X Notice of Intent	Acidize	Deepen	Production	(Start/Resume) Water Shut-Off	
Sub	Alter Casing	Fracture Treat	Reclamation	Well Integrity	
Subsequent Report	Casing Repair	New Construction	Recomplete	Other	
Final Abandonment Notice	Change Plans	X Plug and Abandon	Temporarily	/ Abandon	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disp	osal	
testing has been completed. Final Abandonment determined that the final site is ready for final inspe  XTO Energy Inc. proposes to plug	ection.)	·	-		
	_		EDTE PORMET TARE		
			OIL CONS. DIV.		
	, Not	ify NMOCD 24 hrs ior to beginning operations		DIST. 3	
14. I hereby certify that the foregoing is true and correct Name ( <i>Printed/Typed</i> )					
BARBARA A. NICOL	Title REGULATORY COMPLIANCE TECHNICIAN				
Signature Ballara a. Nic	Date 03/25/2010				
THIS	S SPACE FOR FEDER	AL OR STATE OFFIC	CE USE		
Approved by Original Signed: Stephen Mas	son	Title	Date APR 0 2 2010		
Conditions of approval, if any, are attached. Approval of this not the applicant holds legal or equitable title to those rights in the sul entitle the applicant to conduct operations thereon.	tice does not warrant or certify the bject lease which would	DOD Sffice		_	
Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212	makes it a crime for any person	knowingly and willfully to make	to any denartmen	of or agency of the United States any false	

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

## Scott E Federal 25 #32

Location:

1,190' FNL & 1,510' FEL, Unit B, Section 25, T27N, R11W, San Juan County, NM

API:

30-045-28486

Perfs:

Pictured Cliffs - 1,754'-1,767'

Fruitland Coal (squeezed 08/91) - 1,733'-1,742'

#### PLUG AND ABANDONMENT PROCEDURE

Note: All cement volumes use 100% excess outside pipe and 50' excess inside. The stabilizing wellbore fluid will be 8.3 ppg, sufficient to balance all exposed formation pressures. All cement will be Class B, mixed at 15.6 ppg with a 1.18 cf/sx yield.

- 1. This project requires the Operator to obtain an approved NMOCD C-144 CLEZ Closed-Loop System Permit for the use of an approved steel tank to handle waste fluids circulated from the well and cement wash up.
- 2. Install and test location rig anchors. Comply with all NMOCD, BLM, and Operator safety regulations. MOL and RU daylight pulling unit. Conduct safety meeting for all personnel on location. Record casing, tubing and bradenhead pressures. NU relief line and blow down well. Kill well with water as necessary and at least pump tubing capacity of water down the tubing. ND wellhead and NU BOP. Function test BOP.
- 3. Round trip a 5-1/2" casing scraper to 1,750'; not a wireline gauge ring.
- 4. Plug #1 (Pictured Cliffs and Fruitland Coal, 1,750' 1,330'): TIH and set cement retainer at 1,750'. Mix 56 sxs cement and spot a balanced plug inside the casing to cover the Pictured Cliffs and Fruitland Coal intervals. TOH.

- 5. Plug #2 (Kirtland and Ojo Alamo, 870'- 645'): TIH and spot 38 sxs cement as a balanced plug inside the casing to cover the Kirtland and Ojo Alamo intervals. TOH and WOC. TIH and tag cement.
- 6. Plug #3 (Casing shoe 355' Surface): Mix approximately 48 sxs and pump cement inside the 5-1/2" casing to the surface. Shut in well and WOC.
- 7. ND BOP and cut off casing below surface casing flange. Install P&A marker with cement to comply with regulations. RD, move off location, cut off anchors and restore location.

Tops:

Oio Alamo 665' Kirtland 8201 Fruitland Coal 1,385' Pictured Cliffs 1.750'

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT FARMINGTON DISTRICT OFFICE

1235 LA PLATA HIGHWAY FARMINGTON, NEW MEXICO 87401

Attachment to notice of Intention to Abandon:

Re: Permanent Abandonment Well: 32 Scott E Federal 25

#### CONDITIONS OF APPROVAL

- 1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal and Indian Lease."
- 2. Farmington Office is to be notified at least 24 hours before the plugging operations commence (505) 599-8907.
- 3. The following modifications to your plugging program are to be made:
- a) Place the Kirtland/Ojo Alamo plug from 870' 567'.

You are also required to place cement excesses per 4.2 and 4.4 of the attached General Requirements.

Office Hours: 7:45 a.m. to 4:30 p.m.