

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

**RECEIVED**

APR 07 2010

## Sundry Notices and Reports on Wells

Bureau of Land Management  
Farmington Field Office1. Type of Well  
GAS

2. Name of Operator

**ConocoPhillips**

3. Address &amp; Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit F (SENW), 1510' FNL &amp; 1970' FWL, Section 5, T29N, R10W, NMPM

5. Lease Number  
SF-078194
6. If Indian, All. or  
Tribe Name
7. Unit Agreement Name
8. Well Name & Number  
Ludwick LS 19P
9. API Well No.  
30-045-35094
10. Field and Pool  
Blanco MV / Basin DK
11. County and State  
San Juan, NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

## Type of Submission

## Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - Casing Report☒ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection**13. Describe Proposed or Completed Operations**

03/30/2010 MIRU AWS 730. NU BOPE. PT csg to 600#/30min @ 15:30hrs on 4/1/10. Test - OK. ✓

04/01/2010 RIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 4150' - Inter TD reached 4/3/10. Circ. hole & RIH w/ 103jts total. 97jts, 7", 20#, J-55 ST&C and 6jts, 7", 23#, J-55 ST&C set @ 4132'. 4/3/10 RU to cmt. Pre-flush w/ 10bbls FW, 10bbls GW, 10bbls FW. Pumped scavenger 19sx (57cf-10bbls) Premium lite cmt w/ 3% CACL, .25pps celloflake, 5pps LCM-1, .4% FL-52, .4% SMS, 8% bentonite. Lead w/ 460sx (980cf-174bbls) Premium lite cmt w/ 8% bentonite, 3% CACL2, .25pps celloflake, .4% FL-52, 5pps LCM-1, .4% SMS. Tail w/ 97sx (134cf-24bbls) Type III cmt w/ 3% CACL2, .25pps celloflake, .2% FL-52. Drop plug & displaced w/ 165bbls FW. Bump plug. Circ. 65bbls cmt to surface. Plug down @ 03:46hrs on 4/4/10. RD cmt. WOC. ✓

04/04/2010 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 12:00hrs on 4/4/10. Test - OK. ✓ Drilled ahead w/ 6 1/4" bit to 6748' (TD) TD reached 4/5/10. Circ. hole & RIH w/ 165jts, 4 1/2", 11.6#, L-80 LT&C set @ 6747'. 4/6/10 RU to cmt. Pre-flush w/ 10bbls CW, 2bbls FW. Pumped scavenger 9sx (28cf-5bbls) Premium lite cmt w/ .25pps celloflake, .3% CD-32, 6.25pps LCM-1, 1% FL-52. Tail w/ 181sx (358cf-64bbls) Premium lite cmt w/ .3% CD-32, .25pps celloflake, 1% FL-52, 6.25pps LCM-1. Drop plug & displaced w/ 105bbls FW. Bump plug. Plug down @ 10:20hrs on 4/6/10. RD cmt. WOC. ND BOPE. NU WH. RD RR @ 16:00hrs on 4/6/10 ✓

PT will be conducted by Completion Rig. Results &amp; TOC will appear on next report. ✓

**14. I hereby certify that the foregoing is true and correct.**Signed Crystal Tafoya Crystal TafoyaTitle Regulatory TechnicianDate 4/7/2010

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U S C Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

NMOCD B 4/16

ACCEPTED FOR RECORD
APR 07 2010
FARMINGTON FIELD OFFICE
BY <u>T. Salas</u>