submitted in lieu of Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIVED

MAY **03** 2010

FARMINGTON FIELD OFFICE

Bureau of Land Management Farmington Field Office Sundry Notices and Reports on Wells 5. Lease Number SF-080854 Type of Well If Indian, All. or 6. GAS **Tribe Name** 7. **Unit Agreement Name** Name of Operator San Juan 32-8 Unit **Conoco**Phillips 8. Well Name & Number Address & Phone No. of Operator San Juan 32-8 Unit 29P PO Box 4289, Farmington, NM 87499 (505) 326-9700 9. API Well No. 30-045-35072 Location of Well, Footage, Sec., T, R, M 10. Field and Pool Surface: Unit O (SWSE), 769' FSL & 1740' FEL, Section 11, T31N, R8W, NMPM Blanco MV / Basin DK Bottomhole: Unit O (SWSE), 1225' FSL & 1840' FEL, Section 11, T31N, R8W, NMPM 11. **County and State** San Juan, NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Action Notice of Intent Abandonment Change of Plans X Other --Casing Report Recompletion New Construction RCVD MAY 5'10 Subsequent Report Plugging Non-Routine Fracturing Casing Repair Water Shut off OTL CONS. DIV. Conversion to Injection Final Abandonment **Altering Casing** DIST. 3 13. Describe Proposed or Completed Operations **04/24/2010** MIRU AWS 730. NU BOPE. PT csg to 60<u>0#/30m</u>in @ 3:30hrs on 4/25/10. Test - OK 04/25/2010 RIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3817' - Inter TD reached 4/26/10. Circ. hole & RIH w/ 88jts, 7", 23#, J-55 LT&C set @ 3800' w/ST @ 3067'. 04/27/10 RU to cmt. 1st Stage - Pre-flush w/ 10bbls GW, 2bbls FW. Pumped scavenger 19sx (57cf-10bbls) Premium lite cmt w/ 3% CACL, .25pps celloflake, 5pps LCM-1, .4% FL-52, .4% SMS, 8% bentonite. Tail w/ 90sx (124sx-22bbls) Type III cmt w/ 1% CACL2, .25pps celloflake, .2% FL-52. Drop plug & displaced w/ 150bbls FW. Bump plug. Plug down @ 17:11hrs. Open ST & Circ. 17bbls cmt to surface. WOC. 2nd Stage - Pre-flush w/ 10bbls FW, 10bbls GW, 10bbls FW. Pumped scavenger 19sx (57cf-10bbls) Premium lite cmt w/3% CACL, .25pps celloflake, 5pps LCM-1, .4% FL-52, .4% SMS, 8% bentonite. Lead w/382sx (814cf-145bbls) Premium lite cmt w/8% bentonite, 3% CACL2, .25pps celloflake, .4% FL-52, 5pps LCM-1, .4% SMS. Drop plug & displaced w/ 121bbls FW. Bump plug & close ST. Circ. 50bbls cmt to surface. ✓Plug down @ 22:10hrs on 4/27/10. RD cmt. WOC. 04/28/2010 RIH w/ 6 1/4" bit. Drill out ST @ 3067'. PT 7" csg to 1500#/30min @ 9:30hrs on 4/28/10. Test - OK. Drilled ahead w/ 6 1/4" bit to 8260' (TD) TD reached 4/29/10. Circ. hole & RIH w/ 201jts, 4 1/2", 11.6#, L-80 LT&C set @ 8227'. 4/30/10 RU to cmt. Pre-flush w/ 10bbls CW, 2bbls FW. Pumped scavenger 9sx (28cf-5bbls) Premium lite cmt w/.25pps celloflake, .3% CD-32, 6.25pps LCM-1, 1% FL-52. Tail w/315sx (624cf-111bbls) Premium lite cmt w/.3% CD-32, .25pps celloflake, 1% FL-52,6.25pps LCM-1. Drop plug & displaced w/ 128bbls FW. Bump plug. Plug down @ 18:00hrs on 4/30/10. RD cmt. WOC. ND BOPE. NU WH. RD RR @ 06:00hrs on 5/1/10 ✔ PT will be conducted by Completion Rig. Results & TOC will appear on next report. \checkmark 14. I hereby certify that the foregoing is true and correct. Date <u>5/3</u>/2010 Crystal Tafoya Signed Title Regulatory Technician (This space for Federal or State Office use) ACCEPTED FOR RECORD APPROVED BY Title Date CONDITION OF APPROVAL, if any: MAY 0 4 2010 Title 18 U S C Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction