Submit 3 Copies To Appropriate District Office	Energy, Minerals and Natural Resources		Form C-103 June 19, 2008
District I 1625 N. French Dr., Hobbs, NM 88240			WELL API NO.
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION		60-039-30857 i. Indicate Type of Lease
District III 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Fran Santa Fe, NM 87	icis Dr.	STATE FEE 🛛
<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa 1 0, 14141 07 505		5. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			'. Lease Name or Unit Agreement Name Avella Sultemeier
1. Type of Well: Oil Well 🕅 Gas Well 🗌 Other			3. Well Number #2
2. Name of Operator Approach Operating, LLC			O. OGRID Number 248343
3. Address of Operator			0. Pool name or Wildcat
6500 West Freeway, Suite 800, Fort Worth, TX 76116		7	WC; Mancos
4. Well Location			
Unit Letter L : Section 21	1662feet from theSouth Township 28N	line and 6 Range 04E	feet from theWestline  NMPM Rio Arriba County
11. Elevation (Show whether DR, RKB, RT, GR, etc.)			
7716' GR			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
		REMEDIAL WORK	☐ ALTERING CASING ☐
·		COMMENCE DRILL CASING/CEMENT J	<del></del>
DOWNHOLE COMMINGLE	MOETH CE COMPE	CASING/CEMENTS	OB []
OTUCD.	m	OTHER.	
OTHER:  OTHER:			
Approach Operating, LLC proposes to alter the approved drilling plan as follows:			
Drill a 12-1/4" hole and set 8-5/8", 32#, J-55, ST&C casing at 350' and cement to the surface with 245 sx (289 cu.ft.) of Type III cement with ½ pps celloflake, and 3% CaCl <sub>2</sub> . 100% excess to circulate cement to surface.			
Drill a 6-1/4" hole with air-mist through the Greenhorn formation as determined by a mud logger. Fill the open hole with frac sand			
from TD to above any oil shows. Run 5-1/2", 15.5#, J-55, ST&C casing from the top of the sand fill to surface. Cement to surface with a lead cement consisting of Type III cement with 2% SMS and ¼ pps celloflake and tail with 75 sx (89 cu.ft.) of Type III cement			
with ¼ pps celloflake. Cement volumes calculated to provide a 100% excess to circulate cement to surface.			
Drill out the shoe joint and clean out the open hole to TD with a 4-3/4" bit with air-mist. Run a 4" flush joint slotted liner from TD to 100' above the 5-1/2" casing shoe. No liner hanger will be used and the 4" liner will not be cemented.			
			RCVD JUN 11'10
Spud Date:	Rig Release Date:		OIL CONS. DIV. DIST. 3
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE Paul C. Th	TITLE A	gent/Engineer	DATE6/4/10
Type or print name _Paul C. Thomps For State Use Only			
APPROVED BY:	TITLE	Oil & Gas Inspection #3	DATE JUN 1 1 2010
Conditions of Approval (if any):  PROLITION FOR NSL PENDING			
About a care of the second of			