District I

1625 N. French Dr., Hobbs, NM 88240

1301 W. Grand Ave , Artesia. NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410 District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico

Energy Minerals and Natural Resources

Department Oil Conservation Division 1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-144 July 21, 2008

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

5506

Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

l'ype of action:	X Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Modification to an existing permit
	Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual plt, closed-loop system, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of hability should operations result in pollution of surface water, ground water or the

environment. Nor does approval relieve the operator of its responsibility to comply with any other a	applicable governmental authority's rules, regulations or ordinances.
Operator: Burlington Resources Oil & Gas Company, LP	OGRID#: 14538
Address: PO Box 4289, Farmington, NM 87499	
Facility or well name: ATLANTIC A 8B	·
API Number: 30-045- 35086 OCD Perm	it Number:
U/L or Qtr/Qtr: E(SW/NW) Section: 29 Township: 31N Rang-	e: 10W County: San Juan
Center of Proposed Design: Latitude: 36.87146 °N Longitud	, , , , , , , , , , , , , , , , , , , ,
Surface Owner: X Federal State Private Tribal Trust	or Indian Allotment
String-Reinforced Liner Scams: Welded Factory Other Volume: Welded Factory Other Volume:	DPE HDPE PVC Other bbl Dimensions L x W x D pplies to activities which require prior approval of a permit or
X Drying Pad X Above Ground Steel Tanks Haul-off Bins Other X Lined Unlined Liner type: Thickness 20 mil X LLD Liner Seams X Welded X Factory Other	PE HDPE PVD Other
Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: bbl Type of fluid: Fank Construction material: Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift Visible sidewalls and liner Visible sidewalls only Other Liner Type: Thicknessmil HDPE PVC O	and automatic overflow shut-off
S. Alternative Method: Universal of an exception recases: 12 / Squined	

6 Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks)	— , ,				
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify					
JARIETHARE, Prease specify					
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)					
8					
Signs; Subsection C of 19,15.17.11 NMAC		}			
12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers					
X Signed in compliance with 19.15.3.103 NMAC					
9 Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.					
Please check a box if one or more of the following is requested, if not leave blank:					
Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for considerating (Fencing/BCT Liner)	deration of appr	roval.			
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval,	dj t dd - t				
10					
Siting Criteria (regarding normitting) 19.15.17.10 NMAC Instructions: The application must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.					
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - tWATERS database search; USGS; Data obtained from nearby wells	Yes	□No .			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes _	No			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No			
(Applies to temporary, emergency, or cavitation pits and below-grude tanks)	□NA	1			
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	-	1			
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits)	Yes NA	No			
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image					
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	∐Yęs	∏и́о			
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.					
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, se amounded - Written confirmation or verification from the municipality. Written approval obtained from the municipality	∏Yes	∏No •			
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification man; Topographic map; Visual inspection (certification) of the proposed site	Yes	□Nọ			
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	□ио			
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Sections Transport to man.	Yes	∏ис			
Society; Topographic mep 、 Within a 100-year foodplate 产品体系面积) Jye	Tive			

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the bax, that the documents are attached.
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15,17.9 NMAC
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9.
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of
19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API or Permit
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9
Siting Criteria Comphance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC
X Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
X Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
X Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API
Previously Approved Operating and Maintenance Plan API
13
Permaneut Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15 17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freehoard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazurdous Odors, including H2S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank X Closed-loop System Alternative
Proposed Closure Method: Waste Excavation and Removal
X Waste Removal (Closed-loop systems only)
On-site Closure Method (only for temporary pits and closed-loop systems)
☐ In-place Buriai ☐ On-site Trench
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
Waste Excavation and Removal Closure Plan Checklist (19.13.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check wask in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC
Disposal Facility Name and Permit Number (for liquids, drilling Ilvicis and will unitings)
Set. Backett and Cover-Design Spagify at the appropriate requirements of Coherente Hoff 19 (3:17.13 MHAC
Re-regeration Find - based prom the approximate requirements of Schools of National Find (1) Find C

16 dia	,				
Waste Removal Closure For Clused-loop Systems That Utilize Above Ground Steel Tanks or Hanl-off Bins Only: (19.15.17.13.D NMAC) Instructions: Please identify the facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if more than his facilities are required.	g .				
Disposal Facility Name: Envirotech / JFJ Landfarm % IEl Disposal Facility Permit #: NM-01-0011 / NM-01-	00 10B				
Disposal Facility Name: Basin Disposal Facility Disposal Facility Permit #: NM-01-005					
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will nbe used for future Yes (If yes, please provide the information No	service and				
Required for impacted areas which will not be used for future service and operations: Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection II of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC	√MAC ^				
17 Siting Criteria (Regarding on-site closure methods only: 19.15.17.10 NMAC Instructions, Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below certain siting criteria may require administrative approval from the appropriate district office or may be considered in exception which must be submitted to the coffice for cansideration of approval. Justifications analyse demonstrations of aquivalency are required. Please refer to 19.15 17.10 NMAC for guidance.					
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS: Data obtained from nearby wells	Yes No				
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - IVATERS database search; USGS; Data obtained from nearby wells	Yes No				
Ground water is more than 100 feet below the bottom of the buried waste.	Yes No				
- NM Office of the State Engineer - IVATERS database search; USGS, Data obtained from nearby wells	M/A				
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	Yes No				
- Topographic map; Visual inspection (certification) of the proposed site					
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; satellite image	Yes No				
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existence at the time of the initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site. Within incorporated managinal households or within a defined managinal feet, unter well field covered under a numerical continuous adopted.					
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted Yes No pursuant to NMSA 1978. Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality					
Within 500 feet of a wetland - US Fish and Wildlife Wetland Identification map: Topographic map: Visual inspection (certification) of the proposed site	Yes No				
Within the area overlying a subsurface mine.	Yes No				
 Written confirantion or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; 	Yes No				
Topographic map					
Within a 100-year floodplain FEMA map	Yes No				
18 On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must bee attached to the cloby a check mark in the box, that the documents are attached.	osure plan. Please indicate,				
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.35.17.10 NMAC	•				
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC					
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15 17.11 NMAC					
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15 17 11 NMAC					
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC					
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC					
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection P of 19,.5,17,13 NMAC					
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate resurrements of Subsection H of 19 10.17.13 NiviAC					
Re-vegetation Plan - based imore the appropriate requirements of Subsection 1 of 19 15.17.13 NWAC					
2.14 Michigativa Pini - brusi aras the appropriate rentisprosts of Subsection O of 19.15.17.13 NMAC					

19 Danuaran Anakar	-# C# G #-						
	ation Certification the information sub-	nitted with this application is t	mie, accurate and con	inlete to the heet	of my knowledge and	l belief	
Nume (Print):		/ Marie E Jaramillo	Ti		Staff, Regulatory		
Signature:	The A Was	2000	Da		<u>त्राव</u>	17	
•		jaramillo@conocophillips.co			50S-326	37 V	
e-mail address:	, mane.e.	jaranimo(d)conocopnilips.co	an ter	phone;	* 303-320	-9803	
- 0		*************************************					**************************************
QCD Approval:	Permit Appli	ication (including closure p	lan) 🗍 Closur	Plan (only)	OCD Condition	as (see attachmen	t)
		01	7 00			•	
OCD Representa	itive Signature:	Bare			Approval	Date: <u>6</u>	17/10
'l'itle:	Eusiro	le sec		OCD Permi	t Number		,
Titte.	2.(3(7)	3000		OCD T EI HII			
Instructions: Operative report is required to	tors are required to the	of days of closure complete obtain an approved clastere ple division within 60 days of the d and the closure activities has	an prior to implement completion of the clos	ing any closure i ure activities. I			
_	ivation and Removal from approved plan.		Měthod Alter	native Closure M	fethod Waste	Removal (Closed-lo	юр systems only)
23							
Closure Report Re		noval Closure For Closed-loo or facilities for where the liqu					
Disposal Facility	y Name:		· Oi	sposal Facility (ennit Number:		
Disposal Facility	y Name:		D	spòsal Facility F	ermit Number:		
Were the closed	-loop system operation	ons and associated activities po	erfonned on or in area	is that will not	be used for future serv	rice and opeortions?	Ť
Yes (If yes.	please demonstrate	complitanc to the items below)) No				
		vill not be used for flatire servi	ice and operations:				
	nation (Photo Docum						, -
=	lling and Cover Insta						
Re-vegetati	on Approximan Rate	s and Seeding Technique					
the box, that the	e documents are atta		of the following tem	s must be attack	ied to the closure repo	ort. Please indicate	, by a check mark in
· · · · ·	•	face owner and division)					
=		red for on-site closure) es and temporary pits)					
<u></u>	-		(6)				
		dytical Results (if applicable to the land)					
<u>—</u>	terial sampling At Facility Name and	nalytical Results (if applical Permit Number	oloj		•		
	facinty Name and filling and Cover I	, ,					
	-	nsumation Lates and Seeding Techniqu	ıė				
	mation (Photo Do						
	losure Location:	Latitude:	Lou	gitudo.	1	NAD 1927	☐ Î1983 •
, On-Mile Cl							
		·····					
25 Operator Closus	re Certification						
I hereby certify that	t the information and	d attachments submitted with t				of my knowledge a	nd belief. I also certify that
the closure complie	s with all applicable	s clasure requirements and con	nditions specified in th	ie approved clos	ure plan.		
Name (Print):	_			Tide:			
, Signature.		4	and the same of th	Date:	·		
: ගුළ-ආත්ථ පේල්පලා:				eianhone			
Sketters Schönger)	THE PERSON NAMED IN THE PERSON NAMED IN	manager (may make) and and manager of the control		- Artani	and the second of the second	Baran maren a maren	- washing any

Burlington Resources Oil & Gas Company, LP

Closed Loop Design:

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

Burlington Resources Oil & Gas Company, LP may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19.15.17.11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15.3.103.NMAC. Frac tanks will be utilized on site for fresh water storage.

Closed Loop Operations and Maintenance:

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows:

- Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). Reuse may include the relocating of liquids to be used in other permitted drilling operations.
- 2. Drill solids will be recovered from location and hauled to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burlal of cuttings will occur.
- 3. In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). The liner will be disposed of at the San Juan County Landfill located on CR 3100. The drying pad will be closed within 6 months from the date that the drilling rig is released. Berms constructed from native materials will be bladed on site to the location's contour.
- 4. Any drilling materials or trash will be stored and disposed of appropriately:
- 5. The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately.

Closed'Loop'Closure Plan:

1. Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B). Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % industrial Ecosystem Inc. (Permit #NM-01-0010E) within 6 months from the date that the drilling halfs (elasso).

2. After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

- 3. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4. Notification will be sent to OCD when the reclaimed area is seeded.
- 5. BR shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality) Purity 50 percent Germination 40 percent

Percent PLS 20 percent 5 lb. bulk seed required to make

Source No. two (better quality):

80 percent Purity 83 percent? Germination Percent PLS 50 percent

2 lb. bulk seed regulred to make

1 lb. PLS

1 lb. PLS