Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals. FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

Lease Serial No. NMSF078424

6.	If Indian,	Allottee or	Tribe	Name	

SUBMIT IN T	RIPLICATE - Other instru	ctions on reverse side.	7. If Unit o	or CA/Agreement, Name and/or No. 178417C	
 Type of Well ☐ Oil Well ☐ Gas Well ☐ Gas Well 	Other			8. Well Name and No. SAN JUAN 29-7 UNIT 191	
2. Name of Operator BURLINGTON RESOURCE	Contact:	TAMMY WIMSATT E-Mail: twimsatt@br-inc.com		9. API Well No. 30-039-27474-00-X1	
		3b. Phone No. (include area coo			
3a. Address PO BOX 4289 FARMINGTON, NM 87499 3b. Phone No. Ph: 505.599 Fx: 505.326.			BASIN	10. Field and Pool, or Exploratory BASIN FRUITLAND COAL BLANCO PICTURED CLIFFS	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			11. County or Parish, and		
Sec 22 T29N R7W NWSE	1855FSL 1755FEL		RIO A	RRIBA COUNTY, NM	
12. CHECK AP	PROPRIATE BOX(ES) T	O INDICATE NATURE OF	NOTICE, REPORT, O	OR OTHER DATA	
TYPE OF SUBMISSION		ТҮРЕ	OF ACTION		
Nisting of Internal	Acidize	Deepen	Production (Start/R	Resume) Water Shut-Off	
Notice of Intent	Alter Casing	Fracture Treat	☐ Reclamation	☐ Well Integrity	
Subsequent Report	Casing Repair	☐ New Construction	Recomplete	Other	
Final Abandonment Notice	☐ Change Plans	Plug and Abandon	☐ Temporarily Abanc	don Change to Original A	
	Convert to Injection	Plug Back	☐ Water Disposal		
If the proposal is to deepen direct Attach the Bond under which the following completion of the invol testing has been completed. Final determined that the site is ready for	operation (clearly state all pertine onally or recomplete horizontally work will be performed or provided operations. If the operation represents the complete shall be for final inspection.)	ent details, including estimated star give subsurface locations and mea e the Bond No. on file with BLM/E esults in a multiple completion or re- filed only after all requirements, included the subject well according to	asured and true vertical depths BIA. Required subsequent rep ecompletion in a new interval luding reclamation, have been	s of all pertinent markers and zones. ports shall be filed within 30 days a Form 3160-4 shall be filed once	
If the proposal is to deepen direct Attach the Bond under which the following completion of the invol testing has been completed. Final determined that the site is ready for It is intended to revise the a following: Cement with 88 sxs Type II excess, bring cement to su compressive strength at 60	Operation (clearly state all pertine onally or recomplete horizontally work will be performed or provided operations. If the operation representation of the performed of provided operations. If the operation of the performed operation of the performed operation.) Approved surface cement in the performed operation of the performed operation. Wait on cement appeared of the performed operation of the performance of the performed or provide operation of the performance of the	give subsurface locations and mea e the Bond No. on file with BLM/E esults in a multiple completion or re- iled only after all requirements, inc	asured and true vertical depths BIA. Required subsequent rep ecompletion in a new interval luding reclamation, have been to the (113 cu. ft., 200% chieves 250 psi t for 8 hrs for	s of all pertinent markers and zones. ports shall be filed within 30 days a Form 3160-4 shall be filed once	
If the proposal is to deepen direct Attach the Bond under which the following completion of the involusiting has been completed. Final determined that the site is ready for the involusion of the involusion of the involusion of the involusion of the involution of t	Operation (clearly state all pertine onally or recomplete horizontally work will be performed or provided operations. If the operation represents the operation of the operation	g, give subsurface locations and mea e the Bond No. on file with BLM/E esults in a multiple completion or re- iled only after all requirements, inc in the subject well according to loflake, 3% calcium chloride propriate time until cement ac- up of BOPE. Wait on cemen	asured and true vertical depths BIA. Required subsequent rep ecompletion in a new interval luding reclamation, have been to the (113 cu. ft., 200% chieves 250 psi t for 8 hrs for	s of all pertinent markers and zones. ports shall be filed within 30 days a Form 3160-4 shall be filed once	
If the proposal is to deepen direct Attach the Bond under which the following completion of the invol testing has been completed. Final determined that the site is ready for It is intended to revise the a following: Cement with 88 sxs Type II excess, bring cement to su compressive strength at 60 ventionally set holes before 600 psi for 30 minutes.	poperation (clearly state all pertine onally or recomplete horizontally work will be performed or provided operations. If the operation represents the performed or provided operations. If the operation represents the performed operation represents the performed operation of the performed surface cement in the performed surface cement in the performed surface of the performed operation op	give subsurface locations and meae the Bond No. on file with BLM/E sults in a multiple completion or relied only after all requirements, incoming the subject well according to the subject well according to loflake, 3% calcium chloride propriate time until cement accup of BOPE. Wait on cement out from under surface. Test was a country of the subject well according to the subject well according to loflake, 3% calcium chloride propriate time until cement accup of BOPE. Wait on cement out from under surface. Test was a country of the subject with the subject well according to the subject with the subject well according to the subject wel	asured and true vertical depths BIA. Required subsequent rep ecompletion in a new interval luding reclamation, have been to the (113 cu. ft., 200% chieves 250 psi it for 8 hrs for st casing to	s of all pertinent markers and zones. sorts shall be filed within 30 days , a Form 3160-4 shall be filed once a completed, and the operator has	
Attach the Bond under which the following completion of the involtesting has been completed. Final determined that the site is ready for the site is intended to revise the afollowing: Cement with 88 sxs Type II excess, bring cement to su compressive strength at 60 ventionally set holes before 600 psi for 30 minutes.	poperation (clearly state all pertine onally or recomplete horizontally work will be performed or provided operations. If the operation of Abandonment Notices shall be for final inspection.) Approved surface cement in approved surface cement in approved. Wait on cement approved by the pressure testing or drilling approved testing or drilling approved to the pressure testing or drilling approved to the pressure testing or drilling approved by the pressure testing or drilling approved to the pressure testing the pr	give subsurface locations and meae the Bond No. on file with BLM/E subsurface locations and meae the Bond No. on file with BLM/E ited only after all requirements, incoming the subject well according to the subject well according to loflake, 3% calcium chloride propriate time until cement accup of BOPE. Wait on cement out from under surface. Test was a common to the subject with	asured and true vertical depths BIA. Required subsequent rep ecompletion in a new interval luding reclamation, have been to the (113 cu. ft., 200% chieves 250 psi it for 8 hrs for st casing to	s of all pertinent markers and zones. sorts shall be filed within 30 days , a Form 3160-4 shall be filed once a completed, and the operator has	
If the proposal is to deepen direct Attach the Bond under which the following completion of the invol testing has been completed. Final determined that the site is ready for the involvent of th	poperation (clearly state all pertine onally or recomplete horizontally work will be performed or provided operations. If the operation represents the performed or provided operations. If the operation represents the performed operation represents the performed operation of the performance of the	give subsurface locations and meae the Bond No. on file with BLM/E subsurface locations and meae the Bond No. on file with BLM/E ided only after all requirements, incoming the subject well according to the subject well according to loflake, 3% calcium chloride propriate time until cement accup of BOPE. Wait on cement out from under surface. Test was also be supported by the BLM Wesources of the BLM Wesour	asured and true vertical depths BIA. Required subsequent repecompletion in a new interval luding reclamation, have been to the (113 cu. ft., 200% chieves 250 psi t for 8 hrs for st casing to /ell Information System at to the Farmington of 01/22/2004 (04\$XM0124)	s of all pertinent markers and zones. sorts shall be filed within 30 days , a Form 3160-4 shall be filed once a completed, and the operator has	
If the proposal is to deepen direct Attach the Bond under which the following completion of the involtesting has been completed. Final determined that the site is ready for the involtesting has been completed. Final determined that the site is ready for the involtesting has been completed. Final determined that the site is ready for the involved in the involved for the involved	Operation (clearly state all pertine onally or recomplete horizontally work will be performed or provided operations. If the operation in Abandonment Notices shall be for final inspection.) Approved surface cement in the provided operation in the provided surface cement in the provided surface cement approved. Wait on cement approved operation in the pressure testing or drilling or drilling or drilling operation. Submission for BURLINGTON in the provided surface of the provided su	give subsurface locations and meae the Bond No. on file with BLM/E subsurface locations and meae the Bond No. on file with BLM/E subject well according to the subject well according to t	asured and true vertical depths BIA. Required subsequent rep ecompletion in a new interval luding reclamation, have been to the (113 cu. ft., 200% chieves 250 psi tt for 8 hrs for st casing to /ell Information System to the Farmington to 1/22/2004 (04SXM0124) ULATORY SPECIALIST	s of all pertinent markers and zones. sorts shall be filed within 30 days , a Form 3160-4 shall be filed once a completed, and the operator has	
If the proposal is to deepen direct Attach the Bond under which the following completion of the invol testing has been completed. Final determined that the site is ready for the involvent of th	Operation (clearly state all pertine onally or recomplete horizontally work will be performed or provided operations. If the operation in Abandonment Notices shall be for final inspection.) Approved surface cement in the provided operation in the provided surface cement in the provided surface cement approved. Wait on cement approved operation in the pressure testing or drilling or drilling or drilling operation. Submission for BURLINGTON in the provided surface of the provided su	give subsurface locations and meae the Bond No. on file with BLM/E subsurface locations and meae the Bond No. on file with BLM/E ided only after all requirements, incoming the subject well according to the subject well according to loflake, 3% calcium chloride propriate time until cement accup of BOPE. Wait on cement out from under surface. Test was also be supported by the BLM Wesources of the BLM Wesour	asured and true vertical depths BIA. Required subsequent rep ecompletion in a new interval luding reclamation, have been to the (113 cu. ft., 200% chieves 250 psi tt for 8 hrs for st casing to /ell Information System to the Farmington to 1/22/2004 (04SXM0124) ULATORY SPECIALIST	s of all pertinent markers and zones. sorts shall be filed within 30 days , a Form 3160-4 shall be filed once a completed, and the operator has	
If the proposal is to deepen direct Attach the Bond under which the following completion of the invol testing has been completed. Final determined that the site is ready for the following: Cement with 88 sxs Type II excess, bring cement to su compressive strength at 60 ventionally set holes before 600 psi for 30 minutes. 14. Thereby certify that the foregoin Name (Printed/Typed) TAMMY	Operation (clearly state all pertine onally or recomplete horizontally work will be performed or provided operations. If the operation is Abandonment Notices shall be for final inspection.) Approved surface cement in approved surface cement in the cement with 0.25 pps Celeface). Wait on cement approved degrees F. prior to nipple appressure testing or drilling is pressure testing or drilling for BURLINGTON is Committed to AFMSS for provided Submission. THIS SPACE F	give subsurface locations and meae the Bond No. on file with BLM/E subsurface locations and meae the Bond No. on file with BLM/E subsurface and properties of the subject well according to the subject well according to the subject well according to loflake, 3% calcium chloride propriate time until cement accup of BOPE. Wait on cement out from under surface. Test with the subject well according to the subject well according to the subject well according to the subject with the subject well according to the subjec	asured and true vertical depths BIA. Required subsequent rep ecompletion in a new interval luding reclamation, have been to the (113 cu. ft., 200% chieves 250 psi tt for 8 hrs for st casing to /ell Information System to the Farmington to 1/22/2004 (04SXM0124) ULATORY SPECIALIST	s of all pertinent markers and zones. sorts shall be filed within 30 days , a Form 3160-4 shall be filed once a completed, and the operator has	