This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## **Oil Conservation Division**

## Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

DIST. 3

Operator COP						e Name SAN	Well No. 95			
ocation of We	ell: Unit L	etter _	M	Sec _	04	Twp027N	Rge _	007W API	# 30-039-07159	
	Name of Reservoir or Pool			Pool		Type of Prod	-	Method of Prod	Prod Medium	
Upper Completion	PC				Gas	,	Flow		Tubing	
Lower Completion	MV				Gas					
				Pi	re-Flow S	Shut-In Pressu	ıre Data			
Upper Completion	Hour, Date, Shut-In 4/6/2010				Length of Time Shut-In 225 hours			ess. PSIG 89	Stabilized?(Yes or No) Yes	
Lower Completion	Hour, Date, Shut-In 4/6/2010				Length of Time Shut-In			ess. PSIG	Stabilized?(Yes or No)	
					155 hours			369	Yes	
Commenced	at: /12/2							er or Lower): LC	)WER	
Time (date/time)		Lapsed Time Since*		, , , , , , , , , , , , , , , , , , , ,	PRESSURE		Prod Zone	I .	Domorko	
				Up	per zone	Lower zone	Temperature	8	Remarks	
4/13/2010 9:24:48 AM 22			89 369			Both zones shut in				
4/14/2010 10:45:00 AM			47		89 369			Both zones shut	in.	
4/15/2010 9:42:54 AM 70			89 48			Vent well to get 20% and complete test Turned on PC				
oduction rate	e during te	est								
oil: BPOD Based on:				Bł	ols. In	Hrs.		Grav.	GOR	
as		MCF	PD; Te	st thru (O	rifice or N	Meter)				
				N/	lid-Taet (	Shut-In Pressı	ıre Data			
Upper Completion	Hour, Date, Shut-In			141		of Time Shut-In		ess. PSIG	Stabilized?(Yes or No)	
Lower Completion	Hour, Date, Shut-In				Length of Time Shut-In			SI Press. PSIG Stabilized?(Yes or OIL CONS. DIV.		

A.

(Continue on reverse side)

## Flow Test No. 2

Commenced at: Zone Producing (Upper or Lower)											
Time		Lapsed Time	PRES	SURE	Prod Zone Temperature		Remarks				
(date/tim	ne)	Since*	Upper zone	Lower zone		[ 					
,											
					***************************************		***************************************				
	į										
				J	<del></del>						
Production rat	te during tes	st				Α					
Oil:	BPOD B	ased on:	Bbls. In	Hrs.		Grav.	GOR				
GasMCFPD; Test thru (Orifice or Meter)											
Remarks:											
Vent test wittnessed by Derrick Vigil with NMOCD. The MV is temporarily abandoned.											
I hereby certify that the information herein contained is true and complete to the best of my knowledge.											
Approved:	ALIG	1 3 2010	20	Operat	tor: COP						
		ervation Division		By:	Danny Robe	rts					
علىقىك . By:	7 6. 1			Title:	Multi-Skilled	Operator					
Title:		Oil & Gas Ins		Date:	Date: Thursday, April 29, 2010						

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion Such tests shall also be commenced on all multiple completions within seven days following creompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2 At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5 Following completion of Flow Test No 1, the well shall again be shut-in, in accordance with Paragraph 3 above

- 6 Flow Test No 2 shall be conducted even though no leak was indicated during Flow Test No 1 Procedure for Flow Test No 2 is to be the same as for Flow Test No 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7 Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aziec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)