This form is not to be "used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator BR				Lease Name SAN JUAN 29-7 UNIT					Well No93A	
Location of Well: Unit Letter C Se		Sec	02 Twp 029N		Rge	Rge 007W API		30-039-25478		
	Name of Reservoir or Pool		Pool	Type of Prod			Method of Prod			Prod Medium
Upper Completion	MV			Gas			Artific	Artificial Lift		Fubing
Lower Completion	PC			Gas			Artific	Artificial Lift		Tubing
			Pre	-Flow S	Shut-In P	ressu	re Data			
Upper Completion	Hour, Date, Shut-In 7/21/2010			Length of Time Shut-In 120 hours				SI Press. PSIG		Stabilized?(Yes or No) Yes
Lower Completion	Hour, Date, Shut-In 7/21/2010			Length of Time Shut-In 179 hours			SI Pres	SI Press. PSIG		Stabilized?(Yes or No) Yes
				Flo	ow Test N	lo. 1	•			
Commenced	at:	7/26/201	0		Zoi	ne Pro	ducing (Upper	or Lower):	UPP	ER
Time (date/time)		Lapsed Time Since* Upp		PRESSURE Jpper zone Lowe		zone	Prod Zone Temperature	Remarks		Remarks
7/26/2010 1:36:07 PM		13	1	157	122)	102	start test		
7/27/2010 1:48:24 PM		37	1	111		3	107	7		
7/28/2010 11:35:37 AM 59			76		3	100	crossover met, lower zone stable		er zone stable	
Production rate	e during te	est								
Oil:BPOD Based on:B			Bbis	Bbls. In Hrs.			(Grav		GOR
Gas		MCFPD; Tes	st thru (Orifi	ice or M	/leter)					
			Min	LTact S	Shut-In D	race	ro Data			
Upper Completion	Hour, Date, Shut-In		IVISU	id-Test Shut-In Pressure E Length of Time Shut-In				SI Press. PSIG		Stabilized?(Yes or No)
Lower Completion				Length of Time Shut-In			SI Press. PSIG		8	Stabilized?(Yes or No)

(Continue on reverse side)





Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

		FIC	W Test No. Z						
Commenced at:			Zone Pro	oducing (Uppe	er or Lower)				
Time	Lapsed Time		SURE	Prod Zone		_			
(date/time)	Since*	Upper zone	Lower zone	Temperature	9	Remarks			
						Paller III			
ı									
Production rate d	uring test								
Oil:E	BPOD Based on:	Bbls. In	Hrs.		Grav.	GOR			
Gas	MCFPD; Test t	hru (Orifice or M	leter)						
Dana mulca.									
Remarks:									
1 horoby cortify th	at the information herein	contained is true	and complete	to the best of	f my knowloda				
Thereby certify th			and complete	to the best o	i iliy kilowledg	JC.			
Approved:	AUG 1 3 2010	20	Opera	tor: BR					
New Mexico	Dil Conservation Division		Ву:	Darrell Ellio	tt				
By: New Mexico Oil Conservation Division Delta G. To O. C. By:			Title:	Title: Multi-Skilled Operator					
Do. 2	outy Oil & Gas Inspe	ctor.							
Title: Dep	District #3		Date:	Date: Friday, July 30, 2010					

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days
- 4 For Flow Test No 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-m Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note, if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours
- 5 Following completion of Flow Test No 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6 Flow Test No 2 shall be conducted even though no leak was indicated during Flow Test No, 1. Procedure for Flow Test No 2 is to be the same as for Flow Test No 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- 7 Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows. 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone

8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)