In Lieu of
Form 3160
(June 1990)

UNITED STATES DEPARTMENT OF INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires. March 31, 1993

SUNDRY NOTICE AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir Use "APPLICATION TO DRILL" for permit for such proposals

Lease Designation and Serial No. NMSF-078772

RECEIVED

If Indian, Allottee or Tribe Name

on Well Completion or Recompletion Report

and Log form.)

	SUBMIT IN TRIPLICATE	AUG 26 2010	7.	If Unit or CA, Agreement Designation Rosa Unit
1.	Type of Well Oil Well Gas Well X Other	Farmington Field Office Bureau of Land Manage	8 ite.	Well Name and No. Rosa Unit 129D COM
2.	Name of Operator WILLIAMS PRODUCTION COMPANY	,	9.	API Well No. 30-039-30775
3.	Address and Telephone No. PO Box 640 Aztec, NM 87410-0640 634-4208		10	Field and Pool, or Exploratory Area BLANCO MV/BASIN DK/BASIN MC
4.	Location of Well (Footage; Sec., T, R., M., or Survey Description) SURF: 1670 FSL & 2000' FWL BHL: 925' FSL & 2451' FWL SEC 34 32N 6W		11.	County or Parish, State Rio Arriba, New Mexico

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction X Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Altering Casing Conversion to Injection X Other Reallocation Dispose Water (Note: Report results of multiple completion

N

Williams E&P has run Protechnic's Completion profiler tool for allocation purposes on the Rosa Unit #129D. Based on the results obtained, Williams proposes the following allocation:

Mesaverde	57%	404	Mcf/d	RCVD AUG 30'10 OIL CONS. DIV.
Mancos	19%	134	Mcf/d	DIST. 3
Dakota	24%	170	Mcf/d	viji. j
Total	100%	708	Mcf/d	
	D	H 6 3 756	Ma	

(This space for Federal or State office use)


Approved by Joe Henrit Title 6e0 Date 4-27-10

Conditions of approval, if any

Title 18 U S C Section 1001, makes it a crime for any person knowingly and walfully be wake to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

Williams Production Company Rosa Unit #129D



MEASUREDSOLUTIONS





Williams Production Company

Well Name Rosa Unit #129D

Field Blanco Mesaverde/Basin Dakota

Location | Rio Arriba County, New Mexico

Customer Name | Justin Stolworthy

Date of Survey | August 17, 2010

Date of Analysis | August 24, 2010

Logging Engineer | Loren Healy

Analyst | Derrick George

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful misconduct on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.





Table of Contents

Survey Objectives	4
Logging Procedures	4
Well Information	5
Tool String	6
Results	7
Analysis Summary	12
Brief Description of Process	13
Model Results With Recorded Data	14
Production Rates At Surface Conditions	15
Flow Model at Downhole Conditions With Comparison of Theoretical Response to Recorded Data	25
Overlay of all Log Data	26
Apparent Fluid Velocity Derived from Spinner	27
Spinner Calibration Plots Relationship between R.P.S. and Fluid Velocity (fpm)	28
Well Information	29
Parameters used for Analysis	29





Survey Objectives

- Identify the source of water production.
- Identify gas producing intervals.
- Quantitative production profile.

Logging Procedures

Date	Time	Comment
08/17	07:00	Arrive on location
08/17	06:00	Gauge Run Start
08/17	07:00	Gauge Run Stop
08/17	08:09	Program Completion Profile String
08/17	08:24	Start GIH pass
08/17	08:44	Stop GIH pass
08/17	09:12	Start logging passes
08/17	13:33	Stop logging passes
08/17	13:39	Start out of well pass
08/17	13:59	Stop out of well pass
08/17	14:08	Start download
08/17	14:33	Stop download
08/17	15:00	Rig Down

Interval Logged: [From 5,179 to 8,075 ft.]

60 ft/min 90 ft/min 120 ft/min





Well Information

Casing: 5.50" 17.0 lb/ft surface to 8,091 ft PBTD: 8,083 ft

Tubing: 2.38" 4.7 lb/ft surface to 5,074 ft

Perforations: 5,480; 5,482; 5,484; 5,486; 5,488; 5,490; 5,520; 5,522; 5,524; 5,526;

5,528; 5,530; 5,532; 5,534; 5,536; 5,564; 5,566; 5,568; 5,570; 5,572; 5,574; 5,576; 5,578; 5,580; 5,582; 5,584; 5,586; 5,588; 5,590; 5,592; 5,594; 5,596; 5,598; 5,600; 5,602; 5,604; 5,608; 5,612; 5,616; 5,620; 5,623; 5,626; 5,628; 5,630; 5,632; 5,634; 5,636; 5,638; 5,640; 5,642 ft

(Stage 5 - Cliffhouse/Menefee)

5,773; 5,775; 5,777; 5,779; 5,781; 5,783; 5,785; 5,787; 5,789; 5,791; 5,793; 5,795; 5,799; 5,801; 5,803; 5,805; 5,807; 5,809; 5,822;

5,824; 5,826; 5,828; 5,830; 5,835; 5,839; 5,842; 5,844; 5,846; 5,850;

5,852; 5,854; 5,856; 5,867; 5,869; 5,872; 5,875; 5,877; 5,879; 5,881; 5,883; 5,894; 5,896; 5,990; 5,992; 5,994; 6,002; 6,004; 6,029; 6,031;

6,033; 6,046; 6,048; 6,050; 6,052; 6,078; 6,080 ft

(Stage 4 - Point Lookout)

6,978; 6,988; 6,998; 7,008; 7,018; 7,028; 7,038; 7,045; 7,056; 7,068;

7,078; 7,088; 7,101; 7,108; 7,114; 7,121; 7,128; 7,138; 7,148; 7,158;

7,168; 7,181; 7,192 ft (Stage 3 - Upper Mancos)

7,261; 7,264; 7,269; 7,276; 7,284; 7,290; 7,295; 7,298; 7,302; 7,307;

7,314; 7,320; 7,332; 7,336; 7,341; 7,346; 7,352; 7,357; 7,366; 7,372 ft

(Stage 2 - Lower Mancos)

8,010; 8,013; 8,016; 8,022; 8,026; 8,032; 8,042; 8,048; 8,052; 8,056;

8,060; 8,064; 8,068; 8,072; 8,076; 8,080; 8,084; 8,088 ft

(Stage 1 - Dakota)

Flowing tubing pressure at the time of logging: 420 psi

Daily average surface production reported at the time of logging:

gas: 700 Mscf/d water: 5 bpd





Tool String

The 1 11/16" Completion Profiler string comprised the following sensors:

Battery housing; RS-232/CCL; Memory/CPU; Pressure/Temperature Combo; Gamma Ray; Centralizer; Induction Collar Locator; Fluid Density; Centralizer; Spinner Flowmeter.





Results

The following table summarizes the production from each frac interval.

	1 mm				R PRODUCTION	in a contract the way and the safety		
40.0			The second secon		Rates Reported at			
Zone	Inte	rvals	als Q-Water Qp-Water		Percent of	Q-Gas	Qp-Gas	Percent of
	feet		BFPD	BFPD	Total	MCFD	MCFD	Total
Surface	to to	5480	5 bpd		100 %	707 Mcf/d		100 %
		Stag	e 5 - Cliffhouse/f	/lenefee	13 %			15 %
5480	to	5642	5 bpd	1 bpd		707 Mcf/d	104 Mcf/d	
- 1, 7 - 1 2 2	50.	ં ેૣૺ૾ૺૢ S f	 tägę³4,∹Point`Loc	okout 🔧	16 %	4 (18)	* #4 x 3 w 4 x	¥2 %
5773	to	6080	4 bpd	1 bpd		603 Mcf/d	300 Mcf/d	
(5.1	*,	, ÇŞt	age 3 - Upper Ma	nços	40%	7 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	1 × 500,	13 %
6978	to	7192	3 bpd	2 bpd		304 Mcf/d	90 Mcf/d	
Stage 2 - Lower Mancos			6 %	,	,	6 %		
7261	to	7372	2 bpd	0 bpd		213 Mcf/d	44 Mcf/d	
Stage 1 - Dakota			25 %	,		17 %		
8010	to	8072	1 bpd	1 bpd		170 Mcf/d	120 Mcf/d	
Flow	Contr	ibution f	<u> </u>	epth	0 %	<i>y.</i> ,	,	7 %
8075	to	Below	0 bpd	·	0 %	50 Mcf/d		7 %