

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

RECEIVED

Sundry Notices and Reports on Wells

JUL 29 2010

1. Type of Well
GAS

Farmington Field Office
Bureau of Land Management

5. Lease Number
SF-078997
6. If Indian, All. or
Tribe Name

2. Name of Operator

ConocoPhillips

7. Unit Agreement Name
San Juan 30-5 Unit

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. Well Name & Number
San Juan 30-5 Unit 49P

9. API Well No.

30-039-30900

4. Location of Well, Footage, Sec., T, R, M

Surface: Unit D (NWNW), 745' FNL & 695' FWL, Section 9, T30N, R5W, NMPM
Bottomhole: Unit E (SWNW), 1800' FNL & 1020' FWL, Section 9, T30N, R5W, NMPM

10. Field and Pool
Blanco MV / Basin DK

11. County and State
Rio Arriba, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - ☐ Casing Report☒ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection

**RCVD AUG 9 '10
OIL CONS. DIV.
DIST. 3**

13. Describe Proposed or Completed Operations

07/20/2010 MIRU HP 282. NU BOPE. PT csg to 600#/30min @ 16:30hrs on 7/21/10. Test - OK.

07/21/2010 RIH w/ 8 3/4" big. Tag & DO cmt. Drilled ahead to 3328' Inter TD reached 7/23/10. Circ. hole & RIH w/ 89jts, 7", 23#, J-55 LT&C set @ 3847' w/ ST@2948'. 7/24/10 RU to cmt. 1st Stage - Pre-flush w/ 10bbbs GW, 2bbbs FW. Pumped scavenger 19sx (57cf-10bbbs) Premium lite cmt w/ 3% CACL, .25pps celloflake, 5pps LCM-1, .4% FL-52, 8% bentonite, .4% SMS. Lead w/ 73sx (156cf-28bbbs) Premium lite cmt w/ 8% bentonite, 3% CACL, .25pps celloflake, .4% FL-52, 5pps LCM-1, .4% SMS. Tail w/ 40sx (55cf-10bbbs) Type III cmt w/ 1% CACL, .25pps celloflake, .2% FL-52. Drop plug & displaced w/ 40bbbs FW & 110bbbs MW. Bump plug. Plug down @ 04:15hrs on 7/25/10. Open ST & Circ. 12bbbs cmt to surface. WOC. 2nd Stage - Pre-flush w/ 10bbbs FW, 10bbbs GW, 10bbbs FW. Pumped scavenger 19sx (57cf-10bbbs) Premium lite cmt w/ 3% CACL, .25pps celloflake, 5pps LCM-1, .4% FL-52, 8% bentonite, .4% SMS. Lead w/ 376sx (801cf-142bbbs) Premium lite cmt w/ 8% bentonite, 3% CACL, .25pps celloflake, .4% FL-52, 5pps LCM-1, .4% SMS. Drop plug & displaced w/ 116bbbs FW. Bump plug & close ST. Circ. 46bbbs cmt to surface. Plug down @ 09:58hrs on 7/25/10. RD cmt. WOC.

07/25/2010 RIH w/ 6 1/4" bit. Drill out ST@2948'. PT 7" csg to 1500#/30min @ 20:00hrs on 7/25/10. Test - OK. Drilled ahead w/ 6 1/4" bit to 8105' (TD) TD reached 7/27/10. Circ. hole & RIH w/ 198jts, 4 1/2", 11.6#, L-80 LT&C set @ 8103'. 7/27/10 RU to cmt. Pre-flush w/ 10bbbs GW, 2bbbs FW. Pumped scavenger 9sx (27cf-5bbbs) Premium lite cmt w/ .25pps celloflake, .3% CD-32, 6.25pps LCM-1, 1% FL-52. Tail w/ 305sx (604cf-107bbbs) Premium lite cmt w/ .25pps celloflake, .3% CD-32, 6.25pps LCM-1, 1% FL-52. Flushed lines w/ 15bbbs FW. Drop plug & displaced w/ 126bbbs FW. Bump plug. Plug down @ 07:39hrs on 7/28/10. RD cmt. WOC. ND BOPE. NU WH. RD RR @ 14:00hrs on 7/28/10.

PT will be conducted by Completion Rig. Results & TOC will appear on next report.

14. I hereby certify that the foregoing is true and correct.

Signed Crystal Tafoya Crystal Tafoya

Title Staff Regulatory Technician

Date 7/29/10

ACCEPTED FOR RECORD

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any statement or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within the jurisdiction

Date
AUG 05 2010

**FARMINGTON FIELD OFFICE
BY scv**