RECEIVED

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

AUG 16 2010

		Farmington Field Office	
*********	Sundry Notices and Reports on Wells	reau c	of Land Management
1.	Type of Well	5. 6.	Lease Number SF-078994 If Indian, All. or
	GAS		Tribe Name
2.	Name of Operator	7.	Unit Agreement Name San Juan 30-5 Unit
	ConocoPhillips		
3.	Address & Phone No. of Operator	8.	Well Name & Number San Juan 30-5 Unit 38P
_	PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
4.	Location of Well, Footage, Sec., T, R, M	10	30-039-30892
	Surface: Unit O (SWSE), 975' FSL & 1695' FEL, Section 18, T30N, R5W, NMPM Bottomhole: Unit J (NWSE), 1525' FSL & 2580' FEL, Section 18, T30N, R5W, NMPM	10.	Field and Pool Blanco MV / Basin DK
		11.	County and State Rio Arriba, NM
12.	CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OT	HER	DATA
	Type of Submission Type of Action Notice of Intent Abandonment Change of Plans	_ <u>X</u>	Other - Casing Report
	X Subsequent Report Recompletion New Construction Recompletion New Construction Plugging Non-Routine Fracturing		RCVD SEP 8'10
P	Casing Repair Water Shut off		OIL CONS. DIV.
_	Final Abandonment Altering Casing Conversion to Injection		DIST. 3
08/4 08/4 Inte 10b ben SM Bur 10b SM plu; 08/ 818 Pur Pre FW	Describe Proposed or Completed Operations 07/2010 MIRU HP 282. NU BOPE. PT csg to 600#/30min @ 16:00hrs on 8/8/10. Test - OK. 08/2010 RIH w/ 8 3/4" bit. Tag cmt @ 67' & DO cmt to 197'. PT csg to 600#/30min @ 19:30hrs on 8/8/10. Test TD reached 8/11/10. Circ. hole & RIH w/ 89jts, 7", 23#, J-55 ST&C set @ 3848' w/ ST@2935'. 8/12/2005 SW, 2bbls FW. Pumped scavenger 19sx (57cf-10bbls) Premium lite cmt w/ 3% CACL, .25pps cellorationite, .4% SMS. Lead w/ 78sx (166cf-30bbls) Premium lite cmt w/ 8% bentonite, 3% CACL, .25pps cellorationite, .4% SMS. Lead w/ 78sx (166cf-30bbls) Premium lite cmt w/ 8% bentonite, .2% FL-52. Drop plug & drop plug. Plug down @ 19:46hrs on 8/12/10. Open ST & Circ. 15bbls cmt to surface. WOC. 2nd Stage - Fubls FW. Pumped scavenger 19sx (57cf-10bbls) Premium lite cmt w/ 3% CACL, .25pps celloflake, 5pps 18. Lead w/ 336sx (716cf-127bbls) Premium lite cmt w/ 8% bentonite, 3% CACL, .25pps celloflake, 5ps 18. Lead w/ 336sx (716cf-127bbls) Premium lite cmt w/ 8% bentonite, 3% CACL, .25pps celloflake, .4% g. & displaced w/ 115bbls FW. Bump plug & close ST. Circ. 35bbls cmt to surface. Plug down @ 12:57 13/2010 RIH w/ 6 1/4" bit. Drill out ST@2935'. PT 7" csg to 1500#/30min @ 11:30hrs on 8/13/10. Test 100' (TD) TD reached 8/14/10. RIH w/ 198jts, 4 1/2", 11.6#, L-80 LT&C set @ 8179', 08/15/10 RU to cm 100 plug. Plug down @ 23:45hrs on 8/15/10. RD cmt. WOC. ND BOPE. NU WH. RD RR @ 06:00 will be conducted by Completion Rig. Results & TOC will appear on next report.	10 RU offlake, filloflak isplace Pre-flus LCM-1 6 FL-52 hrs on - OK. offlak offlak	to cmt. 1st Stage - Pre-flush w/5pps LCM-1, .4% FL-52, 8% e., .4% FL-52, 5pps LCM-1, .4% d w/ 40bbls FW & 110bbls MW h w/10bbls FW, 10bbls GW, ., .4% FL-52, 8% bentonite, .4% 2, 5pps LCM-1, .4% SMS. Drop 8/13/10. RD cmt. WOC. Drilled ahead w/ 6 1/4" bit to flush w/ 10bbls GW, 2bbls FW. 2. Tail w/ 307sx (608cf-108bbls pp plug & displaced w/ 124bbls
	I hereby certify that the foregoing is true and correct.		
	ened Cinatul Tafaya Crystal Tafoya Title Staff Regulator	ory Te	chnician Date 8 116 201
AP	nis space for Federal or State Office use) PROVED BY Title	A	CREPTED FOR RECORD
Title	NDITION OF APPROVAL, if any: 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of Inited States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.		AUG 3 0 2010