

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103

June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-039-05523
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: Lindrith Unit
8. Well Number # 23
9. OGRID Number 162928
10. Pool name or Wildcat S. Blanco Pictured Cliffs

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR: USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other
2. Name of Operator Energen Resources Corporation
3. Address of Operator 2010 Afton Place, Farmington, NM 87401
4. Well Location Unit Letter O : 1150 feet from the South line and 1800 feet from the East line Section 09 Township 24N Range 03W NMPM County Rio Arriba
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6892' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐ RCVD SEP 17 '10
OIL CONS. DIV.
DIST. 3

OTHER: refrac ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Energen Resources refraced the Lindrith #23 PC as follows:

08/14/10 MIRU. NU BOP. TOH with 2.375" tubing.

08/17/10 Run CBL, TOC @ 2200'. Re-perforate existing PC from 3074' - 3150' - 4 spf - 160 holes.

08/18/10 Acidize PC with 500 gals 15% HCL.

08/21/10 Frac PC with 79,613 gals Delta 140 and 80,300#20/40 sand.

08/22-09/01/10 Flow back and clean out with air and foam.

09/02/10 TIH with 1.50" 2.4# J-55 tubing, set @ 3121'. ND BOP. NUWH. Return well to production.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Vicki Donaghey TITLE Regulatory Analyst DATE 09/14/10
Type or print name Vicki Donaghey E-mail address: vdonaghe@energen.com PHONE 505.325.6800

For State Use Only

APPROVED BY Kelly G. Pals TITLE Deputy Oil & Gas Inspector DATE SEP 28 2010
Conditions of Approval (if any):