.Form 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIQ

BUREAU OF LAND MANAGEMENT

Expires July 31, 1996 5. Lease Serial No

6. If Indian, Allottee or Tribe Name

SF 079003

FORM APPROVED

OMB No. 1004-0135

| Do not use this form for proposals to drill or reinter and | | | | | | | | | | |
|--|-----|-------|-------|-------|------|---------|--------|-------|------------------|--|
| Do n | ot | use | this | form | for | proposa | ils to | drill | or Seenter and W | |
| aban | dor | ned v | vell. | Use F | -orm | 3160-3 | (APD) | for s | uch proposals. | |

7. If Unit or CA/Agreement, Name and/or No. Bureau of Land Managemen SUBMIT IN TRIPLICATE - Other instructions on reverse side Type of Well Northeast Blanco Unit 8. Well Name and No. X Gas Well Oil Well Other Name of Operator Northeast Blanco Unit #68M 9. API Well No. Devon Energy Production Company, L.P. Phone No. (include area code) 30-045-33474 10. Field and Pool, or Exploratory Area 505-327-4573 PO Box 6459, Navajo Dam, NM 87419 Location of Well (Footage, Sec., T., R., M., or Survey Description) So. Los Pinos Frt/Sd PC & Basin DK 500' FNL & 1205' FEL Unit A Sec. 35, T31N, R07W San Juan County, New Mexico 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Production (Start/Resume) Water Shut-Off | Notice of Intent Acidize Deepen Reclamation Well Integrity Alter Casing Fracture Treat Recomplete X Other Surface Commingle Subsequent Report Casing Repair New Construction Temporarily Abandon Change Plans Plug and Abandon Water Disposal Final Abandonment Notice Convert to Injection Plug Back 13. Describe Proposed or Completed Operations (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to despen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones.

Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA. Required subsequent reports shall be filed within 30 days Following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once Testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) Devon requests administrative approval to surface commingle the South Los Pinos Fruitland Sand Pictured Cliffs (80690) & Basin

Dakota (71599) in this dually completed gas well. Surface commingling will eliminate redundant surface equipment & maximize productivity while not hindering the recovery of liquids & gas. Notice has been filed concurrently on form C-103 with the State. Since the two intervals do not have common ownership, Devon will utilize the test period described in the attached method of RCVD GCT 13'10 allocation. All of the interest owners of both intervals have been notified.

OIL CONS. DIV.

| | orde | v in process | 75. 3 | | | | |
|---------------------------|---|---|---|--|--|--|--|
| 14. I hereby certify | that the foregoing is true and correct | | | | | | |
| Name (Printed/) | Typed) | Title | | | | | |
| | Miķe Pjppin | Petroleum Engineer (Agent) | | | | | |
| Signature | Miko Vignin | Date September 16, 2010 | | | | | |
| | THIS | SPACE FOR FEDERAL OR STATE USE | | | | | |
| Approved by | model | Tito tet. Sno | Date 10/7/10 | | | | |
| certify that the applicar | Yany, are attached. Approval of this notice does not halds legal or equitable title to those rights in the applicant to conduct operations thereon. | | | | | | |
| Title 18 IISC Section | on 1001 makes it a crime for any nerson kno | wingly and willfully to make to any department or a | gency of the United States any false, fictitious or | | | | |

fraudulent statements or representations as to any matter within its jurisdiction.

Method of Allocation

Devon Energy recommends the following procedure to allocate surface commingled production between the Basin-Dakota and the Fruitland Pictured Cliffs pools within the Northeast Blanco Unit:

- The Basin-Dakota and Fruitland Pictured Cliffs formations will be completed simultaneously.
- A single 2-3/8" tubing string will be run in the well, with a packer isolating the two horizons.
- The Dakota completion will be produced up the tubing string.
- The Fruitland Pictured Cliffs completion will be produced up the 2-3/8" x 4-1/2" annulus.
- Production from each zone will be measured separately using a 3 phase metering device prior to flowing through a mutual production separator. Total well stream gas will be measured using a conventional orifice plate meter tube located downstream of the production separator.
- The completions will be flow tested separately for approximately 90 days to establish a stabilized rate and trend.
- Following the testing period the two pools will be surface commingled. Total well production
 will flow through common surface facilities and total produced gas will be measured.
- Production will be allocated between the Dakota and Fruitland Pictured Cliffs intervals by applying the variable percentage schedule to the daily total well production.

The Variable Percentage Schedule was derived using Basin-Dakota and Pictured Cliffs production type curves. These type curves were generated by normalizing production data from surrounding wells. The variable percentage schedule is required due to the dissimilar decline trends exhibited by the Pictured Cliffs and Dakota. Figure 1 depicts a typical Pictured Cliffs – Dakota production allocation. The actual percentages will vary from well to well, depending on well productivity.

gurface




Figure 1

The Basin-Dakota type curve was generated from normalized production of 40 offsetting Basin-Dakota producers. The Basin-Dakota type curve clearly defines the decline rate for the life of a well. Comparison of this type curve with the production schedule obtained by using flow test data demonstrates the reliability of this method for projecting production. (See Figure 2) The curve covers a thirty two month period with a variance in cumulative normalized production of less than 0.1%.

NEBU AREA DAKOTA TYPE CURVE




Figure 2

The Fruitland Pictured Cliffs type curve was generated from normalized production of 15 offsetting Fruitland Pictured Cliffs producers. The Fruitland Pictured Cliffs type curve clearly defines the decline rate for the life of a well. Comparison of this type curve with the production schedule obtained by using flow test data demonstrates the reliability of this method for projecting production. (See Figure 2) The curve covers a five year period with a variance in cumulative normalized production of only 0.8%.




Figure 3