

submitted in lieu of Form 3160-5
**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

RECEIVED

NOV 19 2010

Sundry Notices and Reports on Wells

Farmington Field Office
Bureau of Land Management

1. Type of Well
GAS

5. Lease Number
SF-079491

6. If Indian, All. or
Tribe Name

2. Name of Operator

BURLINGTON

RESOURCES OIL & GAS COMPANY LP

7. Unit Agreement Name
San Juan 27-5 Unit

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. Well Name & Number
100N

9. API Well No.

30-039-30798

4. Location of Well, Footage, Sec., T, R, M

Surface: Unit G (SWNE), 1705' FNL & 1585' FEL, Section 1, T27N, R5W, NMPM

BHL: Unit J (NWSE), 2087' FSL & 2201' FEL, Section 1, T27N, R5W, NMPM

10. Field and Pool

Blanco MV / Basin DK

11. County and State
Rio Arriba, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Other — ☐ Completion Report

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Plugging

☐ Non-Routine Fracturing

☐ Final Abandonment

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

PLEASE SEE ATTACHED

RCVD DEC 1 '10

OIL CONS. DIV.

DIST. 3

14. I hereby certify that the foregoing is true and correct.

Signed

Dollie L. Busse

Dollie L. Busse

Title Staff Regulatory Technician

Date

11/19/10

(This space for Federal or State Office use)

APPROVED BY


Title

Date

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD



San Juan 27-5 Unit 100N

API #30-039-30798

Blanco MV / Basin DK

- ✓
- 10/05/2010** RU Basin W/L. RIH w/ 3 3/4" gauge ring. Run GR/CCL/CBL Logs. TOC @ 4128'. RD W/L.
- 10/20/2010** Install Frac valve. PT csg to 4500#/30min. @ 10:45hrs on 10/20/10. Test – OK.
- 10/20/2010** RU Basin W/L to Perf **Dakota** w/ .34" diam. – 2 SPF @ 8916', 8914', 8912', 8910', 8908', 8906', 8904', 8902', 8900', 8898', 8896', 8865', 8863', 8861', 8859', 8857', 8855', 8853', 8851', 8849', 8847', 8845', 8843' = 46 Holes. 1SPF @ 8760', 8756', 8752', 8748', 8742', 8738', 8734' = 7 Holes. Acidize w/ 10bbls 15% HCL. Frac w/ 108,150gals Slickwater pad, 40,235# 20/40 Arizona Sand. Set CBP @ 6932'.
- Perf **Point Lookout** w/ .34" diam. – 1SPF @ 6816', 6813', 6798', 6794', 6784', 6773', 6767', 6758', 6751', 6743', 6736', 6725', 6721', 6709', 6706', 6701', 6672', 6640', 6627', 6620', 6592', 6588', 6533', 6496' = 24 Holes. Acidize w/ 10bbls 15% HCL. Frac w/ 127,750gals 70% N2 Slick/Foam, w/ 100,707# 20/40 Arizona Sand. N2:1,346,000SCF. Set CFP @ 6468'.
- Perf **UMF/Cliffhouse** w/ .34" diam. – 1 SPF @ 6427', 6422', 6404', 6372', 6355', 6337', 6333', 6329', 6325', 6317', 6309', 6305', 6294', 6291', 6287', 6276', 6272', 6264', 6228', 6214', 6210' = 21 Holes. Acidize w/ 10bbls 15% HCL. Frac w/ 126,840gals 70% N2 Slick/Foam, w/ 100,303# 20/40 Arizona Sand. Set CFP @ 6170'.
- Perf **Lewis** w/ .34" diam. 1 SPF @ 6138', 6130', 6122', 6108', 6093', 5989', 5909', 5864', 5781', 5736', 5722', 5681', 5674', 5655', 5648', 5576', 5572', 5550', 5540', 5530', 5520', 5511', 5496', 5488', 5482' = 25 Holes. Frac w/ 107,268gals 75% Visco-Elastic foam, w/ 120,266# 20/40 Arizona Sand. N2:2,120,900SCF. Start Flowback. ✓
- 10/29/2010** RIH w/ CBP set @ 5364'. RD Flowback & Frac Equip. MIRU AWS 378. ND WH. NU BOPE. PT BOPE. Test – OK.
- 11/01/2010** Tag & D/O CBP @ 5364'. Tag & D/O CFP @ 6170'. Tag & D/O CFP @ 6468'. Flowback. ✓
- 11/03/2010** Flow test MV. C/O & M/O CBP @ 6932'. Flowback.
- 11/04/2010** C/O to PBTD @ 8951'
- 11/04/2010** **Started selling DK & MV gas thru GRS.** ✓
- 11/08/2010** Run Spinner on Dakota. ✓
- 11/10/2010** RIH w/ 287jts, 2 3/8", 4.7#, L-80 tbq set @ 8858' w/ F-Nipple @ 8858'. ND BOPE. NU WH. RD RR @ 12:30hrs on 11/10/2010. ✓