

District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. <b>30-031-20611</b>
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name <b>Hospah Sand Unit</b>
8. Well Number <b>93</b>
9. OGRID Number <b>256689</b>
10. Pool name or Wildcat <b>Upper Hospah</b>

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other: **Injection Well**

2. Name of Operator  
**Nacogdoches Oil & Gas Inc.**

3. Address of Operator  
**PO Box 23418 Nacogdoches TX. 75963**

4. Well Location  
Unit Letter **C** : **2010'** feet from the **West** line and **770'** feet from the **North** line  
Section **1** Township **17N** Range **9W** NMPM **McKinley** County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
**6954' GR**

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: **Supplemental**

PERFORM REMEDIAL WORK X PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Work over proposal to repair holes in 5.5" Casing. Sand off perforations from TD to 1530'. Run in hole With 2.5" bailer, dump 2 sks., Class B cement on top of sand. Let cement set for 12 hrs. Tag cement. Nipple up to casing, bullhead squeeze cement through damaged casing holes. Pump cement until Hole is plugged and casing pressures up or cement is reached at surface through Braden head. Let cement set up for 48 to 72 Hrs. Pressure up on casing and MIT. Drill out cement plug and circulate sand out Clean out to TD @ 1604'. Run Tubing and Packer and perform MIT. Place back on injection to satisfy Agreed Compliance Order, work to begin on approval.

RCVD NOV 10 '10  
OIL CONS. DIV.

DIST. 3

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE 

TITLE **UP Exp**

DATE **11-10-10**

Type or print name **Mike Allen**

E-mail address: **mike.allen@nmsr.com** PHONE: **505-260-7420**

For State Use Only

Deputy Oil & Gas Inspector,  
District #3

APPROVED BY: 

TITLE

DATE **11-19-10**

