

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE

(See other In-
structions on
reverse side)

RCVD JAN 28 '11

FOR APPROVED

OMB NO. 1004-0137

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

NM-0609

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Report to lease

8. FARM OR LEASE NAME, WELL NO.

ATLANTIC A 7C

9. API WELL NO.

30-045-35101-00SI

10. FIELD AND SURFACE LOCATION

BLANCO MESAVERDE

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

OIL CONS. DIV.
Sec. 29, T31N, R10W

DIST. 3

12. COUNTY OR
PARISH

San Juan

13. STATE

New Mexico

14. PERMIT NO.

DATE ISSUED

15. DATE SPUNDED

08/17/10

16. DATE T.D. REACHED

09/15/10

17. DATE COMPL. (Ready to prod.)

01/10/11

18. ELEVATIONS (DF, RKB, RT, BR, ETC.)

GL 6085' KB 6100'

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

5721'
5249' / 5498'

21. PLUG, BACK T.D., MD & TVD

5718' / 5495'

22. IF MULTIPLE COMPL.,
HOW MANY*

N/A

23. INTERVALS
DRILLED BY

ROTARY TOOLS

CABLE TOOLS

yes

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

Blanco Mesaverde 4530' - 5603'

25. WAS DIRECTIONAL
SURVEY MADE

YES

26. TYPE ELECTRIC AND OTHER LOGS RUN

GR/CBL/CCL

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8 / H-40	32.3#	233'	12 1/4"	Surface, 76sx(122cf-22bbbls)	6bbbls
7" / J-55	23#	3609'	8 3/4"	Surface, 472sx(958cf-171bbbls)	40bbbls
4 1/2" / L-80	11.6#	5719'	6 1/4"	TOC@3296', 156sx(319cf-57bbbls)	

29. LINER RECORD				30. TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)
					2 3/8"	5514'
					4.7# / L-80	

31. PERFORATION RECORD (Interval, size and number)	32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.
Point Lookout w/ .34" diam. 1SPF @ 4950' - 5603' = 22 Holes UMF/Ciffhouse w/ .34" diam. 1SPF @ 4530' - 4895' = 23 Holes MV Total Holes = 45 ✓	4950' - 5603' Acidize w/ 10bbbls 15% HCL. Frac w/ 120,848gals 70% N2 SlickFoam w/ 40,196# of 20/40 Arizona Sand. Pumped 80bbbls Fluid flush. N2:1,088,200SCF. 4530' - 4895' Frac w/ 108,920gals 70% N2 SlickFoam w/ 37,855# of 20/40 Arizona Sand. Pumped 24bbbls & 28,200SCF Foramed bbbls flush. N2:1,023,600SCF.

33. PRODUCTION	34. TEST
DATE FIRST PRODUCTION 01/05/11 GRS ✓	PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) FLOWING ✓
DATE OF TEST 01/10/11 ✓	WELL STATUS (Producing or shut-in) SI ✓
HOURS TESTED 1hr.	CHOKE SIZE 2"
CHOKE SIZE 2"	PROD'N FOR TEST PERIOD 0
CHOKE SIZE 2"	OIL-BBL 0
CHOKE SIZE 2"	GAS-MCF 43 mcf / h
CHOKE SIZE 2"	WATER-BBL trace / bwph
CHOKE SIZE 2"	GAS-OIL RATIO ✓
CHOKE SIZE 2"	WATER-BBL 3.0 / bwph
CHOKE SIZE 2"	OIL GRAVITY-API (CORR.) ✓

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold	TEST WITNESSED BY
--	-------------------

35. LIST OF ATTACHMENTS This is going to be a Blanco Mesa Verde stand-alone.	
---	--

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Marilyn J. Javallo TITLE Staff Regulatory Technician DATE 01/14/11

(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

ACCEPTED FOR RECORD
JAN 26 2011
FARMINGTON FIELD OFFICE
BY TL Salyers

API # 30-045-35101		Atlantic A 7C			
Ojo Alamo	1416'	1538'	White, cr-gr ss.	Ojo Alamo	1416'
Kirtland	1538'	2562'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	1538'
Fruitland	2562'	2993'	Dk gry-gr carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	2562'
Pictured Cliffs	2993'	3170'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	2993'
Lewis	3170'	3727'	Shale w/siltstone stringers	Lewis	3170'
Huerfanito Bentonite	3727'	4070'	White, waxy chalky bentonite	Huerfanito Bent.	3727'
Chacra	4070'	4524'	Gry fn grn silty, glauconitic sd stone w/drk gry shale	Chacra	4070'
Mesa Verde	4524'	4842'	Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	4524'
Menefee	4842'	5263'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	4842'
Point Lookout	5263'	5718'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Point Lookout	5263'
Mancos	n/a	n/a	Dark gry carb sh.	Mancos	n/a
Gallup	n/a	n/a	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg. interbed sh	Gallup	n/a
Greenhorn	n/a	n/a	Highly calc gry sh w/thin lmst.	Greenhorn	n/a
Graneros	n/a	n/a	Dk gry shale, fossil & carb w/pyrite incl.	Graneros	n/a
Dakota	n/a	n/a	Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay Y shale breaks	Dakota	n/a
Morrison	'	'	Interbed grn, brn & red waxy sh & fine to coarse grn ss	Morrison	'