

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

RECEIVED

Sundry Notices and Reports on Wells

JAN 24 20111. Type of Well
GAS2. Name of Operator
BURLINGTON
RESOURCES OIL & GAS COMPANY LP3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Surface: Unit J (NWSE), 1491' FSL & 1559' FEL, Section 27, T30N, R7W, NMPM

BHL: Unit H (SENE), 2550' FNL & 710' FEL, Section 27, T30N, R7W, NMPM

6. Lease Number
SF-0793837. If Indian, All. or
Tribe Name7. Unit Agreement Name
San Juan 30-6 Unit8. Well Name & Number
San Juan 30-6 Unit 97M

9. API Well No.

30-039-30944

10. Field and Pool

Blanco MV / Basin DK

11. County and State
Rio Arriba, NM**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

Type of Submission

Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - ☐ Casing Report☒ Subsequent Report☐ Recompletion☐ New Construction☐ Plugging☐ Non-Routine Fracturing☐ Final Abandonment☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection**13. Describe Proposed or Completed Operations**

1/02/2011 MIRU AWS 730. NU BOPE. PT csg to 600#/30min @ 06:00hrs on 1/03/11. Test - OK. RIH w/ 8 3/4" bit. Tag cmt @ 198' & D/O cmt to 237'.
 1/08/2011 Drilled ahead w/ 8 3/4" bit to 4763' - Inter TD reached 1/08/11. Circ hole & RIH w/ 112jts, 7", 23#, J-55 LT&C csg set @ 4750' w/ ST @ 3588'.
 1/09/11 RU to cmt. 1st Stage - Pre-flush w/ 10bbbs GW, 2bbbs FW. Pumped scavenger 19sx(56cf-10bbbs) Premium Lite w/ 3% CaCl, .25pps celloflake, 5pps LCM-1, .4% FL-52, 8% bentonite & .4% SMS. Lead w/ 66sx(141cf-25bbbs) Premium Lite w/ 3% CaCl, .25pps celloflake, 5pps LCM-1, .4% FL-52, 8% bentonite & .4% SMS. Tail w/ 102sx(141cf-25bbbs) Type III cmt w/ 1% CaCl, .25pps celloflake & .2% FL-52. Drop plug & displaced w/ 185bbbs FW. Plug down. Bump plug. Open ST & circ. 5bbbs cmt to surface. 2nd Stage - Pre-flush w/ 10bbbs FW, 10bbbs GW, 10bbbs FW. Pumped scavenger 19sx(56cf-10bbbs) Premium Lite w/ 3% CaCl, .25pps celloflake, 5pps LCM-1, .4% FL-52, 8% bentonite & .4% SMS. Lead w/ 456sx(971cf-173bbbs) Premium Lite w/ 3% CaCl, .25pps celloflake, 5pps LCM-1, .4% FL-52, 8% bentonite & .4% SMS. Drop plug & displaced w/ 141bbbs FW. Plug down. Bump plug & close ST. Circ. 50bbbs cmt to surface. Plug down @ 22:58hrs. on 1/09/11. RD cmt. WOC. ✓
 1/10/2011 RIH w/ 6 1/4" bit. Drill out ST @ 3588'. PT 7" csg to 1500#/30min @ 20:30hrs on 1/10/11. Test - OK. Drilled ahead w/ 6 1/4" bit to 8601' (TD) TD reached 1/13/11. Circ hole & RIH w/ 201jts, 4 1/2", 11/6#, L-80 BTC set @ 8600'. 1/13/11 RU to cmt. Pre-flush w/ 10bbbs CW, 2bbbs FW. Pumped scavenger 9sx(28cf-5bbbs) Premium Lite HS FM, .25pps celloflake, .3% CD-32, 6.25pps LCM-1 & 1% FL-52. Tail w/ 265sx(525cf-93bbbs) Premium Lite HS FM, .25pps celloflake, .3% CD-32, 6.25pps LCM-1 & 1% FL-52. Drop plug & displaced w/ 134bbbs FW. Bump plug. Plug down @ 01:30hrs on 1/14/11. RD cmt. WOC. ND BOPE. NU WH. RD RR @ 06:00hrs on 1/14/11. ✓
 PT will be conducted by Completion Rig. Results & TOC will appear on next report. ✓

14. I hereby certify that the foregoing is true and correct.Signed Dollie L. Busse Dollie L. Busse Title Staff Regulatory Technician Date 1-24-11

(This space for Federal or State Office use)

APPROVED BY _____

Title

CONDITION OF APPROVAL, if any:

NMOCD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

