Form 3160-5 (August 2007)

UNITED STATES

DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OMB NO. 1004-0137 Expires July 31, 2010 5. Lease Serial No.

FORM APPROVED

SUNDRY NOTICES	JICARILLA 98				
Do not use this form for abandoned well. Use For	6. If Indian, Allottee or Tribe Name JICARILLA APACHE				
SUBMIT IN TRIPLICA	TE - Other instructions on page 2-10	7. If Unit or CA/Agreement, Name and/or No.			
Type of Well Oil Well X Gas Well Other 2. Name of Operator	FEB 03 2011	8. Well Name and No. JICARILLA 98 2B			
ENERGEN RESOURCES CORPORATION 3a. Address	Sureau of and Managemen. 3b. Phone No. (include area code)	9. API Well No. 30-039-27308			
2010 Afton Place, Farmington, NM 8 4. Location of Well (Footage, Sec., T., R., M., or Survey I 2200 FSL, 660 FEL, Sec. 19, T26N, R	Description)	10. Field and Pool, or Exploratory Area BLANCO 11. County or Parish, State Rio Arriba NM			
12. CHECK APPROPRIATI	E BOX(ES) TO INDICATE NATURE OF NOTICE, RI	EPORT, OR OTHER DATA			
TYPE OF SUBMISSION	TYPE OF ACTION				
X Notice of Intent Subsequent Report Final Abandonment Notice	Alter Casing Fracture Treat Reclar Casing Repair New Construction Reco	mation Water Shut-Off Well Integrity mplete X Other PC PayAdd morarily Abandon and Downhole r Disposal Commingle			
If the proposal is to deepen directionally or recomp Attach the Bond under which the work will be per following completion of the involved operations. I testing has been completed. Final Abandonment N determined that the final site is ready for final insper		e vertical depths of all pertinent markers and zones. ed subsequent reports shall be filed within 30 days n a new interval, a Form 3160-4 shall be filed once mation, have been completed, and the operator has			
	ne PC to the Jicarilla 98 #2B as per the at ngled per the approved order #R-13347.	og 101121314757673			



.0771		<u></u>
14. I hereby certify that the foregoing is true and correct Name (Printed Typed) Martin Cabrera Ti	ide District Engineer	
Signature	ate 02/01/11	
THIS SPACE FOR FEDERAL	OR STATE OFFICE USE	
Approved by Original Signed: Stephen Mason	Title	Date FEB 0 4 2011
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office	

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Energen Resources Corp. Pay Add Schedule – Jicarilla 98 2B API# 30-039-27308 DP#3120312B AFE# SJ11-105

Location: 2200' FSL, 660' FEL, Section 19, T 26 N, R 03 W, Rio Arriba Co., N.M.

Field: Blanco Mesaverde Elevation: 7026' TD: 6293'

PBTD: 6277'

KB: 12'

Cemented:

Consultant:

Casing Record:	<u>Csg. Size</u> 9-5/8" 7" 4-1/2"	Wt. & Gra 32# H-40 20# J-55 10.5# K-)	Depth Set 228' 4099' 3944'-6292'	Cement 150 sks 600 sks 300 sks	TOC Surface TS @ 610' TOC @ 3944'
Formation Tops:	Ojo Ala Kirtlan Fruitlar Picture	d	3135' 3400' 3464' 3681'	Mer	vis fhouse nefee nt Lookout	3850' 5175' 5400' 5834'

Logging Record: GR TEMP HRI SPECDEN DUAL SPACEDNEUT, MRIL. CCL

Existing Perforations MV:

5797',99,5803',05,07,17,19,21,42,44,46,50,52,55,57,59,62,64,66,72,74,76,80,82,84,96,5900',04,06,08,56,5 8,76,78,94,96,6011',13,36,38,71, - 6074' w/43 holes w/1 JSPF (point lookout)

Recommended Completion Procedure:

- 1. MIRU WSU NUBOP. POOH production tubing.
- 2. TIH W/ RBP and set right below PC formation. Load the casing with clean 2% KCL W/ Biocide. Pressure Test Casing to desired specifications (80% yield press). Note: A packer may be required to isolate the wellhead from pressure. NU Frac Head/Valve assembly.
- 3. MIRU WL. TIH & perforate the PC formation per the selected interval.

Perforate Pictured Cliffs: 3690'-94', 3708'-38'

- 4. Pump the Breakdown schedule per the attached Halliburton procedure.
- 5. Fracture the PC per the attached Halliburton procedure. Note: The Max treating pressure will be 80% yield press. Maximum rate to be limited to 30 BPM (total rate) to ensure we stay within our target zone. Will frac w/ 20/40 sand.
- 6. TIH w/ tubing and POOH w/ RBP.

- 7. Cleanout to PBTD w/ air mist, TOH TIH w/ Prod. Tubing and land tubing.
- 8. NDBOP NUWH RDMO WSU. Turn the well over to production.