

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0135
Expires January 31, 2004

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

1. Lease Serial No.

NM 01806

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.
N.M.

8. Well Name and No.

Prowler #2

9. API Well No.

30-039-24116

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

Rio Arriba, NM

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

McElvain Oil & Gas Properties, Inc.

3a. Address

1050 17th Street #1800 Denver, CO 80265

3b. Phone No. (include area code)

303-893-0933

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

910' FNL & 1705' FEL Sec. 5 T25N R2W NMPM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="radio"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="radio"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="radio"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input checked="" type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompletable horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletable in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

A CIBP was set at 8110' and capped via dump bailer with 50' of cement.

A CIBP was set at 7040' and capped via dump bailer with 50' of cement.

The casing was perforated with two squeeze holes at 6250'. A retainer was set at 6220'. The well was cemented with 40 sx Class B cement to isolate the annular space 6250'-6085'. A CBL was run to confirm a successful squeeze.

The Mesaverde was recompleted as per the attached sheet, ON DATE 1/22/04

14. I hereby certify that the foregoing is true and correct

Name (Printed/Typed)

John D. Steuble

Title Engineering Manager

Signature

John D. Steuble

Date January 30, 2004

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

/s/ Adam M. Salameh

Division of Multi-Resources

Date FEB 13 2004

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)

PROWLER #2 Mesaverde Recompletion

Perforate 6063'-6095' (28 holes)

Acidize with 2500 gallons 15% HCl

Acidize with 12,500 gallons 60 quality foamed 15% HCl

Set CIBP at 6060' and capped with 12' cement via dump bailer

Perforate 5937'-6011' (24 holes)

Acidize with 1500 gallons 15% HCl

Frac with 1046 bbls slick water, 1290770 scf Nitrogen and 46000# 20/40 sand

Set composite Bridge Plug at 5915' and capped with 25' cement via dump bailer

Perforate 5765'-5776' (22 holes)

Acidize with 1500 gallons 15% HCl

Perforate 5658'-5692' (34 holes)

Acidize with 1500 gallons 15% HCl

Frac with 867 bbls slick water, 1045000 scf Nitrogen and 86140# 20/40 sand

Perforate 5604'-5612' (16 holes)

Acidize with 500 gallons 15% HCl

Frac with 339 bbls slick water, 508787 scf Nitrogen and 20000# 20/40 sand