

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

1. Type of Well <input type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other: COAL BED METHANE		5. Lease Serial No. NMSF078426
2. Name of Operator CONOCOPHILLIPS COMPANY		6. If Indian, Allottee or Tribe Name
3a. Address 5525 HIGHWAY 64 FARMINGTON, NM 87401		7. If Unit or CA/Agreement, Name and/or No. NMMN78416E
3b. Phone No. (include area code) Ph: 505.599.3454 Fx: 505-599-3442		8. Well Name and No. SAN JUAN 29-6 UNIT 208A
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Sec 17 T29N R6W SWNW 1700FNL 1300FWL 36.72829 N Lat, 107.49031 W Lon		9. API Well No. 30-039-27540-00-X1
		10. Field and Pool, or Exploratory BASIN FRUITLAND COAL
		11. County or Parish, and State RIO ARRIBA COUNTY, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Deepen
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Fracture Treat
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Plug and Abandon
	<input type="checkbox"/> Plug Back
	<input type="checkbox"/> Production (Start/Resume)
	<input type="checkbox"/> Reclamation
	<input type="checkbox"/> Recomplete
	<input type="checkbox"/> Temporarily Abandon
	<input type="checkbox"/> Water Disposal
	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Well Integrity
	<input checked="" type="checkbox"/> Other Well Spud

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

SPUD REPORT

2/9/04 MIRU Key #49 Spud 12-1/4" hole @ 0000 hrs 2/10/04. Drilled to 245'. Circ. hole. RIH w/9-5/8", 32.3#, H-40 casing and set @ 235'. RU Schlumberger to cement. Pumped a preflush of 30 bbls FW w/dye in last 10 bbls. Pumped 150 sx 174 cf - 31 bbl slurry) Class G cement w/2% CaCl₂, .25#/sx Cellophane. Dropped wiper plug and displaced plug w/14 bbls FW. Bumped plug w/400 psi. Circ. 15 bbls good cement to surface. RD Schlumberger. WOC. NU WH & BOP. PT - OK. PT blind rams, choke line valves & casing to 300 psi - 3 min. and 1000 psi for 30 minutes. Good test.

