

**OCD CATHODIC PROTECTION DEEPWELL GROUND BED REPORT
DATA SHEET: NORTHWESTERN NEW MEXICO**

SUBMIT 2 COPIES TO O.C.D. AZTEC OFFICE

OPERATOR: ConocoPhillips CO.
FARMINGTON, NM 87401
PHONE: 599-3400

LOCATION INFORMATION

API Number 3003930866
WELL NAME OR PIPELINE SERVED: SJ 29-7 #75M LEGAL LOCATION: G Sec 32 T29 R7 INSTALLATION DATE: 112611
PPCO. RECTIFIER NO.: 295W ADDITIONAL WELLS: 75E & 560 & 75
TYPE OF LEASE: Private Land LEASE NUMBER: FEE

GROUND BED INFORMATION

TOTAL DEPTH: 300' CASING DIAMETER: 8" TYPE OF CASING: Sch 40 CASING DEPTH: 20' CASING CEMENTED: ☐
TOP ANODE DEPTH: 107' BOTTOM ANODE DEPTH: 275'
ANODE DEPTHS: 275, 263, 251, 239, 227, 215, 203, 191, 179, 167, 155, 143, 131, 119, 107
AMOUNT OF COKE: 75 Bags 50# Bags


WATER INFORMATION

WATER DEPTH (1): 180' WATER DEPTH (2): N/A
GAS DEPTH: N/A CEMENT PLUGS: N/A

OTHER INFORMATION

TOP OF VENT PERFORATIONS: 200' VENT PIPE DEPTH: 300'

REMARKS:



IF ANY OF THE ABOVE DATA IS UNAVAILABLE, PLEASE INDICATE SO. COPIES OF ALL LOGS, INCLUDING DRILLERS LOGS, WATER ANALYSIS, AND WELL BORE SCHEMATICS SHOULD BE SUBMITTED WHEN AVAILABLE. UNPLUGGED UNABANDONED WELLS ARE TO BE INCLUDED.

*- LAND TYPE MAY BE SHOWN: F-FEDERAL; I-INDIAN; S-STATE; P-FEE
IF FEDERAL OR INDIAN, ADD LEASE NUMBER.

Wednesday, Nov

COMPANY:	Conoco Phillips	DATE:	1/26/2011	CASING:	sch 40
COMPANY REP.:	Randy Smith	DIA. HOLE:	7 7/8	DIAMETER:	8"
LOCATION:	SAN JUAN 29-7 #75M	DEPTH:	300'	CASING DEPTH:	20'
JOB NO.:	140712	COKE TYPE:	sw	# OF ANODES:	15
FOREMAN:	Ron Luna	# OF COKE:	75	ANODE TYPE:	2284Z
DRILLER:	Darrel Ferrier	# OF BENTONITE:	N/A	ANODE LEAD:	hmwpe #8

RECTIFIER MFG:	n/a
MODEL:	n/a
SERIAL #:	n/a
V-DC:	n/a
A-DC:	n/a

WELL LOG											ANODE PLACEMENT			
DEPTH FT.	DRILLERS LOG - TYPE	SOIL	VOLTS	AMPS	COMMENTS / ANODE #	SOIL TYPE	VOLTS	AMPS	COMMENTS / ANODE #	ANODE NO.	ANODE DEPTH	AMPS W/O COKE	AMPS W/ COKE	
0	CASING					GREY SANDSTONE WET		2.40		1	275	1.10	2.70	
5	CASING					GREY SANDSTONE WET		2.10		2	263	1.20	2.10	
10	CASING					GREY SANDSTONE WET		2.10		3	251	1.20	2.30	
15	CASING					GREY SANDSTONE WET		2.10		4	239	1.20	2.60	
20	CASING					GREY SANDSTONE WET		2.20		5	227	1.30	2.50	
25	BROWN DIRT STICKY					GREY SANDSTONE WET		2.30		6	215	2.30	3.70	
30	BROWN DIRT STICKY					GREY SANDSTONE WET		2.40		7	203	1.10	1.90	
35	BROWN DIRT STICKY					GREY SANDSTONE WET		2.10		8	191	1.00	2.00	
40	BROWN DIRT STICKY					GREY SANDSTONE WET		2.10		9	179	1.20	2.30	
45	BROWN DIRT STICKY					GREY SANDSTONE WET		2.10		10	167	2.20	4.00	
50	BROWN DIRT STICKY					GREY SANDSTONE WET		2.10		11	155	3.20	6.40	
55	BROWN DIRT STICKY									12	143	3.70	7.40	
60	BROWN DIRT STICKY									13	131	3.70	8.00	
65	BROWN DIRT STICKY									14	119	3.00	7.50	
70	BROWN DIRT STICKY									15	107	1.60	5.10	
75	BROWN DIRT STICKY									16				
80	BROWN DIRT STICKY			1.10						17				
85	BROWN DIRT STICKY			2.20						18				
90	BROWN DIRT STICKY			2.20						19				
95	BROWN DIRT STICKY			1.40						20				
100	BROWN DIRT STICKY			1.10						21				
105	TAN SANDSTONE			1.50						22				
110	TAN SANDSTONE			2.00						23				
115	TAN SANDSTONE			2.90						24				
120	TAN SANDSTONE			2.70						25				
125	GREY SANDSTONE			3.30						GROUNDBED RESISTANCE				
130	GREY SANDSTONE			3.50						TOTAL VOLTS: 14.30				
135	GREY SANDSTONE			3.20						TOTAL AMPS: 21.70				
140	GREY SANDSTONE			3.00										
145	GREY SANDSTONE			3.40										
150	GREY SANDSTONE			3.10										
155	GREY SANDSTONE			2.80										
160	GREY SANDSTONE			3.40										
165	GREY SANDSTONE			3.00										
170	GREY SANDSTONE			2.60										
175	GREY SANDSTONE			2.20										
180	GREY SANDSTONE			1.10										
185	GREY SANDSTONE			1.10										
190	GREY SANDSTONE			1.10										
195	GREY SANDSTONE			1.10										
200	GREY SANDSTONE			1.20										
205	GREY SANDSTONE WET			2.60										
210	GREY SANDSTONE WET			2.70										
215	GREY SANDSTONE WET			1.50										
220	GREY SABDSTONE WET			1.40										
225	GREY SANDSTONE WET			1.40										
230	GREY SANDSTONE WET			1.30										
235	GREY SANDSTONE WET			1.30										
240	GREY SANDSTONE WET			1.30										
245	GREY SANDSTONE WET			1.40										