

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

MAR 22 2011

Sundry Notices and Reports on Wells

Farmington Field Office
Bureau of Land Management

1. Type of Well
GAS

6. Lease Number
SF-078945
If Indian, All. or
Tribe Name

2. Name of Operator
BURLINGTON
RESOURCES OIL & GAS COMPANY LP


7. Unit Agreement Name
SAN JUAN 29-7 UNIT

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. Well Name & Number
SAN JUAN 29-7 UNIT 84B

4. Location of Well, Footage, Sec., T, R, M
Surface: Unit A (NE/NE), 1020' FNL & 1045' FEL, Section 1, T29N, R7W, NMPM
Bottomhole: Unit G (SW/NE), 1930' FNL & 1930' FEL, Section 1, T29N, R7W, NMPM

9. API Well No.
30-039-30868
10. Field and Pool
BLANCO MV / BASIN DK
11. County and State
Rio Arriba, NM



MC

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Table with columns: Type of Submission, Type of Action, and checkboxes for various actions like Abandonment, Recompletion, etc.

13. Describe Proposed or Completed Operations

03/01/11 MIRU AWS 711. NU BOPE. PT csg to 600#/30min @ 11:45hrs on 03/01/11. Test - OK.
RIH w/ 8 3/4" bit. Tag cmt @ 197' & DO cmt @ 239'. Lost all rtns @ 3925'. Mix & Pumped down backside w/ 120bbls 50Vis, 30% . Drilled to 4292' - Inter TD reached 03/04/11. Circ. hole & RIH w/ 100jts, 7", 23# J-55 LT&C set @ 4263' w/ ST @ 3351'. 1st Stage - Pre-flushed w/ 10 bbls GW, 2 bbls FW. Pumped scavenger w/ 19sx(57cf-10bbls=3.02yld.) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Lead w/ 36sx(77cf-14bbls=2.13yld.) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Tail w/ 99sx(137cf-24bbls=1.38yld.) Type III cement w/ 1% CaCl, 0.25 pps celloflake, & 0.2% FL-52. Dropped plug & displaced w/ 50bbls FW & 116bbls MW. Bump plug. Plug down @ 10:00hrs 03/11/11. Open ST & Circ. 18bbls cmt to surface. WOC. 2nd Stage - Pre-flush w/ 10 bbls FW, 10bbls GW, 10bbls FW. Pumped scavenger w/ 19sx(57cf-10bbls=3.02yld.) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Lead w/ 388sx(826cf-147bbls=2.13yld.) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Dropped Plug & Displaced w/ 132bbls of FW. Bump plug & close ST. No cmt to surface. Plug down @ 12:29hrs on 03/11/11. WOC. RD cmt. Ran temp. survey, TOC @ 400'.
03/12/11 TIH w/ 6 1/4" bit. Tag cmt @ 3340' & D/O ST @ 3351'. PT 7" csg to 1500#/30min @ 08:00hrs on 03/12/11. Test -OK. Drilled w/ 6 1/4" bit to 8460' TD reached 03/15/11. Circ. hole & RIH w/ 197jts(BTC 11jts & LTC 186jts), 4 1/2", 11.6#, L-80 set @ 8442', RU to cmt. Pre-flushed w/ 10bbls GW & 2bbls FW. Pumped scavenger 9sx(28cf -5bbls=3.10yld.) Premium lite HS FM, 0.25pps celloflake, 0.3% CD-32, 6.25pps LCM-1, & 1%FL-52. Tail w/298sx(590cf-105bbls=1.98yld.) Premium lite HS FM, 0.25 pps celloflake. 0.3% CD-32, 6.25pps LCM-1 & 1% FL-52. Dropped plug & displaced w/ 131bbls FW. Bumped plug. Plug down @ 14:20hrs on 03/16/11. RD cmt. WOC. ND BOPE. NU WH. RD RR @ 06:00hrs on 03/17/11.

PT will be conducted by Drilling Rig. Results & TOC will appear on next report.

14. I hereby certify that the foregoing is true and correct.

Signed Marie E. Jaramillo Title Staff Regulatory Technician Date 03/21/11


(This space for Federal or State Office use)

APPROVED BY Title

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD



PC