Form 3160-5 *(December 1989)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

SUNDRY NOTICES AND REPORTS ON WELF

Do not use this form for proposals to drill, deepen or reentry to a different reservoir

	 /*** \	::,	

FORM APPROVED Budget Bureau No. 1004-0135 Expires: September 30, 1990

Lease Designation and Serial No.

| 5SF-079010

If Indian, Allottee or Tribe Name

	11 37		0 11/-11 17
SUBM	IIT IN TRIPLICATE		
			7. If Unit
Use "APPL	LICATION FOR PERMIT" fo	or such proposals' 🕖	A

or CA, Agmt. Design.: Northeast Blanco Unit

8. Well Name and No .: 1. Type of Well: oil well gas well X N.E.B.U. 71A 2. Name of Operator: Devon Energy Production Co., L.P. 9. API Well No.: 3300 N. Butler Avenue, Suite 211, Farmington, NM 87401 3. Address of Operator: 30-045-30668 4. Location of Well: (Footage, Sec., T., R., M., or Survey Description) Field & Pool/Exploratory Area:

1395' FSL, 665' FEL - Section 23, T31N, R7W

Blanco Mesaverde/Basin Dakota

11. County or Parish, State:

			San Juan, New Mexcio		
12.	CHECK APPROPRIATE BOX(s) TO I	CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA			
	TYPE OF SUBMISSION	TYPE OF AC	TION		
X	X Notice of Intent	Abandonment	Change of Plans		
		Recompletion	New Construction		
	Subsequent Report	Plugging Back	Non-Routine Fracturing		
		Casing Repair	Water Shut-Off		
	Final Abandonment Notice	Altering Casing	Conversion to Injection		
		X Other: MV Compl	etion		
		(Note: Report results of multiple completion on Well			
		Completion or Recompletion Report and Log form.)			

13. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Devon proposes to the following work:

- 1. MIRU service unit. NDWH, NUBOPE.
- 2. TOOH with tubing.
- 3. Set CIBP, isolating the existing Dakota completion and test to 4400 psi.
- 4. Run cement evaluation log to identify the top of the foamed cement.
- 5. Perforate Point Lookout intervals.
- 6. Frac Point Lookout interval with 100,000 gal slickwater and 100,000 pounds sand.
- 7. Set plug isolating the Point Lookout completion.
- 8. Perforate Menefee and Cliffhouse intervals.
- 9. Frac Menefee and Cliffhouse intervals with 100,000 gal slickwater and 100,000 pounds sand.
- 10. Set plug isolating the Menefee and Cliffhouse completions.
- 11. Perforate Lewis interval.
- 12. Frac Lewis intervals with 70 quality N2 foam and 200,000 pounds sand.
- 13. Drill out all Mesa Verde plugs and flow well to clean up and establish initial produciton rate.

false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

- 14. Drill out Dakota CIBP.
- 15. Run production tubing, and connect well to gas sales line.
- 16. Return well to production as a downhole commingled Mesa Verde Dakota producer.



14. I hereby certify that the foregoing is true : Signed:	CHUCK FREIER 505-324-0033	Title: Company Representative	Date: <u>12/3/2002</u>
(This space for Federal or State o Original Signed: Steph	ffice use)		TOUR FEW FUR RECEST
Approved by	Title	Date _	12/4/02
Conditions of approval, if any:			1 DEC 0 4 2002
Title 18 U.S.C. Section 1001, makes it a	crime for any person kno	wingly and willfully to make to any der	partment or agency or the Wolfd States any