Form 3160-5 (August 1999)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires Inovember 30, 2000

5: Lease Serial No.

SUNDRY NOTICES AND REPORTS ON Do not use this form for proposals to drill abandoned well. Use Form 3160-3 (APD) for s	l or reenter an	SF-047039-A 6-17 Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE – Other instructi		Tylf Unit or CA/Agreement, Name and/or No.
Type of Well Oil Well Gas Well Other		8. Well Name and No.
2. Name of Operator		Kutz Government #9S
Breck Operating Company		9. API Well No.
3a. Address 3b.	· · · · · · · · · · · · · · · · · · ·	30-045-31742
	05-327-4892	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		Basin Fruitland Coal
2560' FSL and 1980" FWL, Section 20, T28N, R10W	, <u> </u>	11. County or Parish, State
Report Pressure Te	st only)	San Juan
TYPE OF SUBMISSION	TYPE OF ACTI	ON
Notice of Intent Acidize		iction (Start/Resume) Water Shut-Off
Alter Casing		mation Well Integrity
Subsequent Report Casing Repair	New Construction Reco	mplete Other
Change Plans  Final Abandonment Notice  Convert to Injection	_ ·	orarily Abandon r Disposal
13. Describe Proposed or Completed Operations (clearly state all pertinent deta If the proposal is to deepen directionally or recomplete horizontally, gives Attach the Bond under which the work will be performed or provide the Following completion of the involved operations. If the operation results in Testing has been completed. Final Abandonment Notices shall be filed or determined that the site is ready for final inspection.)	us, including estimated starting date ubsurface locations and measured an Bond No. on file with BLM/BIA. R is a multiple completion or recompleting after all requirements, including	of any proposed work and approximate duration the con- i true vertical depths of all pertinent markers and zones, equired subsequent reports shall be filed within 30 days on in a new interval, a Form 3160-4 shall be filed once reclamation, have been completed, and the operator has
11/10/03 Spud surface hole. Drilled to 130'. Ran 3 jts.(126.75") of 7", 23#, LT&C casing and set at 132' KB.  Cemented with 75 sx (89Cu.ft.) of Cl "B" with 3% CaCl 2 and 1/4#/sk celloflake. Circulated 5.0 bbls of good		
cement to surface. Pressure test to 600 psi.		
11/1503 Ran 49 jts. (2149.95') of 4-1/2", 10.5#, J-55, ST& Cemented with 190 sx (397 cu.ft.) of Cl "B" 2% econolite c by 100 sx (123 cu.ft.) of Cl "B" with 1/4#/sk celloflake and Cement top is 209' by temperature survey.	ement with 1/4#sk celloflake o	nd 5#/sk gilsonite, followed
14. I hereby certify that the foregoing is true and correct		
Name (Printed/Typed) Paul Thompson	Title	Engineer/Agent
Signature	Date	Engineer/Agent
This space for FEDERAL OR STATE USE  January 13, 2004  THIS SPACE FOR FEDERAL OR STATE USE		
Approved by	Title	Date
Conditions of approval, if any, are attached. Approval of this notice does not wat certify that the applicant holds legal or equitable title to those rights in the subject which would entitle the applicant to conduct operations thereon.		

Title 18 U.S.C. Section 1001, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.