

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-045-31151
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator XTO Energy Inc.		6. State Oil & Gas Lease No.
3. Address of Operator 2700 Farmington Ave., Bldg. K. Ste 1 Farmington, NM 87401		7. Lease Name or Unit Agreement Name: STATE GAS COM BP
4. Well Location Unit Letter I : 2430 feet from the SOUTH line and 760 feet from the EAST line Section 32 Township 29N Range 09W NMPM County SAN JUAN		8. Well No. #1F
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 6107' GR		9. Pool name or Wildcat BLANCO MESAVERDE / BASIN DAKOTA

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐


SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Spudded 12-1/4" hole @ 9:30 p.m., 12/9/02. TIH w/8 joints 9-5/8", 36#, J-55, ST&C surface casing to 324.07' KB. Cemented casing w/225 sx Class "B" cement w/2% CaCl2 & 1/4#/sx celloflake (mixed @ 15.6 ppg, 1.18 cuft/sx). Circulated 23 bbls cmt to surf. PT BOP's & surface casing to 1,000 psig for 30 minutes. Held OK.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jeff Patton TITLE DRILLING ENGINEER DATE 12/11/02

Type or print name JEFF PATTON Telephone No. 505-324-1090

(This space for State use)

APPROVED BY Charles H. L. TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 5 DATE DEC 12 2002

Conditions of approval, if any: