

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells


API # (assigned by OCD)
30-031-05089
5. Lease Number
Fee
6. State Oil & Gas Lease #
Fee
7. Lease Name/Unit Name
Walker Dome
8. Well No.
#2
9. Pool Name or Wildcat
10. Elevation:

1. Type of Well
Oil

2. Name of Operator
Elmer L. White

3. Address & Phone No. of Operator
C/O NMOCD, 1000 Rio Brazos Road, Aztec, NM 87410

4. Location of Well, Footage, Sec., T, R, M
Sec 19, T-16-N, R-9-W, NMPM, McKinley County
Unit D, 415' FNL and 1040' FWL



Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

This well was plugged under NMOCD Contract #00-521-25-205 per attached work report.

SIGNATURE

William F. Clark, President, A-Plus Well

January 8, 2001

(This space for State Use)

Approved by _____ Title _____

JAN - 8 2001
Date _____

A - PLUS WELL SERVICE

P.O. BOX 1979 • FARMINGTON, NM 87499

505-325-2627 • FAX (505) 325-1211

Rig No #1 Elmer White Date Multiple
 Well No Wellbore #2 Location D-19-16W Company Nerdline

FROM	TO	DESCRIPTION OF OPERATION
		<u>Oct 2000 - No tubing in well.</u>
<u>11-1-00</u>		<u>R-D wireline. T/H + SET 4 1/2" Plug well CIBP @ 755'. POOH. R-D wireline. Bruce Martin w/AMOCO on LOC. R.W + S.S</u>
<u>THU 11-16-00</u>		<u>R-D CADD + P-T #104. T/H with coiled TBG + TAG CIBP @ 755'. LOAD The Hole + circulate clean with 8 BBLs water. TRY to test CSG, CSG would not test. Pumping in to holes @ 1/4 BPM @ 800'. Plug #1 mix + Pump 24 SKS ^{15.6"} cement, from 755' to TOC @ 439'. POOH with TBG to 250'. Circulate the Hole. POOH. R-D equip man. Henry Villanueva w/AMOCO on LOC.</u>
<u>MON 11-20-00</u>		<u>T/H with wireline + TAG TOC @ 439'. Pull up Hole + Perforate 2-HSC Holes @ 125'. POOH. Henry Villanueva w/AMOCO on LOC.</u>
<u>Tue 11-21-00</u>		<u>BREAK circulation out the B-H with 8 BBLs water. Plug #2 mix + Pump 28 SKS ^{15.6"} cement from 125' with good cement. Returns out the B-H. Henry Villanueva w/AMOCO on LOC.</u>
<u>Fri 12-1-00</u>		<u>CUT OFF Well Head. INSTALL MARKER with 5 SKS cement. All for the marker 4 1/2" CSG DOWN 2' + SURFACE CSG Full</u>
		<u>Dec 2000 - No equipment on location</u>

Fuel & Motor Oil _____ Water Hauled _____
 Rental Equipment _____ Cement Retainers _____
 Cementing P-#1-24 SKS P-#2-28 SKS MARKER 5 SKS - 57 SKS
 Wireline 4 1/2" CIBP/POD 750' 2-HSC Holes @ 125' (b.c. - 60 SKS)

CREW	NAME	UNIT #	MILEAGE	HOURS
Supervisor	<u>R. Whiteley</u>			
Operator	<u>S. STUART</u>			
Helper				
Helper				
Helper				