

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

30-031-20132

5a. Indicate Type of Lease	State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.		

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)


1. CIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <u>Dry Hole</u>	7. Unit Agreement Name
2. Name of Operator <u>James C. Vandiver</u>	8. Farm or Lease Name <u>Judi</u>
3. Address of Operator <u>P.O. Box 202, Farmington, New Mexico 87401</u>	9. Well No. <u>No. 1</u>
4. Location of Well UNIT LETTER <u>I</u> , <u>2310</u> FEET FROM THE <u>South</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>5</u> TOWNSHIP <u>15N</u> RANGE <u>6W</u> NMPM.	10. Field and Pool, or Wildcat <u>Wildcat</u>
15. Elevation (Show whether DF, RT, GR, etc.) <u>Gr. 6515</u>	12. County <u>McKinley</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to TD 653' on 12/23/69 and placed cement plugs as follows:

Topped Gallup at 510'. Cut two faults at 375' and 563' without reaching Hospah or Dakota formations.  
Placed cement plug at bottom from 603'- 653' TD, 50' plug.  
Placed 15' surface casing plug and erected 4" steel dry-hole Marker.  
Covered pits, cleaned and leveled location.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED James C. Vandiver TITLE Operator DATE 2/18/70  
APPROVED BY Cumy Ames TITLE Sgt. Pitt DATE 7-30-70  
CONDITIONS OF APPROVAL, IF ANY: