

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM-8270

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER P & A Well

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
Suite 1200 Lincoln Tower Bldg., Denver, Colo. 80203

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
330' F/SL and 3630' F/WL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hospah

9. WELL NO.

45

10. FIELD AND POOL, OR WILDCAT

Lone Pine Dakota "D"11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 12, T-17-N, R-9-W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7096 GR

12. COUNTY OR PARISH

McKinley

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☒
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well spudded 4-14-71 w/12-1/4" hole and drilled to TD of 76', Ran
2 jts of 8-5/8" 24# Landed at 76', cemented with 40 sacks circulated.
Tested casing and BOP to 1000 psi, held O.K. Drilled out with 7-7/8"
hole to TD of 2850', Logged and all zones tested dry. We propose
to P & A as follows:

Depth		No. sacks cement
From	To	
2850	2600	75
2100	1700	100
120	surface	40

Install Dry hole marker & clean location

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Sr. Production ClerkDATE 4-21-71

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

