

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other2. NAME OF OPERATOR
Tenneco Oil Company3. ADDRESS OF OPERATOR
720 So. Colo. Blvd., Denver, CO. 802224. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 785' FNL & 1775' FWL, Unit C
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☒
☐
☐
☐
(other) Deepen well in Lower
Hospah Formation5. LEASE
NM-12335

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Hospah9. WELL NO.
4710. FIELD OR WILDCAT NAME
South Hospah, Lower Sand11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 12, T-17-N, R-9-W12. COUNTY OR PARISH
McKinley13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
7051' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/21/79 - 5/26/79

MIRUPU. Installed BOP. Drilled 6 1/4" hole from 1663' (old T.D.) to new T.D. @ 1780'. Ran electric logs. Ran 184' 4 1/2", 10.5#, J-55 csg w/liner and set @ 1778' w/top of liner @ 1594'. Cemented w/20 bbls mud flush, 35 Sx class "A" cement w/2% CACL, slurry volume 7.35 bbl @ 15.6#/gal, 1.18 cu ft/Sx. Circulated cement. WOC 12 hrs. Pressure tstd liner to 600 psi for 30 min- held ok. Ran electric logs. Perforated the Lower Hospah formation from 1640' - 1670' w/4 JSPF. Acidized w/1155 gal 15% MCA Acid. Well went on vacuum. RDMOPU. Ran submersible pump & set @ 1575'. Returned well to production.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Carley Totten

TITLE Admin. Supervisor

DATE

6/7/79

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Nymoc



Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

UPO: 1076 O - 214-149