

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	/
LAND OFFICE	/
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Colorado Plateau Geological Services, Inc.	8. Farm or Lease Name Santa Fe Pacific
3. Address of Operator P. O. Box 537; Farmington, New Mexico 87401	9. Well No. No. 1
4. Location of Well UNIT LETTER P 165' FEET FROM THE South LINE AND 965 FEET FROM THE East LINE, SECTION 21 TOWNSHIP 20N RANGE 9W NMPM.	10. Field and Pool, or Wildcat Chaco Wash Mesaverde
15. Elevation (Show whether DF, RT, GR, etc.)	12. County McKinley

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 2/5/75. Drilled 6½ hole to 500'. Cored 311 - 323'. Cut 12'. Recovered 2 feet oil sand. Plugged back 350' to 300' w/10 sx cement. Reamed hole from surface to 316' w/6 3/4" bit. Ran 9 Jts (306') 4½", 10.50# used casing. Cemented with 25 sx regular cement above cement basket @ 306'. Left open hole 306' - 316'. Pressure tested casing to 400 PSI for 15 minutes. Held o.k. Drilled out plug and shoe. Ran 10 joints (306.6') 2 3/8" EUE tubing. Swabbed well. Ran downhole pump and 5/8" rods. Waiting on pumping, unit, tank and electricity to test and complete.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mark E. Weidner TITLE Consulting Petroleum Geologist DATE 3/12/75
Mark E. Weidner

Original Signed by Emery C. Arnold SUPERVISOR DIST. #3 DATE MAR 21 1975
APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY: