

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
BASIN FUELS, LTD.

3. ADDRESS OF OPERATOR 87401
Suite 300, 300 W. Arrington, Farmington, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL and 2310' FEL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drill 6 3/4" hole to TD 2780'. Open hole logs and mud logger indicate well to be non-commercial. Plugged and abandoned well as follows:

Plug #1	30 sacks class "B" cement	2655-2755'
Plug #2	30 sacks class "B" cement	1550-1650'
Plug #3	30 sacks class "B" cement	345- 445'
Plug #4	35 sacks class "B" cement	0- 75'

Well Plugged and abandoned 5:30 PM, 04/23/79. Install dry hole marker. Fenced pits. Will restore location to BIA and USGS specifications as soon as practical.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

AGENT

DATE April 25, 1979

APPROVED BY
CONDITIONS OF APPROVAL

APPROVED
FEB 10 1982
For JAMES F. SIMS
DISTRICT ENGINEER

TITLE

DATE

*See Instructions on Reverse Side

