

This form is to be filed with the appropriate District Office of the Commission not later than 26 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in triplicate except on state land, where six copies are required. See Rule 1165.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout <u>470'</u>	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos <u>500'</u>	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup <u>Hospah 728'</u>	T. Ignacio Qizte _____
T. Glorieta _____	T. McKee _____	T. Big Gallup <u>800'</u>	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota <u>1635'</u>	T. _____
T. Blinberry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto <u>2950'</u>	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada <u>3000'</u>	T. _____
T. Abo _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from <u>728</u> to <u>740</u>	No. 4, from _____ to _____
No. 2, from _____ to _____	No. 5, from _____ to _____
No. 3, from _____ to _____	No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from <u>800</u> to <u>900</u> feet	<u>Heavy drilling mud in hole</u>
No. 2, from _____ to _____ feet	_____
No. 3, from _____ to _____ feet	_____
No. 4, from _____ to _____ feet	_____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	470	470	surface sds and sh				
470	492	22	Point Lookout (Dalton)				
492	728	236	sd and sh				
728	760	12	Hospah Sand				
740	800	40	Shale				
800	900	100	Gallup Sand				
900	1630	730	Greenhorn				
1630	2030	400	Dakota				
2030	2950	920	Morrison				
2950	3000	50	Todilto				
3000	3060	60	Entrada TD				