

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR
DAKOTA RESOURCES, INC.

3. ADDRESS OF OPERATOR C/o Walsh Engr. & Prod. Co.
P.O. Box 254 Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660'FNL, 660'FEL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
NM-15843-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Jeffrey Federal 30

9. WELL NO.
41

10. FIELD OR WILDCAT NAME
Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 30-T17N-R9W

12. COUNTY OR PARISH
McKinley

13. STATE
New Mexico

14. API NO.
30-031-20727

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6988'G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/11/81 Spud Well

9/11/81 Ran 3 joints 8-5/8", 24.0 lb., K-55 casing (121.83') set at 133.83' with 100 sacks Class "B" cement with 3% Calcium Chloride and 1/4 lb. Flocele per sack. Cement circulated. Pressure test with 500 psig. Test ok.

9/18/81 2632'. Ran 65 joints 4-1/2", 11.60, K-55 casing (2620') set at 2630' with :

Cement with 125 sacks 65-35 Pozmix with 12% Gel and 6-1/4 lbs. Gilsonite per sack, followed by 450 sacks 50-50 Pozmix (2% Gel) with 6-1/4 lbs. Gilsonite and 6 lbs. salt per sack. Cement circulated to surface.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

FOR: DAKOTA RESOURCES, INC.

18. I hereby certify that the foregoing is true and correct

ORIGINAL SIGNED BY

SIGNED

EWELL N. WALSH

TITLE

President, Walsh

DATE

9/29/81

Ewell N. Walsh, PE

Engr. & Prod. Corp.

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMCCC