

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved
Budget Bureau No. 1004-0-3
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR
Geo Engineering, Inc.

3. ADDRESS OF OPERATOR
P.O. Box 2966, Santa Fe, New Mexico 87501

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
**1650 FNL, 340 FEL, sec 30, T20N, R9W
McKinley County, New Mexico**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
6450 G.L.

5. LEASE DESIGNATION AND SERIAL NO.
NM-254488

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N.A.

7. UNIT AGREEMENT NAME
N.A.

8. FARM OR LEASE NAME
Federal "A"

9. WELL NO.
3

10. FIELD AND POOL, OR WILDCAT
Blackeye MV

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SENE sec 30, T20N R9W

12. COUNTY OR PARISH
McKinley

13. STATE
N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud well on 3-24-85, set 120' of 7" csq with 35 cu. Ft. of cement. Cement Circulated to surface. Set/ 2000 psi W.P. B.O.P, WOC 18 hrs. Pressure test csq and BOP @ 500 psi For 30 minutes, held OK. Resume drilling on 3-26-85 with 6 3/4" bit to T.D. ~~Set~~ Set 4 1/2" csq. @ 1050 Feet and cemented with 250 cu. Ft. of Class C Cement. Cement circulated to surface. Will perf. well and test the week of April 15, 1985.

MAY 03 1985
OIL & GAS
DIST. 8

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Petroleum Engineer

DATE

4-9-85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

MAY 03 1985

FARMINGTON RESOURCE AREA

*See Instructions on Reverse Side

NMOC