Form 3160-5 June 1990) Do not use	DEPARTMENT BUREAU OF SUNDRY NOTICES this form for proposals to di	TED STATES IT OF THE INTERIOR LAND MANAGEMENT  AND REPORTS ON WELLS  III or to deepen or reentry to a different reservoir. R PERMIT—" for such proposals 22 File 15	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993  5. Lease Designation and Serial No. NWNM94825  6. If Indian, Allottee or Tribe Name
	SUBMIT	7. If Unit or CA, Agreement Designation	
1. Type of Well Oil Well 2. Name of Opera	Gas Well X Other Dry hol	8. Well Name and No.	
3. Address and T	High Plains Petr	Red Dog Federal #1	
		30-031-20983  10. Field and Pool, or Exploratory Area	
3860 Carlock Dr., Boulder, CO 80303 303-494-4529  4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  370' FNL & 710' FEL Sec. 10, T17N, R5W, NMPM			Wildcat-Torreon Area II. County or Parish, State McKinley County. New Mexico
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA			T, OR OTHER DATA
	PE OF SUBMISSION		
X	Notice of Intent	Abandonment	Change of Plans
	Subsequent Report	Recompletion Plugging Back	New Construction Non-Routine Fracturing
	Final Abandonment Notice	Casing Repair Altering Casing Other	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion of Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)  13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*			
Plug Well bord as follows: Set drill pipe @ 1152' & pmpd. 80 sx. std. cmt. containing 3%CaCl2, 59 sx. to set a plug across the Pt. Lookout and 50' up into the Menefee plus 30% excess. Top of cmt. 890'; pulled and laid down d.p. & collars; set @ 180' and circ. cmt. to the surface, setting a plug from 52' below surf. csg. to the surface and using 85 sx. std. cmt. containing 3% CaCl2. Approximately, 2 Bbls. circ. to the pit after pulling the remaining d.p. and topping off the 9 5/8" surface csg Fenced the pit and cleaned up the location, hauling the mud sacks, trash and a palate to the Torreon dump.			
Bore	hole Profiles from	שטונג (	CEIVED AY 1 2 1998  SON. DIV.
14. I hereby certi	fy that the foregoing is flue and correct		न्मकति° <u>पर</u>
Signed D. Signed TidePetroleum Engineer & Pres. Date Jan. 18, 1996  (This space for Federal or State office use)  SJ-Dresne W. Spencer  MAY -8 1998			
Approved by Conditions of	approval, if any:	Title	Date

b

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side